



# CIRCUIT BREAKER FINDERS

## SPEC SHEET

| CIRCUIT BREAKER FINDER SPECIFICATIONS                         |  |  |
|---|--|---|
| TRANSMITTER FEATURES  | 61-534   | 61-532  |
| CAT Rating (Safety)   | CAT II 300V  | CAT II 300V   |
| Listing   | UL 1436  | UL 1436   |
| Line Voltage  | Line Powered (120VAC)  | Line Powered (120VAC)   |
| Supply Frequency  | 47-63Hz  | 47-63Hz   |
| Weight  | 50g (approx.)  | 50g (approx.)   |
| Pulse Amplitude   | 18A (approx.) @ 120V   | 18A (approx.) @ 120V  |
| Pulse Rate  | 4mS every 17ms (@ 60Hz)  | 4mS every 17ms (@ 60Hz)   |
| Power Consumption   | 200mW max. @ 120V AC   | 200mW max. @ 120V   |
| Operating Temperature   | 32° - 122°F (0 to 50°C)  | 32° - 122°F (0 to 50°C)   |
| GFCI  | ✓  | —   |
| Polarity Indication   | ✓  | —   |
| RECEIVER FEATURES   |  |   |
| Visual and Audible Indicators                                 | ✓  | ✓   |
| Low Battery Indication  | ✓  | ✓   |
| Auto Power Off (after 10 mins. of no activity)                | ✓  | ✓   |
| Battery Type  | 9V   | 9V  |
| Weight  | 85g (w/o battery)  | 85g (w/o battery)   |
| Warranty  | 2-Year*  | 2-Year*   |
| ACCESSORIES   |  |   |
| Light Socket and 3-prong to 2-prong Adapters, Alligator Clips | TL-532A  | TL-532A   |