

PRODUCT DATA SHEET

Solder Research Kits

Solder Research Kits

At Indium Corporation, we have created a strong research and development team that has made us one of the top solder manufacturers in the world. We understand the challenges of developing viable products for today's marketplace.

One of the key hurdles in product development is being able to test a variety of options at a reasonable cost. With our Solder Research Kits, you can select various assembly solders to experiment with, and then choose the one that works best in your application.

Solder selection depends on a variety of requirements, including:

- Maximum soldering temperature
- Maximum and minimum operating temperature
- Base metal compatibility
- Tensile strength
- Corrosion resistance
- Electrical or thermal conductivity
- CTE mismatch
- Environmental concerns (i.e., Pb content)

Safety Considerations

When you are using fluxes and solders, you should be careful to avoid unsafe conditions. Always make sure your solder equipment is in good working order and that your area is well ventilated. To ensure safe working conditions, please refer to the SDS document within the product shipment, or contact our local team to receive a copy.

Reflow Temperature

When soldering, you will need to heat the solder to a temperature 20–40°C above the liquidus temperature of the alloy.

Material Cleanliness

To create a strong solder joint, the surfaces being joined need to be clean and free of oxides. Selecting the proper flux is essential in this process. The choice is based on the metallization of the surfaces being soldered, the liquidus temperature of the solder, and the application. All of the kits come with appropriate flux options for the alloys.



From One Engineer To Another®



Form No. 99603 R1

PRODUCT DATA SHEET

Solder Research Kits

Available Solder Research Kits

Wire Selector Kit

- Select either 2, 5, or 10 of our most popular alloys
- 3 feet of each selected alloy in 0.030" diameter solid wire
- Choose up to 3 of the available fluxes

Ribbon Selector Kit

- Choose either 3, 6, or 12 of our most popular alloys
- 3 feet of each selected alloy in 1.00" x 0.002" ribbon
- Choose up to 3 of the available fluxes

Paste Selector Kit

- Choose 2, 3, or 5 of our most popular indium- and bismuth-containing alloys
- Type 3 size powder
- No-clean flux
- Syringe or jar packed

Low-Temperature Pb-Free Wire Kit

- 5 solid wires containing indium or bismuth
- 3 feet of 0.030" solid wire
- 2 compatible TACFluxes

Low-Temperature Pb-Free Paste Kit

- 2 indium- or bismuth-containing alloys
- No-clean flux
- Syringe packed

Nitinol Solder Research Kit

- 2 solid wires of Indalloy®121
- 3 feet of 0.030" wire
- Flux #2 and Flux #3

Soldering to Gold Research Kit

- Choice of 3 indium-containing alloys
- 3 feet of 0.030" solid wires
- TACFlux®007 and TACFlux®012

Other Kits

Indium Plating Kit

- 1 liter indium sulfamate plating bath
- 2 indium anodes (1.00" x 0.0625" x 12")

Heat-Spring® Thermal Interface Kits

- HSD patterned Heat-Spring®
- Choice of sizes at 0.004" thick
- Pure indium or 52In/48Sn
- HSHP pattern with Sn+ is also available



See all of the options online at <https://buy.solder.com/>

This product data sheet is provided for general information only. It is not intended, and shall not be construed, to warrant or guarantee the performance of the products described which are sold subject exclusively to written warranties and limitations thereon included in product packaging and invoices. All Indium Corporation's products and solutions are designed to be commercially available unless specifically stated otherwise.

All of Indium Corporation's solder paste and preform manufacturing facilities are IATF 16949:2016 certified. Indium Corporation is an ISO 9001:2015 registered company.

Contact our engineers: askus@indium.com

Learn more: www.indium.com

ASIA +65 6268 8678 • CHINA +86 (0) 512 628 34900 • EUROPE +44 (0) 1908 580400 • USA +1 315 853 4900



©2021 Indium Corporation