

INDIUM CORPORATION OF AMERICA ®\EUROPE®\ASIA-PACIFIC® INDIUM CORPORATION (SUZHOU) ®

SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: 16-1000 THINNER

SDS Number: SDS-HG400 Revised Date: 9 SEPTEMBER 2016

Product Use: INDUSTRIAL THINNER USED IN SOLDERING APPLICATIONS

MANUFACTURER:

In America:

The Indium Corporation of America 1676 Lincoln Ave., Utica NY 13502 Information: (315) 853-4900

nswarts@indium.com

The Indium Corporation of America 80 Scott Street Elk Grove Village, Illinois 60004 (847) 439-9135

In Europe:

Indium Corporation of Europe 7 Newmarket Ct.

i Newmarket Ct.

Kingston, Milton Keynes, UK, MK 10 OAG

Information: +44 [0] 1908 580400

In Asia:

Indium Corporation of America Asia-Pacific Operations-Singapore 29 Kian Teck Avenue

Singapore 628908

Information: +65 6268-8678

EMERGENCY PHONE:

CHEMTREC 24 hrs. USA: 1 (800) 424-9300

Outside USA: +1 (703) 527-3887

In China:

Indium Corporation (Suzhou) Co., Ltd

No. 428 Xinglong Street Suzhou Industrial Park Suchun Industrial Square

Unit No. 14-C

Jiangsu Province, China 215126 Information: (86) 512-6283-4900

2. HAZARDS IDENTIFICATION

PRIMARY ROUTES OF ENTRY:

Carcinogen listed in

*Eye *Inhalation *Skin *Ingestion NTP IARC OSHA *Not Listed

GHS





Signal Word: Danger Hazard statement(s)

H225 Highly flammable liquid and vapor H319 Causes serious eye irritation H336 May cause drowsiness or dizziness

Precautionary statement(s)

P210 Keep away from heat/sparks/open flames/hot surfaces – No smoking

P233 Keep container tightly closed

P240 Ground/Bond container and receiving equipment

P241 Use explosion-proof electrical/ventilating/lightening/equipment

P242 Use only non- sparking tools

P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P270 Do not eat, drink or smoke when using this product

P273 Avoid release to the environment

P280 Wear protective gloves/protective clothing/eye protection/face protection

P362 Take off contaminated clothing and wash before reuse

P301 + P314 IF SWALLOWED: Get Medical advice/attention if you feel unwell

P302 +P352 IF ON SKIN: Wash with plenty of soap and water

P304 + 341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable

for breathing

P305 + 351 IF IN EYES: Rinse continuously with water for several minutes (15 mins)

Classification:

Flammable Liquid – Category 2 Eye irritation – Category 2A

Specific target organ toxicity- single exposure - Category 3- central nervous system

POTENTIAL HEALTH EFFECTS:

Eye Contact: Vapors may be irritating, liquid may damage eye tissue.

Ingestion: May cause persistent nausea, vomiting and abdominal pain.

Inhalation: Vapor may cause headaches and or dizziness. High concentrations may cause central nervous

system depression.

Skin Contact: Prolonged contact may cause irritation and dermatitis.

Chronic: Repeated skin contact can cause dryness.

NOTE: The Indium Corporation does not recommend, manufacture, market or endorse any of its'

products for human consumption.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Components	% wt	CAS Registry #	PEL mg/m³	TLV-TWA mg/m³	TLV-STEL mg/m³
ISOPROPANOL	100	67-63-0 (US)	980	983	1225
PROPAN-2-OL (IPA)		(EU)	-	999	1250
		(Canada)	-	983	1228
		(Singapore)	983	-	1230
		(Mexico)	-	980	1225
		(China)	-	350	700
		(Germany)	-	980	-

N.E. = Not established EU = European Exposure Limits IDLH Level 12,000 ppm (IPA)

4. FIRST AID MEASURES

Eye Contact: Hold eyelids apart and flush eyes with plenty of tepid water for at least 15 minutes. Seek medical

attention if irritation persists.

Ingestion: If patient is conscious, ONLY induce vomiting as directed by trained personnel. NEVER give

anything by mouth to an unconscious person. Seek medical attention immediately.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel.

Seek immediate medical attention.

Skin Contact: Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before

reuse. If irritation persists, obtain medical attention.

5. FIRE FIGHTING MEASURES

Flash Point: 12°C (53°F) Method: Closed Cup

Auto-ignition Temperature: 750 F

Flammable Limits: Upper: 12 ; Lower 2

Extinguishing Media: Dry chemical, CO₂ Dry sand, alcohol foam. Use extinguishers appropriate for the

surrounding fire conditions.

Special Fire Fighting

Procedures: Wear protective clothing and self- contained breathing apparatus. Use water to cool fire exposed containers. Flammable vapors may travel great distances to ignition source and flash back.

6. ACCIDENTAL RELEASE MEASURES

Spill or Leak Procedures: DO NOT allow material to enter sewer system or waterway. Wear personal protective equipment. Eliminate sources of ignition. Use non-sparking tools. Ventilate area in accordance with regulations. Dispose of following all Federal, State and Local regulations. In the EU refer to the Special Waste Regulations. Classified as a flammable liquid.

7. HANDLING AND STORAGE

Handling Keep containers tightly closed when not in use. Use care to avoid spills. Wear personal

Precautions: protective equipment.

Storage Precautions: Store product in tightly capped original containers in a cool, dry area. Keep away from sources

of ignition. Refer to product label for specific storage temperature requirements. Rotate stock

to ensure use before expiration date on the label.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Face velocity >2.1 cubic feet/minute in confined areas. Exhaust ventilation recommended when there is a potential for exposure. Heating of product requires ventilation and care when heating a flammable material.

Personal protection:

Eyes: Chemical safety glasses/goggles. Face shield/goggles for splash hazards.

Respirator: An approved or compliant marked air-purifying respirator with a fume/organic chemical

cartridge is recommended where airborne concentrations are expected to be elevated.

Skin: Compatible chemical resistant gloves. Use gloves such as nitrile, which are compatible with alcohol.

Other: Lab coat, eye-wash fountain in work area. Avoid the use of contact lenses in high fume/splash

areas.

Work/Hygienic Maintain good housekeeping. Clean up spills immediately.

Practices: Good personal hygiene is essential. Avoid eating, smoking or drinking in the work area.

Wash hands thoroughly with soap and water immediately upon leaving the work area.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Colorless liquid **Boiling Point:** 82°C (180°F)

Odor: Alcohol odor. 22ppm threshold Evaporation Rate: 2.4

Specific Gravity: 0.790 @ 60° F **pH:** Neutral

Vapor Pressure:44 mm HG @ 25 FSolubility in Water:Miscible

Vapor Density: 2.1 (air=1) % Volatiles by volume: 100

Molecular Weight: 60.1 Flash Point: 54F (12C)

Molecular Formula: C3 H8 O

10. STABILITY AND REACTIVITY

General: Stable.

Conditions to Avoid: Direct heat, open flames and storage in aluminum.

Incompatible Materials: Anhydrides, halogens, phosphorus, trichlorides, monomers, aldehydes, acids

Hazardous Decomposition /

Carbon dioxide/carbon monoxide, peroxides.

Combustion:

Hazardous Polymerization: Will not occur.

11.TOXICOLOGICAL INFORMATION

Carcinogenicity: National Toxicity Program NTP: No

Occupational Safety & Health Administration **OSHA**: No International Agency for Research on Cancer **IARC**: No

LD50: Not established. **LC50:** Not established.

NIOSH RTECS - NT8050000

Oral rat LD50 - 4396 mg/kg Dermal rat LD50 - 12800 mg/kg Dermal rabbit - 12870 mg/kg Inhalation rat - 72.6 mg/l 4 h

12. ECOLOGICAL INFORMATION

Freshwater Algae - 1000 mg/l EC50 >72h

Freshwater Fish - 1400000 ug/l LC50 96h

Water Flea - 13299 mg/l EC50 48 h

No other information is available.

13. DISPOSAL CONSIDERATION

Waste Disposal Method: Dispose of in accordance with all Federal, State and Local

environmental regulations. In Europe follow the Special Waste Regulations.

Flammable liquid classification. Recycle/reuse if possible. Empty containers should be

considered as hazardous as they contain product residues.

14. TRANSPORT INFORMATION

Transport in accordance with applicable regulations and requirements.

UN 1219, Isopropanol, 3, PG II



North America Emergency Guide Book - Guide #129

15. REGULATORY INFORMATION

The information in this Safety Data Sheet meets the requirements of the United States Occupational Safety and Health Act and regulations promulgated hereunder (29 CFR 1910.1200 ET. SEQ.).

SARA 313 Listing - 40 CFR 372.65: Only those who manufacture by the strong acid process are subject.

CERCLA: Reportable Quantity (RQ) 100 lbs.

All ingredients are listed on the EPA TSCA Inventory, listed on the Philippines Inventory of Chemicals and Chemical Substances 2000, listed on the Canadian DSL and listed under EINECS # 200-661-7.

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR).

WHMIS: Class B2 Flammable Liquid, D2B Toxic Material Causing Other Toxic Effects (eye irritation in animals).





This product has been classified in accordance with the guidelines set by the Dept. of Industrial Health of the Republic of Singapore.

This product has been classified under the Mexican regulations NOM-018-STPS-2015 and NOM-010-STPS-2014.

Malaysia:

This product has been classified in accordance with: Malaysian – OCCUPATIONAL SAFETY AND HEALTH (CLASSIFICATION, LABELING AND SAFETY DATA SHEET OF HAZARDOUS CHEMICALS) REGULATION OCTOBER 2013 – (CLASS). (GHS)

In China:

Decree No. 591: Regulations on the Control over Safety of Hazardous Chemicals GB 30000.2-29-2013, Rules for classification and labeling of chemicals. (GHS)

GB/T 16483-2008, GB/T 17517-2013

This product has been classified using the Chinese Occupational Limit for Hazardous Agents in the Workplace, GBZ2-2007.

This product is in full compliance with the RoHS European Directive regarding the use of certain hazardous substances in electrical and electronic equipment.

16. OTHER INFORMATION

HMIS Hazard Rating: Health: 2

Fire: 3 Reactivity: 0

Revised Date: 9 SEPTEMBER 2016

Prepared by: Nancy Swarts, Indium Corporation of America

Approved by: Nancy Swarts, Indium Corporation of America

The information and recommendations contained herein are, to the best of The Indium Corporation of America's knowledge and belief, accurate and reliable as of the date issued. The Indium Corporation of America does not warrant or guarantee their accuracy or reliability, and The Indium Corporation of America shall not be liable for any loss or damage arising out of the user thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.