

SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: #16-3000 THINNER

SDS Number: SDS-HG015 Revised Date: 21 DECEMBER 2018

Product Use: INDUSTRIAL USE - THINNER

MANUFACTURER:

In America: EMERGENCY PHONE:

The Indium Corporation of America®.

34 Robinson Rd., Clinton, NY 13323

CHEMTREC 24 hrs.

USA: 1 (800) 424-9300

Information: (315) 853-4900 Outside USA: +1 (703) 527-3887

nswarts@indium.com In China: Emergency 86+ 4008417580

In Europe:

The Indium Corporation of America® (European Operations)

7 Newmarket Ct

Kingston, Milton Keynes, UK, MK 10 OAG

Information: +44 [0] 1908 580400

In Asia:

Indium Corporation of America Asia-Pacific Operations-Singapore

29 Kian Teck Avenue Singapore 628908

Information: +65 6268-8678 http://www.indium.com

In China:

Indium Corporation (Suzhou), Co., Ltd.

No. 428 Xinglong Street Suzhou Industrial Park Suchun Industrial Square

Unit No. 14-C

Jiangsu Province, China 215126 Information: (86) 512-6283-4900

2. HAZARDS IDENTIFICATION

PRIMARY ROUTES OF ENTRY:

Carcinogen listed in

*Eye *Inhalation *Skin *Ingestion NTP IARC OSHA *Not Listed

GHS





Signal Word: Danger Hazard statement(s)

H225 Highly flammable liquid and vapor
 H319 Causes serious eye irritation
 H336 May cause drowsiness or dizziness

Precautionary statement(s)

P210 Keep away from heat/sparks/open flames/hot surfaces – No smoking

P233 Keep container tightly closed

P240 Ground/Bond container and receiving equipment

P241 Use explosion-proof electrical/ventilating/lightening equipment

P242 Use only non-sparking tools

P243 Take precautionary measures against static discharge
P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P270 Do not eat, drink or smoke when using this product

P273 Avoid release to the environment

P280 Wear protective gloves/protective clothing/eye protection/face protection

P362 +P364 Take off contaminated clothing and wash before reuse

P301 + P314 IF SWALLOWED: Get medical advice/attention if you feel unwell

P302 +P352 IF ON SKIN: Wash with plenty of soap and water

P304 + 341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable

for breathing

P305 + 351 IF IN EYES: Rinse continuously with water for several minutes (15 mins)

Classification

Flammable Liquid- Category 2 Eye irritation- Category 2A

Specific target organ toxicity- single exposure - Category 3, central nervous system

POTENTIAL HEALTH EFFECTS:

Eye Contact: Vapors may be irritating, liquid may damage eye tissue.

Ingestion: May cause irritation.

Inhalation: Vapor may cause headaches and or dizziness. May cause irritation.

Skin Contact: Prolonged contact may cause irritation.

Chronic: Not established.

NOTE: The Indium Corporation does not recommend, manufacture, market or endorse any of its

products for human consumption.

3. COMPOSITION / INFORMATION ON INGREDIENTS						
Components	% wt	CAS Registry #	PEL mg/m³	TLV-TWA mg/m³	TLV-STEL mg/m³	
ISOPROPANOL	97-98	67-63-0/200-661-7 (US)	980	983	1225	
PROPAN-2-OL		(EU)	-	999	1250	
		(Canada)	-	983	1228	
		(Singapore)	983	-	1230	
		(Mexico)	-	980	1225	
		(China)	-	350	700	
PROPRIETARY	2-3		N.E.	N.E.	N.E.	
N.E. = Not established						

4. FIRST AID MEASURES

Eye Contact: Hold eyelids apart and flush eyes with plenty of tepid water for at least 15 minutes. Seek medical

attention if irritation persists.

Ingestion: If patient is conscious, ONLY induce vomiting as directed by trained personnel. NEVER give

anything by mouth to an unconscious person. Seek medical attention immediately.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel.

Seek immediate medical attention.

Skin Contact: Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before

reuse. If irritation persists, obtain medical attention.

5. FIRE FIGHTING MEASURES

Flash Point: 12°C (53°F) Method: Closed Cup

Auto-ignition Temperature: N/A

Flammable Limits: Upper: 12 @77°F; Lower 2 @ 77°F

Extinguishing Media: Dry chemical, Water or CO₂. Use extinguishers appropriate for the surrounding fire

conditions.

Special Fire Fighting

Procedures: Wear protective clothing and self - contained breathing apparatus. Use water to cool fire

exposed containers. Flammable vapors may travel great distances to ignition source and flash back.

6. ACCIDENTAL RELEASE MEASURES

Spill or Leak Procedures: DO NOT allow material to enter sewer system or waterway. Wear personal protective equipment. Eliminate sources of ignition. Ventilate area in accordance with regulations. Dispose of following all Federal, State and Local regulations. In the EU refer to the Special Waste Regulations.

7. HANDLING AND STORAGE

Handling Keep containers tightly closed when not in use. Use care to avoid spills. Wear personal

Precautions: protective equipment. Ground containers from static charge.

Storage Precautions: Store product in tightly capped original containers in a cool, dry area. Refer to product

label for specific storage temperature requirements. Rotate stock to ensure use before

expiration date on the label.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Face velocity >2.1 cubic feet/minute in confined areas. Exhaust ventilation recommended.

Personal protection:

Eyes: Chemical safety glasses/goggles. Face shield for splash hazards.

Respirator: An approved or compliant marked air-purifying respirator with a fume/organic chemical

cartridge is recommended where airborne concentrations are expected to be elevated.

Skin: Compatible chemical resistant gloves. Use gloves such as nitrile, which are compatible with alcohols

and lower pH chemicals. Other gloves: butyl rubber, viton and 4H.

Other: Lab coat, eye-wash fountain in work area. Avoid the use of contact lenses in high fume areas.

Work/Hygienic Maintain good housekeeping. Clean up spills immediately. Bond/ground containers. **Practices:** Good personal hygiene is essential. Avoid eating, smoking or drinking in the work area. Wash hands thoroughly with soap and water immediately upon leaving the work area.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Colorless Boiling Point: 82°C (180°F)

Odor:Alcohol odor.Evaporation Rate:2.4Specific Gravity:0.790 @ 60° FpH:NeutralVapor Pressure:90 mm HG @100 FSolubility in Water:Soluble

Vapor Density: 2.1 (air=1) % Volatiles by volume: 100

Flash Point: 12C (53F)

Shelf Life= 2 Years. Please consult the product container for manufacture date and shelf date.

10. STABILITY AND REACTIVITY

General: Stable.

Conditions to Avoid: Direct heat, open flames and storage in aluminum.

Incompatible Materials: Anhydrides, halogens, phosphorus, trichlorides, monomers, aldehydes

Hazardous Decomposition /

Combustion:

Carbon dioxide/carbon monoxide.

Hazardous Polymerization: Will not occur.

11.TOXICOLOGICAL INFORMATION

Carcinogenicity: National Toxicity Program NTP: No

Occupational Safety & Health Administration **OSHA**: No International Agency for Research on Cancer **IARC**: No

LD50: Not established. **LC50:** Not established.

12. ECOLOGICAL INFORMATION

Product not tested.

13. DISPOSAL CONSIDERATION

Waste Disposal Method: Dispose of in accordance with all Federal, State and Local

environmental regulations.

14. TRANSPORT INFORMATION

Transport in accordance with applicable international regulations and requirements.

UN 1219, Isopropanol, 3, PG II (mixture)



North America Emergency Guide Book - Guide #129

Flammable Liquid

15. REGULATORY INFORMATION

The information in this Safety Data Sheet meets the requirements of the United States Occupational Safety and Health Act and regulations promulgated hereunder (29 CFR 1910.1200 ET. SEQ.).

SARA 313 Listing - 40 CFR 372.65: None

All ingredients are listed on the EPA TSCA Inventory.

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR).

WHMIS: Canadian WHMIS: Class B Division 2 Flammable, D2B Toxic Material Causing Other Toxic Effects (eye irritation in animals).





This product has been classified in accordance with the guidelines set by the Dept of Industrial Health of the Republic of Singapore.

This product has been classified under the Mexican regulations NOM-018-STPS-2015 and NOM-010-STPS-2014.

Malaysia:

This product has been classified in accordance with: Malaysian – OCCUPATIONAL SAFETY AND HEALTH (CLASSIFICATION, LABELING AND SAFETY DATA SHEET OF HAZARDOUS CHEMICALS) REGULATION OCTOBER 2013 – (CLASS).

Regulatory Information China:

GB/T 16483-2008, GB/T 17519-2013, Safety Data Sheets for Chemical Products

GB 30000.2-29-2013, Rules for classification and labeling of chemicals (GHS)

Decree No. 591: Regulations on the Control Over Safety of Hazardous Chemicals.

This product has been classified using the Chinese Occupational Limit for Hazardous Agents in the Workplace, GBZ2-2007.

This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or any other reproductive harm.

16. OTHER INFORMATION

HMIS Hazard Rating: Health: 2

Fire: 3 Reactivity: 0

Revised Date: 21 DECEMBER 2018

Prepared by: Nancy Swarts, Indium Corporation of America

Approved by: Nancy Swarts, Indium Corporation of America

The information and recommendations contained herein are, to the best of The Indium Corporation of America's knowledge and belief, accurate and reliable as of the date issued. The Indium Corporation of America does not warrant or guarantee their accuracy or reliability, and The Indium Corporation of America shall not be liable for any loss or damage arising out of the user thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.