No. 428 Xinglong Street

Jiangsu Province, China 215126

Information: (86) 512-6283-4900

Suzhou Industrial Park Suchun Industrial Square

Unit No. 14-C



SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: WAVE SOLDER FLUX #3590-TX

SDS-HG007 **SDS Number: Revised Date:** 22 JUNE 2018

Industrial Use - Wave Solder Flux **Product Use:**

MANUFACTURER:

EMERGENCY PHONE: In America:

The Indium Corporation of America®. **CHEMTREC 24 hrs.** 34 Robinson Rd., Clinton, NY 13323 USA: 1 (800) 424-9300

Information: (315) 853-4900 Outside USA: +1 (703) 527-3887

nswarts@indium.com

In Europe:

The Indium Corporation of America® (European Operations) In China: Indium Corporation (Suzhou), Co., Ltd.

7 Newmarket Ct

Kingston, Milton Keynes, UK, MK 10 OAG

Information: +44 [0] 1908 580400

In Asia:

Indium Corporation of America®

Asia-Pacific Operations-Singapore

29 Kian Teck Avenue Singapore 628908

Information: +65 6268-8678 http://www.indium.com

Page 1 of 6

2. HAZARDS IDENTIFICATION

PRIMARY ROUTES OF ENTRY:

Carcinogen listed in

⊗Eye ⊗Inhalation ⊗Skin ⊗Ingestion NTP IARC OSHA ⊗Not Listed

GHS:





Signal Word: Danger

Hazard Statement(s):

H225 Highly Flammable liquid and vapor
 H319 Causes serious eye irritation
 H336 May cause drowsiness or dizziness

Precautionary statement(s)

P210 Keep away from heat/sparks/open flames/hot surfaces. – No smoking

P233 Keep container tightly closed

P240 Ground container and receiving equipment

P242 Use spark resistant tools

P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P270 Do not eat, drink or smoke when using this product

P273 Avoid release to the environment

P280 Wear protective gloves/protective clothing/eye protection/face protection

P362 +P364 Take off contaminated clothing and wash before reuse

P301 + P314 IF SWALLOWED: Get Medical advice/attention if you feel unwell

P302 +P352 IF ON SKIN: Wash with plenty of soap and water

P304 + P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable

for breathing

P305 +P351 IF IN EYES: Rinse continuously with water for several minutes (15 mins)

.....

Classification:

Isopropyl alcohol:

Flammable Liquid - Category 2

Serious eye damage/eye irritant - Category 2

Specific target organ systemic toxicity (single exposure) - Category 3 Central Nervous system

POTENTIAL HEALTH EFFECTS:

Eye Contact: Vapors may be irritating, liquid may damage eye tissue.

Ingestion: May cause persistent nausea, vomiting and abdominal pain.

Inhalation: Vapor may cause headaches and or dizziness. Irritating to respiratory tract

Skin Contact: Prolonged contact may cause irritation and dermatitis.

Chronic: Not established.

NOTE: The Indium Corporation does not recommend, manufacture, market or endorse any of it's

products for human consumption.

WARNING: This product can expose you to chemicals including [trace amounts of 1,4 dioxane] which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

3. COMPOSITION / INFORMATION ON INGREDIENTS						
Components	% wt	CAS Registry #	PEL mg/m³	TLV-TWA mg/m³	TLV-STEL mg/m³	
ISOPROPANOL	90-95	67-63-0 (US)	980	983	1225	
PROPAN-2-OL		(EU)	-	999	1250	
		(Canada)	-	983	1228	
		(Singapore)	983	-	1230	
		(Mexico)	-	980	1225	
		(China)	-	350	700	
PROPRIETARY	0 - 5		N.E.	N.E.	N.E.	
ORGANIC ACID	0 - 5	68603-87-2 (US)	N.E	N.E	N.E.	
N.E. = Not established EU = European Exposure Limits						

4. FIRST AID MEASURES

Eye Contact: Hold eyelids apart and flush eyes with plenty of tepid water for at least 15 minutes. Seek medical

attention if irritation persists.

Ingestion: If patient is conscious, ONLY induce vomiting as directed by trained personnel. NEVER give

anything by mouth to an unconscious person. Seek medical attention immediately.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel.

Seek immediate medical attention.

Skin Contact: Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before

reuse. If irritation persists, obtain medical attention.

5. FIRE FIGHTING MEASURES

Flash Point: 12°C (54°F) Method: Closed Cup

Auto-ignition Temperature: None

Flammable Limits: Upper: 12.7 @77°F; Lower 2 @ 77°F

Extinguishing Media: Dry chemical. Use extinguishers appropriate for the surrounding fire conditions.

Special Fire Fighting Wear protective clothing. Use water to cool fire exposed containers.

SDS - HG007 Wave Solder Flux #3590-TX

6. ACCIDENTAL RELEASE MEASURES

Spill or Leak Procedures: DO NOT allow material to enter sewer system or waterway. Wear personal protective equipment. Eliminate sources of ignition. Ventilate area in accordance with regulations. Dispose of following all Federal, State and Local regulations. In the EU refer to the Special Waste Regulations.

7. HANDLING AND STORAGE

Handling Keep containers tightly closed when not in use. Use care to avoid spills. Wear personal

Precautions: protective equipment.

Storage Precautions: Store product in tightly capped original containers in a cool, dry area. Refer to product

label for specific storage temperature requirements. Rotate stock to ensure use before

expiration date on the label.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Face velocity >2.1 cubic feet/minute in confined areas. Exhaust ventilation recommended.

Personal protection:

Eyes: Chemical safety glasses/goggles. Face shield for splash hazards.

Respirator: An authority approved or compliant marked air-purifying respirator with a fume/organic chemical

cartridge is recommended where airborne concentrations are expected to be elevated.

Skin: Compatible chemical resistant gloves. Nitrile gloves.

Other: Lab coat, eye-wash fountain in work area. Avoid the use of contact lenses in high fume/splash

areas.

Work/Hygienic Maintain good housekeeping. Clean up spills immediately.

Practices: Good personal hygiene is essential. Avoid eating, smoking or drinking in the work area.

Wash hands thoroughly with soap and water immediately upon leaving the work area.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:Liquid, clearBoiling Point:79°C (175°F)Odor:Alcohol odor.Melting Point:Not applicable

Specific Gravity: 0.815 @ 60° F **pH**: 3.2 (as is) 3.6 (1% solution)

Vapor Pressure: 33 mm HG @68°F **Solubility in Water:** Soluble

Vapor Density: 2.1(air=1)

10. STABILITY AND REACTIVITY

General: Stable.

Conditions to Avoid: Direct heat, open flames and storage in aluminum.

Incompatible Materials: Anhydrides, halogens, phosphorus, trichlorides, monomers, aldehydes

Hazardous Decomposition /

Combustion:

Carbon dioxide/carbon monoxide.

Hazardous Polymerization: Will not occur.

SDS - HG007

11.TOXICOLOGICAL INFORMATION

Carcinogenicity: NTP: No

OSHA: No IARC: No

LD50: Not established. **LC50:** Not established.

Oral LD50 (isopropyl alcohol)

LD50 Oral- rat- 5,045 mg/kg

Inhalation LC50 (isopropyl alcohol) LC50 inhalation-rat-8h-16000 ppm

Dermal LD50

LD50 – Dermal- rabbit-12,800 mg/kg

RTECS: Isopropyl alcohol NT8050000

12. ECOLOGICAL INFORMATION

Product not tested.

LC50-Pimephales promelas (fathead minnow)- 9,640 mg/l – 96h (isopropyl alcohol)

EC50-Daphnia magna (water flea) - 5,102 mg/l - 24h (isopropyl alcohol)

13. DISPOSAL CONSIDERATION

Waste Disposal Method: Dispose of in accordance with all Federal, State and Local

environmental regulations. In Europe follow the Special Waste Regulations.

14. TRANSPORT INFORMATION

Transport in accordance with applicable international regulations and requirements.

UN1219, Isopropanol, 3, PGII

FLAMMABLE 3

Flammable label North American Emergency Guide Book : Guide #129

MARINE POLLUTANT: NO

15. REGULATORY INFORMATION

The information in this Safety Data Sheet meets the requirements of the United States Occupational Safety and Health Act and regulations promulgated hereunder (29 CFR 1910.1200 ET. SEQ.).

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR).

Canadian WHMIS: Class B Division 2 Flammable, D2B Toxic Material Causing Other Toxic Effects (eye irritation in animals).





This product has been classified in accordance with the guidelines set by the Dept of Industrial Health of the Republic of Singapore.

This product has been classified under the Mexican regulations NOM-018-STPS-2015 and NOM-010-STPS-2014.

In China:

Decree No. 591: Regulations on the Control over Safety of Hazardous Chemicals GB 30000.2-29-2013, Rules for classification and labeling of chemicals. (GHS) GB/T 16483-2008, GB/T 17517-2013

Information on exposure levels in China is from regulation document GBZ2-2007 Occupational Exposure Limit for Hazardous Agents in the Workplace.

This product has been classified in accordance with: Malaysian – OCCUPATIONAL SAFETY AND HEALTH (CLASSIFICATION, LABELING AND SAFETY DATA SHEET OF HAZARDOUS CHEMICALS) REGULATION OCTOBER 2013 – (CLASS).

WARNING: This product can expose you to chemicals including [trace amounts of 1,4 dioxane] which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

SARA 313 Listing - 40 CFR 372.65: trace levels of 1, 4 Dioxane

All ingredients are listed on the EPA TSCA Inventory.

Ingredients are listed on the Canadian Domestic Substance List.

16. OTHER INFORMATION

HMIS Hazard Rating: Health: 2

Fire: 3 Reactivity: 0

Revised Date: 22 JUNE 2018

Prepared by: Nancy Swarts, Indium Corporation of America

Approved by: Nancy Swarts, Indium Corporation of America

The information and recommendations contained herein are, to the best of The Indium Corporation of America's knowledge and belief, accurate and reliable as of the date issued. The Indium Corporation of America does not warrant or guarantee their accuracy or reliability, and The Indium Corporation of America shall not be liable for any loss or damage arising out of the user thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.