SDS - IN LF013 http://www.indium.com NC-771



SAFETY DATA SHEET

Note: This SDS may be translated into an international language. If there is any misinterpretation or misunderstanding of any words or phrases that may occur within any translation the ENGLISH language shall always prevail

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: NC-771

SDS Number: SDS-IN LF013 Revised Date: 16 AUGUST 2022

Version 1.3

Product Use: Industrial Use - Liquid Flux

MANUFACTURER:

In America:

The Indium Corporation of America®.

34 Robinson Road, Clinton NY 13323

Information: (315) 853-4900 EHS_Compliance@indium.com

In United Kingdom:

The Indium Corporation of America® (European Operations)

7 Newmarket Ct.

Kingston, Milton Keynes, UK, MK 10 OAG

Information: +44 [0] 1908 580400

In Asia:

The Indium Corporation of America Asia-Pacific Operations-Singapore

29 Kian Teck Avenue Singapore 628908

Information: +65 6268-8678

In Korea:

Indium Corporation (Korea) Co., Ltd. 248-6, Songjeong-dong, Heungdeok-gu, Cheongju-si

Chungcheongbuk-do, Korea PC: 361-290

Information: +82-43-271-9823

Fax: +82-43-271-9828

In India:

Indium Solder Private Limited Shed A, NP-7 Guindy Industrial Estate, Ekkaduthangal, Chennai, Tamil Nadu, India 600032

Information: +91-044-46877888

EMERGENCY PHONE:

CHEMTREC 24 hrs. USA: 1 (800) 424-9300

Outside USA: +1 (703) 527-3887 China: Emergency 86+ 4001-204937

Malaysia: 1-800-815-308 Costa Rica: 506-40003869 Mexico: 01-800-681-9531

In China:

Indium Corporation (Suzhou), Co., Ltd. No. 428 Xinglong Street

Suzhou Industrial Park
Suchun Industrial Square

Unit No. 14-C

Jiangsu Province, China 215126 Information: (86) 512-6283-4900

2. HAZARDS IDENTIFICATION

PRIMARY ROUTES OF ENTRY:

Carcinogen listed in

☐ Eye ☐ Inhalation ☐ Skin ☐ Ingestion NTP IARC OSHA ☐ Not Listed

Classification:

Eye irritant – (Category 2A) Flammable liquids - (Category 2)

Specific target organ systemic toxicity (single exposure) – (Category 3), Central nervous system

GHS:





Signal Word: Danger

Hazard Statements:
H225 Highly Flammable liquid and vapor
H319 Causes serious eve irritation

H319 Causes serious eye irritation
H336 May cause drowsiness or dizziness

Precautionary statement(s)

P210 Keep away from heat/sparks/open flames/hot surfaces. – No smoking

P233 Keep container tightly closed

P240 Ground container and receiving equipment

H242 Use only non-sparking tools

P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P270 Do not eat, drink or smoke when using this product

P273 Avoid release to the environment

P280 Wear protective gloves/protective clothing/eye protection/face protection

P362+P364 Take off contaminated clothing and wash before reuse

P301+P314 IF SWALLOWED: Get Medical advice/attention if you feel unwell.

P302+P352 IF ON SKIN: Wash with plenty of soap and water

P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position

comfortable for breathing

P305+P351+P338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and

easy to do - continue rinsing.

POTENTIAL HEALTH EFFECTS:

Eye Contact: Irritating to the eyes and if not removed promptly, may result in serious eye injury. Do

not allow material to come in contact with the eyes.

Ingestion: May cause irritation.

Inhalation: Heated vapor concentrations may be irritating to respiratory tract. Vapors may cause drowsiness and

dizziness. Acute effects to high levels of isopropyl alcohol through inhalation are alcoholic intoxication

and narcosis.

Skin Contact: May cause skin irritation.

Chronic: Isopropyl alcohol target organs: nerves/kidneys. Otherwise not established.

Note: The Indium Corporation does not recommend, manufacture, market or endorse any of it's product's for human consumption.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Components 2-PROPANOL	% wt CAS Registry #/EINECS		PEL mg/m³	TLV-TWA mg/m³	TLV-STEL mg/m³
(ISOPROPYL ALCOHOL)	85-95	67-63-0/200-661-7			
		(US)	980	983	1230
		(EU)	N.E.	999	1250
		(Canada)	N.E.	983	1228
		(Singapore)	983	-	1230
		(Mexico)	-	980	1225
		(China)	-	350	700
POLYGLYCOL ETHER	5-15	9038-95-3	N.E.	N.E.	N.E.

N.E. = Not established EU = European Union Occupational Exposure

4. FIRST AID MEASURES

Eye Contact: Hold eyelids apart and flush eyes with plenty of tepid water for at least 15 minutes. Seek medical

attention if irritation persists.

Ingestion: If patient is conscious, ONLY induce vomiting as directed by trained personnel. NEVER give

anything by mouth to an unconscious person. Seek medical attention immediately.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration or oxygen by trained personnel.

Seek immediate medical attention.

Skin Contact: Remove contaminated clothing. Wash affected area with soap and water. Wash clothing before

reuse. If irritation persists, obtain medical attention.

5. FIRE FIGHTING MEASURES

Flash Point: 16°C(60°F) Method: Closed cup equilibrium method.

Auto-ignition Temperature: Not established.

Flammable Limits: Flammable, limits not established

Extinguishing Media: Use extinguishers appropriate for the surrounding fire conditions.

Special Fire Fighting Firefighters must wear NIOSH approved self-contained breathing apparatus and full

Procedures: protective clothing.

6. ACCIDENTAL RELEASE MEASURES

Spill or Leak Procedures: Wear a respirator and appropriate personal protection (See Exposure

Controls/Personal Protective Section). Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Do not allow to enter waterway. Keep flame away or other sources of ignition. Dispose of following all Federal, State and

Local regulations. In the EU refer to the Waste assessment rules.

7. HANDLING AND STORAGE

Handling Precautions: Keep containers tightly closed when not in use. Use care to avoid spills. Avoid breathing

vapors from heated material. Avoid contact with eyes, skin and clothing. Use with

adequate ventilation. Ground containers.

Storage Precautions: Store product in tightly capped original containers in a cool, dry area. Keep away from heat

and flame. Store away from incompatible materials. Empty containers may be hazardous as

they contain product residue. Ground containers for static protection.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Local exhaust ventilation may be necessary to control any air contaminants to within their

exposure limits during the use if thus product. Additionally, the odor threshold of isopropyl alcohol is 50 ppm and ventilation may be required to keep annoyance odors to the minimum levels. Ventilation is recommended when heating product. Use non - sparking

tools and equipment.

Personal protection:

Eyes: Chemical safety glasses/goggles. Face shield for splash hazards.

Respirator: An authority approved or compliant marked air-purifying respirator with a fume/organic chemical

cartridge is recommended under certain circumstances where airborne concentrations are expected

to be elevated.

Skin: Compatible chemical resistant gloves(nitrile). Protective outer garment, apron and sleeves as

appropriate.

Other: Eyewash fountain in work area. Avoid the use of contact lenses in high fume/splash areas.

Work/Hygienic Practices: Maintain good housekeeping. Clean up spills immediately. Avoid eating, smoking or drinking

in the work area. Wash hands thoroughly with soap and water immediately upon leaving the work area.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:Clear Liquid mixtureBoiling Point:Not applicable.Odor:Mild alcoholic odor.Melting Point:Not applicableSpecific Gravity:0.8255Flash Point:16C (60F)

Vapor Pressure: Not applicable. Solubility in Water: Soluble

Vapor Density: (air=1) Not applicable.

10. STABILITY AND REACTIVITY

General: Stable.

Conditions to Avoid: Open flame or other sources of ignition and high temperatures. Acids, halogens,

aluminum and oxidizing agents.

Hazardous Decomposition /

Combustion:

Elemental oxides

Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Carcinogenicity: NTP: No (National Toxicity Program)

OSHA: No (Occupational Safety & Health Administration) **IARC:** No (International Agency for Research on Cancer)

Oral LD50 (isopropyl alcohol) LD50 Oral- rat- 5,045 mg/kg

Inhalation LC50 (isopropyl alcohol) LC50 inhalation-rat-8h-16000 ppm

Dermal LD50

LD50 – Dermal- rabbit-12,800 mg/kg RTECS: Isopropyl alcohol NT8050000

12. ECOLOGICAL INFORMATION

Product not tested.

LC50-Pimephales promelas (fathead minnow)- 9,640 mg/l – 96h (isopropyl alcohol)

EC50-Daphnia magna (water flea) – 5,102 mg/l – 24h (isopropyl alcohol)

13. DISPOSAL CONSIDERATION

Waste Disposal Method: Dispose of in accordance with all Federal, State and Local environmental regulations.

In Europe follow the Special Waste Regulations. Recycle or dispose of as hazardous

waste.

14. TRANSPORT INFORMATION

Transport in accordance with applicable international regulations and requirements.

Shipping Name: UN1219, Isopropanol ,3, PG II

Transportation hazard Class(es):

Class 3: Flammable liquids



North American Emergency Guide Book: Guide #129

Marine Pollutant: No

Shipping small quantities: Ground ONLY

40 CFR 173.150 - Exceptions for Class 3 (Flammable Liquids). Limited quantities of flammable liquids, Class 3, are excepted from labeling requirements for ground shipment only. For Packing Group II, inner packaging not over 1.0L (0.3 gallons) net capacity each, packed in a strong outer packaging.

40 CFR 172.203 – Limited quantities- when a shipping paper is required the description for a material offered for transportation as "limited quantity" must include the words "Limited Quantity" following the basic description.

Shipping: UN 1219, Isopropanol, 3, PG II (Limited Quantity) (mixture)

Review 40 CFR for clarification and further information.

Shipping via aircraft requires compliance with the regulations and not under exceptions.

15. REGULATORY INFORMATION

The information in this Safety Data Sheet meets the requirements of the United States Occupational Safety and Health Act and regulations promulgated hereunder (29 CFR 1910.1200 ET. SEQ.).

SARA 313 Listing - 40 CFR 372.65 - None All ingredients are listed on the EPA TSCA Inventory.

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR).

Canadian WHMIS: Class B Division 2 Flammable, D2B Toxic Material Causing Other Toxic Effects (eye irritation in animals).



This product complies with the requirements under the EU Directive 2002/95/EC (RoHS).

This product has been classified in accordance with the guidelines set by the Dept. of Industrial Health of the Republic of Singapore.

This product has been classified under the Mexican regulations NOM-018-STPS-2015 and NOM-010-STPS-2014.

Malaysia:

This product has been classified in accordance with: Malaysian – OCCUPATIONAL SAFETY AND HEALTH (CLASSIFICATION, LABELING AND SAFETY DATA SHEET OF HAZARDOUS CHEMICALS) REGULATION OCTOBER 2013 – (CLASS).

Regulatory Information China:

GB/T 16483-2008, GB/T 17519-2013, Safety Data Sheets for Chemical Products GB 30000.2-29-2013, Rules for classification and labeling of chemicals (GHS)

Decree No. 591: Regulations on the Control Over Safety of Hazardous Chemicals.

This product has been classified using the Chinese Occupational Exposure Limit for Hazardous Agent in the Workplace, GBZ2-2007.

California Prop 65: This product does not contain any chemical(s) known to the State of California to cause cancer and/or birth defects (or other reproductive harm).

16. OTHER INFORMATION

HMIS Hazard Rating: Health: 2

Fire: 3

Reactivity: 0

Revised Date: 16 AUGUST 2022

Prepared by: Matthew Wojcik, Indium Corporation of America

Approved by: Matthew Wojcik, Indium Corporation of America

The information and recommendations contained herein are, to the best of The Indium Corporation of America's knowledge and belief, accurate and reliable as of the date issued. The Indium Corporation of America does not warrant or guarantee their accuracy or reliability, and The Indium Corporation of America shall not be liable for any loss or damage arising out of the user thereof. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.