

SPECIFICATION SHEET 280-EV6151V

EVOLUTION™ DELUXE 6151V STANDARD BRIM HARD HAT

- High-Density Polyethylene (HDPE) shell designed with five raised channels running across the top for strength, and an extended back area for extra protection
- 6-Point polyester textile suspension system offers unrivaled comfort without compromising performance
- Unique "3D Adjustment" provides a precise fit using harness depth settings unlike any other hard hat on the US market today
- Revolution™ Wheel Ratchet is easy to use and creates a firm comfortable fit
- Chamlon[™] sweatband
- Universal accessory slots accepts virtually any competitors' accessories
- Packed ready-to-wear with no installation of the suspension required
- Vented to reduce inside helmet temperatures
- Meets ANSI/ISEA Z89.1, Type I, Class C requirements
- Also meets the ANSI requirements for Reverse Donning and Lower Temperature

APPLICATIONS

- Construction
- · Oil & gas
- Mining
- Demolition
- High pressure jetting
- Energy companies
- Certain emergency services (FEMA & USAR)
- High-risk environments where high impact situations are of concern

CARE INSTRUCTIONS

The unit may be cleaned with soap and warm water and dried with a soft cloth. The helmet should not be cleaned with chemical or abrasive cleaners. The helmet should be stored out of direct sunlight, away from chemicals and not exposed to extremes of temperature.

TECHNICAL DATA

MATERIAL	Shell: High Density Polyethylene, Recyclable Suspension: HDPE strap & clips, polyester straps Sweatband: Egyptian cotton core with PU coating
COLOR	☐ White(-10) ☐ Yellow(-20) ☐ Gray(-40) ☐ Blue(-50) ☐ Red(-60) ☐ Bright Orange(-OR) ☐ Lime Yellow(-LY)
HAT SIZE	6 5/8 - 8 (20 7/8" - 25")
EACH WEIGHT	13.2 oz / 374.2 g
PACKAGING	10 per case
CASE	9.5" x 23" x 18" / 24.1cm x 58.4cm x 45.7cm
CASE WEIGHT	8.4 lbs / 3.8 kg
C00	UK

BARCODES

ITEM	EACH	DOZEN	CASE
☐ 280-EV6151V-10	50308428136815		05038428812030
280-EV6151V-20	05038428136822		05038428812047
■ 280-EV6151V-40	05038428814171		05038428239615
280-EV6151V-50	05038428021449		05038428813228
280-EV6151V-LY	05038428192217		05038428813785
280-EV6151V-OR	05038428018890		05038428813136



DIMENSIONS (in)

	OSFA
A	11.5 / 29.2
В	6.375 / 16.2

