



Red & Redi

Multi-Purpose Red Grease



FEATURES

- Delivers excellent lubrication
- Prevents rust, corrosion and oxidation
- Remains effective at extremely high temperatures 450°F (232°C)
- Reduces friction and vibration
- Resists shock
- Red color allows easy visual inspection
- Penetrates quickly
- Non-melting
- NLGI Grade 2
- Exceptional adhesive and cohesive properties, resists throw-off at high speeds

APPLICATIONS

- Automotive
- Aviation
- Cables
- Cams and Pistons
- Chains
- Guide Rails
- Latches
- Marine
- Open Gears
- Overhead Door Tracks
- Packaging
- Slide Conveyors

SPECIFICATIONS AND APPROVALS

- Timken Steel

PROPERTIES

Appearance/physical state	Gas/Aerosol
Odor	Mild, Solvent
Melting point/freezing point	Not applicable
Boiling point/range	158°F (-70.2°C)
Vapor pressure	2500 - 3500 mm Hg @20°C (calculated aerosol)
Partition coefficient	Not established
Percent volatile	65
Flammability limit	Flammability limit - lower (%) 1.8% Flammability limit - upper (%) 9.5%
Propellant	Petroleum Gases, Liquefied, Sweetened
VOC Content	65% per State and Federal Consumer Product Regulations
Color	Red
Flash point	> -20.2°F (> -29.0°C) (bulk liquid) estimated
Relative density	Not available
Evaporation rate	< 1 (Ethyl Ether =1)
Vapor density	2 - 3 (air = 1)
Auto-ignition temperature	Not established
Viscosity	3100 - 4000 cP (bulk liquid)
Specific Gravity (water=1)	0.77 - 0.8 @20°C
NLGI	2
Thickener Type	Clay
Timken OK Load	65 lbs
Temperature Range °F(°C)	-22°F (-30°C) to 450°F (232°C)
Dropping Point	550°F (288°C)
Load Wear Index	70
4-Ball Weld Load	>205 kg

DIRECTIONS

Shake well before using to insure proper mixing. Spray a thin film on the surface to be lubricated or protected. To apply to hard to reach areas, insert the extension tube provided into valve cap. A thickened grease will form within seconds after application.

HANDLING

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. (See Section 7 of the SDS)

STORAGE

Level 3 Aerosol. Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. (See Section 7 of the SDS)

DISPOSAL INFORMATION

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations. (See Section 13 of the SDS)

AVAILABLE PRODUCTS

US	Part No.		Net Contents	Container Type	Units/Case	Case Weight
	Canada	Europe				
05816	C05816	M05816	11 wt oz / 312 g / 451 mL	aerosol	12	12 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved