



# LCI

# Low-Odor Corrosion Inhibitor



## FEATURES

- Prevents rust and corrosion for up to 9 months outdoors and 2 years indoors
- Wax-base coating maintains flexibility after application and self-heals for long-lasting corrosion protection
- Resists dust and debris from adhering to treated surfaces
- Removable, when needed, using LPS solvent degreasers: A-151, F-104°, or PreSolve
- Low-odor formulation for improved worker comfort during application and drying
- Penetrates to displace moisture for deep protection
- Sets in as little as 5 minutes for outdoor storage and stays in place in extreme conditions
- Opaque (non-colored) film applies evenly and protects parts without impacting aesthetics

## APPLICATIONS

- For shop application to protect:
  - Heavy machinery and equipment
  - Metal machinery parts
- Fabricated metal parts

## SPECIFICATIONS AND APPROVALS

- NSF International, H2

## AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Case Weight
06122	20 oz	trigger bottle	12	18 lbs
06105	5 gal	pail	1	39 lbs
06155	55 gal	drum	1	408 lbs

## PROPERTIES

<b>Appearance / Physical State</b>	opaque / liquid
<b>Odor</b>	mild
<b>Percent Volatile</b>	69%
<b>Flammability</b>	lower: 0.7 upper: 5%
<b>VOC Content</b>	69%
<b>Color</b>	opaque white
<b>Flash Point</b>	108°F
<b>Density</b>	6.92 lbs/gal
<b>Vapor Density</b>	heavier than air
<b>Viscosity</b>	400-1200cP
<b>Specific Gravity</b>	0.83 g/mL

## DIRECTIONS

Apply on clean surface when possible. Additional applications may be added as needed. Safe to use on fabric, rubber, paint, and other finishes. Easily removed with LPS® A-151 Solvent Degreaser or F-104° Solvent Degreaser.

## HANDLING

Do not handle, store, or open near an open flame, sources of heat, or sources of ignition. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Wash hands thoroughly after handling.

## STORAGE

Store locked up. Keep away from heat, sparks, and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see section 10 of the SDS).

## DISPOSAL

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.



**CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!**

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved