



Food Grade Anti-Seize



FEATURES

- Protects against seizure, heat-freeze, galling, rust and corrosion
- Contains no metals
- Lowers friction; reduces wrench torque
- Service rating: -65°F (-54°C) to 1800°F (982°C)
- Great for food processing and food handling applications
- Non-staining, odorless
- Water resistant

APPLICATIONS

- Castors
- Chutes
- Conveyors
- Food Racks
- Guards
- Guide Rails
- Plastic Gears
- Plastic Rollers
- Pipe Fittings
- Press Fit Assemblies
- Pump Gears
- Worm Gears
- Bolts
- Bottling Machinery
- Chain Drives
- Conveyor & Oven Bearings
- Gaskets
- Motors
- Nuts
- Packaging Machinery
- Screws
- Stainless Steel Fittings
- Valve Assemblies

SPECIFICATIONS AND APPROVALS

- Canadian Food Inspection Agency
- FDA Regulation 21 CFR 178.3570 for Incidental Food Contact
- MIL-PRF-907E
- NSF International, H1

AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Approximate Case Weight
US	Canada				
06508	C06508	0.5 lb / 227 grams	container	12	8 lbs
06510	C06510	1 lb / 454 grams	container	12	15 lbs

PROPERTIES

Appearance / Physical State	Solid, Paste
Odor	Slight
Melting / Freezing Point	Not available.
Boiling Point / Range	Not available.
Vapor Pressure	Not available.
Partition Coefficient	Not available
Percent volatile	Not available
Flammability	Not available.
Propellant	N/A
VOC Content	Negligible
Color	White
Flash Point	Not available.
Density	Not available
Evaporation Rate	Not available.
Vapor density	Not available
Auto-Ignition Temperature	Not available
Viscosity	Not available
Specific Gravity	1.18 @ 20°C
Temperature Range	-65°F (-54°C) to 1800°F (982°C)
4-Ball Weld Load	Weld Point kgf: 400

DIRECTIONS

Designed for applications where incidental food contact may occur. Food Grade Anti-Seize is NSF® H1 registered. NOTE: Not for use on oxygen systems.

HANDLING

Observe good industrial hygiene practices.

STORAGE

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS)

DISPOSAL

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose in accordance with all applicable regulations.



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved