

# **Precision Clean** Aviation Grade Cleaner/Degreaser



## FEATURES

- **Dilutable Formulation**: Allows for customized product strength based on the soil level
- Dye Free & Non-Corrosive: Strong enough to remove dirt build-up, salt, hydrolic fluid, bug debris, carbon exhaust, grease and safe to use on painted and upainted aircraft exterior surfaces. Conforms to Boeing D6-17487 & SAE AMS 1526C spec for surface compatibility requirements such as paint softening, hydrogen embrittlement, sandwich corrosion.
- **Improved Appearance**: Cleaner/Degreaser revitalizes the gloss and inherent shine like a just waxed surface. Rinses clean and does not leave a dull or hazy film behind, even in hard water dilutions.
- Reduce Drag & Increase Fuel Efficiency: Specialized surfactant formula is very effective at removing a wide range of aircraft exterior soils which can increase drag and resulting fuel consumption.
- Environmentally Prefered Formula: Utilizes a biodegradable, low VOC formula which is compliant in all 50 states

## APPLICATIONS

- Aircraft Exteriors
- Leading Edges
- Engine Cowlings
- Underbellies
- Wheel Wells
- Composites
- Plastic
- Hangar Floors
- Hoists
- Tools

- Landing Gear
- Wings
- Tail Sections
- Fuselage
- Fin Stabilizers
- Fiberglass
- Rubber Surfaces
- Tanks
  - Machinery
  - Ground Service Equipment

IS (IDENTIFICATION SYSTEM)

## SPECIFICATIONS AND APPROVALS

• Boeing D6-17487 Rev. T

• AMS 1526C

# AVAILABLE PRODUCTS

Part No.	Net Contents	Container	Case Pack	Case Wt.	
Ready-to-Use					
92728	28 fl. oz. (828 mL)	Trigger	12	27 lbs.	
Concentrate					
92701	1 gal. (3.78 L)	Bottle	4	38 lbs.	
92705	5 gal. (18.93 L)	Pail	1	46 lbs.	
92755	55 gal. (208 L)	Drum	1	535 lbs.	



# **CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!** 800.241.8334 | www.lpslabs.com

©2019 ITW Pro Brands • LPS<sup>®</sup> is a registered trademark of Illinois Tool Works All Rights Reserved • TDS92728 • 190503



**Precision Clean** Aviation Grade Cleaner/Degreaser

PROPERTIES	CONCENTRATE	RTU (TRIGGER SPRAY)
Appearance/Physical State	Colorless to Light Amber/Liquid	Colorless to Light Amber/Liquid
Odor	None	None
Melting Point/Freezing Point	32°F (0°C)	32°F (0°C)
Boiling Point/Range	212°F (100°C)	212°F (100°C)
Percent Volatile	98-100%	98-100%
рН	10-11	9.5-10.5
VOC Content	1%	0%
Color	Colorless to Light Amber	Colorless to Light Amber
Flash Point	None	None
Specific Gravity (water=1)	0.95-1.05	0.95-1.05
Solubility in Water	Soluble	Soluble

### DIRECTIONS

KEEP FROM FREEZING. Mix well before using. Follow dilution chart below. Rinse and/or wipe dry any residue. Undiluted product may be used for spotcleaning hard-to-remove soils. Material compatibility: LPS® recommends testing on a small inconspicuous area or similar expendable component prior to use to assure material compatibility.

Dilution Ratio Product:				
Mix Ratio	Soil Level	Applications		
1:1 to 1:3	Heavy	Landing gear, wheel wells, underbellies, heavy carbon or grease stained areas		
1:3 to 1:9	Medium	Leading edges, engine cowlings, wheel wells, underbellies		
1:9 to 1:19	Light	Routine cleaning of aircraft exterior, hangar floors, ground service equipment, etc.		

### HANDLING

Precautions for Safe Handling: Avoid contact with skin and eyes.

Hygiene measures: Handle in accordance with good industrial hygiene and safety practice.

### STORAGE

Technical measures: Provide adequate ventilation.

Storage condition(s): Store in dry, cool, well-ventilated area; avoid freezing.

## DISPOSAL INFORMATION

Regional legislation (waste): Dispose of contents/container to comply with applicable local, national and international regulations. Waste disposal recommendations: Comply with local regulations for disposal.



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY! 800.241.8334 | www.lpslabs.com ©2019 ITW Pro Brands • LPS® is a registered trademark of Illinois Tool Works All Rights Reserved • TDS92728 • 190503