

according to WHMIS 2023 and HCS 2024

Date of issue 04/23/2025

Version number 4.00

Revision: 04/23/2025

Page 1/13

1 Identification

Product identifier

- · Trade name: 422C
 - Other Means of Identification: Silicone Conformal Coating
 Related Part Number: 422C-Aerosol, 422C-340G, 422C-445ML
- · Application of the substance / the mixture Conformal Coating
- · Uses advised against Not available

[.] Details of the supplier of the safety data sheet

Manufacturer/Supplier:

MG Chemicals (Head Office) 1210 Corporate Drive Burlington, Ontario L7L 5R6 CANADA +(1) 800-340-0772 +(1) 905-331-1396 info@mgchemicals.com

· Information department: sds@mgchemicals.com

[•] Emergency telephone number:

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents) USA or CANADA-Call Verisk 3E at +1-866-519-4752 or +1-760-476-3962 (Service access code: 335388)

For emergencies involving the transport of dangerous goods; 24/7 service CANADA-Call CANUTEC collect at +1-613-996-6666 or *666 on cellular phones

2 Hazard identification

	Flammable aerosol. Pressurized container: may burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
	H319

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms



· Signal word Warning

• Hazard-determining components of labeling: acetone

(Contd. on page 2)

CA —



Safety Data Sheet according to WHMIS 2023 and HCS 2024

Date of issue 04/23/2025

Version number 4.00

Revision: 04/23/2025

Trade name: 422C

	(Contd. of page 1)
n-butyl acetate	
[3-(2,3-epoxyprop	poxy)propyl]trimethoxysilane
 Hazard statemer 	nts
H223-H229 Flam	mable aerosol. Pressurized container: may burst if heated.
H319 Caus	es serious eye irritation.
H336 May	cause drowsiness or dizziness.
 Precautionary st 	tatements
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No
	smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing mist, vapors or spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves / eye protection.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P33	8 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P337+P313	If eye irritation persists: Get medical advice/attention.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents and container in accordance with local, regional, and national
	regulations.
ar hanarda	

· Other hazards

Warning! May displace oxygen and cause rapid suffocation. Repeated exposure may cause skin dryness or cracking.

3 Composition/Information on ingredients

[·] Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

[·] Dangerous components:		
67-64-1	acetone	32% w/w
115-10-6	dimethyl ether	30% w/w
123-86-4	n-butyl acetate	18% w/w
2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2% w/w
		CA —

(Contd. on page 3)

Page 2/13



according to WHMIS 2023 and HCS 2024

Date of issue 04/23/2025

Version number 4.00

Revision: 04/23/2025

(Contd. of page 2)

Trade name: 422C

4 First-aid measures

Description of first aid measures

• After inhalation:

Remove person to fresh air and keep comfortable for breathing.

If feeling unwell: Call a POISON CENTRE or doctor.

- After skin contact:
- Wash with plenty of water or shower.

Take off contaminated clothing and wash it before reuse.

• After eye contact:

Rinse cautiously with water for 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

- After swallowing:
- Rinse mouth.
- Do NOT induce vomiting.

If symptoms persist consult doctor.

· Information for doctor: Treat symptomatically

[•] Most important symptoms and effects, both acute and delayed

See section 11 for additional information.

[•] Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

Extinguishing media

Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use water spray to cool containers.

· Special hazards arising from the substance or mixture

Prevent fire-fighting wash from entering waterway or sewer system.

Aerosols containers may erupt with force at temperatures above 50 °C [122 °F].

• Hazardous combustion products:

Carbon Oxides (COx) Silicone oxides formaldehyde other toxic fumes

· Advice for firefighters

· Protective equipment: Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

6 Accidental release measures

• Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

— CA —

Page 3/13



Version number 4.00

Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Date of issue 04/23/2025

Trade name: 422C

Ensure adequate ventilation

Remove or keep away all sources of extreme heat or open flames. Avoid breathing mist, spray, or vapors.

· Environmental precautions: Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Collect liquid in a sealable, chemical-resistant container. Wash residue with a paper towel and place dirty towels in container. Use soap and water to remove the last traces of residue.

Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Wear protective gloves and eye protection. Wash hands and exposed skin thoroughly after handling. Take off contaminated clothing and wash it before reuse. Avoid breathing mist, spray, or vapors. Use only outdoors or in a well-ventilated area. Keep out of reach of children. Do not pierce or burn, even after use. • **Information about protection against explosions and fires:** Do not spray on a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Preservized container: protect from sunlight and do not expose to tem

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

Conditions for safe storage, including any incompatibilities

[·] Storage:

Requirements to be met by storerooms and receptacles:
 Observe official regulations on storing packagings with pressurized containers.
 Keep in a dry and clean area, away from incompatible substances
 Store in a well-ventilated place. Keep cool.
 Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep receptacle tightly sealed. Protect from heat and direct sunlight.

(Contd. on page 5)

Page 4/13

Revision: 04/23/2025

(Contd. of page 3)



according to WHMIS 2023 and HCS 2024

Date of issue 04/23/2025

Version number 4.00

Trade name: 422C

· Specific end use(s) See section 1.2

8 Exposure controls/ Personal protection

[·] Control parameters

· Components with limit values that require monitoring at the workplace:			
67-64-1 aceto	pne		
EL (Canada)	STEL: 500 ppm TWA: 250 ppm		
EV (Canada)	STEL: 750 ppm TWA: 500 ppm		
PEL (USA)	TWA: 2400 mg/m³, 1000 ppm		
REL (USA)	TWA: 590 mg/m ³ , 250 ppm		
TLV (USA)	STEL: 1187 mg/m³, 500 ppm TWA: 594 mg/m³, 250 ppm A4, BEI		
115-10-6 dim	ethyl ether		
EL (Canada)	TWA: 1000 ppm		
WEEL (USA)	TWA: 1000 ppm		
123-86-4 n-bi	ityl acetate		
EL (Canada)	STEL: 150 ppm TWA: 50 ppm		
EV (Canada)	STEL: 950 mg/m³, 200 ppm TWA: 710 mg/m³, 150 ppm		
PEL (USA)	TWA: 710 mg/m ³ , 150 ppm		
REL (USA)	STEL: 950 mg/m³, 200 ppm TWA: 710 mg/m³, 150 ppm		
TLV (USA)	STEL: 712 mg/m³, 150 ppm TWA: 238 mg/m³, 50 ppm		
· Ingred	ients with biological limit values:		
67-64-1 aceto	one		
	BEI (USA) 25 mg/L		
	Medium: urine		
	me: end of shift arameter: Acetone (nonspecific)		

· Additional information:

The lists that were valid during the creation were used as basis.

Refer to the national or regional occupational exposure limit regulation for abbreviations and acronyms.

• Exposure controls

• Appropriate engineering controls Keep airborne concentrations below exposure limits.

(Contd. on page 6) - CA —

Page 5/13

Revision: 04/23/2025

(Contd. of page 4)



according to WHMIS 2023 and HCS 2024

Date of issue 04/23/2025

Version number 4.00

Revision: 04/23/2025

Trade name: 422C

[•] Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Advice should be sought from respiratory protection specialists.

If the product is heated or worker has a known allergic reaction, consider using a full mask with organic vapor cartridge or with an independent air supply.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.



Protective gloves: EN374

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:

Safety glasses



Safety glasses or tightly sealed goggles: EN 166

9 Physical and chemical properties

[·] Information on basic physical and chemical properties

- Physical state
- · Form:
- · Color:
- · Odor:
 - · Odor threshold:
- · Melting point/Melting range:

Aerosol Liquid, in aerosol format. Clear Ester-like Not determined. Undetermined. (Contd. of page 5)

(Contd. on page 7)





according to WHMIS 2023 and HCS 2024

Date of issue 04/23/2025

Version number 4.00

Revision: 04/23/2025

Trade name: 422C

	(Contd. of page
 Boiling point/Boiling range: 	56 ℃ (132.8 °F)
· Flammability:	Flammable.
· Explosion limits:	
· Lower:	1.2 Vol %
· Upper:	18.6 Vol %
· Flash point:	-17 ℃ (1.4 ℉)
· Auto igniting:	≥200 °C (≥392 °F)
 Decomposition temperature: 	Not determined.
pH-value:	Not determined.
· Viscosity:	
· Kinematic:	Not determined.
· Dynamic:	Not determined.
[•] Solubility in / Miscibility with	
· Water:	Not miscible or difficult to mix.
 Partition coefficient (n-octanol/water): 	Not determined.
· Vapor pressure at 20 °C (68 °F):	5,200 hPa (3.900 mm Hg)
· Vapor pressure at 50 °C (122 °F):	800 hPa (600 mm Hg)
[•] Relative density at 25 °C (77 °F):	0.88
 Vapor density (air=1): 	<2.01
 Particle characteristics 	Not applicable.
· Other information	
¹ Important information on protection of health	
and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of
	explosive air/vapor mixtures are possible.
· Solvent content:	· ·
· Organic solvents:	80.00 %
 Solids content: 	18.0 %
• Evaporation rate	<1

10 Stability and reactivity

- · Reactivity No further relevant information available.
- Chemical stability Chemically stable at normal temperatures and pressures. • Thermal decomposition / conditions to be avoided:
 - No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid Temperatures above 50 °C, open flames, and incompatible substances
- **Incompatible materials:** Strong bases Strong oxidizing agents Strong reducing agents

(Contd. on page 8)



according to WHMIS 2023 and HCS 2024

Date of issue 04/23/2025

Version number 4.00

Revision: 04/23/2025

Page 8/13

Trade name: 422C

Strong acids Phosphorous oxychloride

[•] Hazardous decomposition products:

No dangerous decomposition products known. Hazardous combustion products: see section 5.

11 Toxicological information

Information on toxicological effects

• Acute toxicity:

• LD/	· LD/LC50 values that are relevant for classification:		
67-64-1 ac	etone		
Oral	LD50	5,800 mg/kg (rat)	
Dermal	LD50	>7,426 mg/kg (rabbit)	
Inhalative	LC50/ 3 h	132 mg/L (rat)	
115-10-6 c	limethyl et	iher	
Inhalative	LC50/ 4 h	308 g/m3 (rat)	
123-86-4 r	n-butyl ace	tate	
Oral	LD50	>10,768 mg/kg (rat)	
Dermal	LD50	>17,600 mg/kg (rabbit)	
Inhalative	LC50/4 h	>21 mg/L (rat)	
2530-83-8	2530-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane		
Oral	LD50	8,025 mg/kg (rat)	
Dermal	LD50	4,250 mg/kg (rabbit)	

Primary irritant effect:

• on the eye: Irritating effect.

· Sensitization: No sensitizing effects known.

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

· Carcinogenicity Based on available data, the classification criteria are not met.

• **Reproductive toxicity** Based on available data, the classification criteria are not met.

* Specific target organ toxicity - single exposure May cause drowsiness or dizziness.

· Specific target organ toxicity - repeated exposure

Based on available data, the classification criteria are not met.

• Aspiration hazard Based on available data, the classification criteria are not met.

[•] Summary of effects and symptoms by route of exposure

· Eyes:

- redness, serious irritation pain blurred vision
- · Skin: dry skin, redness

· Inhalation:

dizziness or drowsiness cough

(Contd. on page 9)

(Contd. of page 7)



sore throat headache nausea • **Swallowed:** Low toxicity: abdominal pain diarrhea

according to WHMIS 2023 and HCS 2024

Date of issue 04/23/2025

Version number 4.00

Revision: 04/23/2025

Page 9/13

Trade name: 422C

(Contd. of page 8)

nausea vomiting • Delayed and immediate effects as well as chronic effects from short and long-term exposure Prolonged or repeated exposure may defat skin and cause skin dryness and cracking, and local redness and discomfort.

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
None of the ingredients is listed.	
· NTP (National Toxicology Program)	
None of the ingredients is listed.	

12 Ecological information

[·] Toxicity

• Aquatic toxicity:

67-64-1 acetone

EC50/ 48 h 13,500 mg/L (daphnia)

LC50 96h 5,540 mg/L (trout)

123-86-4 n-butyl acetate

LC50 96h 18 mg/L (minnow)

· Persistence and degradability No further relevant information available.

· **Bioaccumulative potential** No further relevant information available.

· Mobility in soil No further relevant information available.

Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 10)



according to WHMIS 2023 and HCS 2024

Date of issue 04/23/2025

Version number 4.00

Revision: 04/23/2025

(Contd. of page 9)

Trade name: 422C

· Other adverse effects No further relevant information available.

13 Disposal considerations

[·] Waste treatment methods

• Recommendation: This material and its container must be disposed of as hazardous waste.

[•] Uncleaned packagings:

· Recommendation:

Containers may still present a chemical hazard/ danger when empty.

Dispose of contents in accordance with all local, regional, national, and international regulations. Where possible retain label warnings and SDS and observe all notices pertaining to the product.

14 Transport information · UN-Number · DOT/TDG, IMDG, IATA UN1950 · UN proper shipping name · DOT/TDG, IATA Aerosols, flammable · IMDG **AEROSOLS** · Transport hazard class(es) · DOT/TDG (Transport dangerous goods): · Class 2.1 Gases Label 2.1 · IMDG, IATA · Class 2.1 Gases · Label 2.1 Packing group · DOT/TDG, IMDG, IATA Not applicable (Contd. on page 11) - CA —

Page 10/13



according to WHMIS 2023 and HCS 2024

Date of issue 04/23/2025

Version number 4.00

Revision: 04/23/2025

Trade name: 422C

	(Contd. of page 10)
· Environmental hazards:	Not applicable.
 Transport in bulk according to Annex II MARPOL73/78 and the IBC Code 	of Not applicable.
· Transport/Additional information:	
 DOT/TDG Quantity limitations 	On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	1L Code: E0 Not permitted as Excepted Quantity
 Special precautions for user Hazard identification number (Kemler EMS Number: Stowage Code 	Not applicable. code): - F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
 Segregation Code 	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

• OSHA Hazard Communication Standard (29 CFR Part 1900) The safety data sheet and label comply with HCS 2024.

• Hazardous Products Act (R.S.C., 1985, c. H-3) The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2023.

(Contd. on page 12)

Page 11/13



Version number 4.00

Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Date of issue 04/23/2025

Trade name: 422C

(Contd. of page 11)

Revision: 04/23/2025

⁻ Sara	
· Section 355 (extremely hazardo	ous substances):
None of the ingredients is listed.	
· Section 313 (Specific toxic che	mical listings):
None of the ingredients is listed.	
• TSCA (Toxic Substances Contr	rol Act):
All components have the value ACTIVE.	
· Hazardous Air Pollutants	
None of the ingredients is listed.	
[·] Proposition 65	
. Ohemieele kneuwe te eeuse eeu	

· Chemicals known to cause cancer:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

· Carcinogenic categories

	<u> </u>	
۰T	LV (Threshold Limit Value)	
67-64-1	acetone	A4
¹ NIOSH-Ca (National Institute for Occupational Safety and Health)		
None of	the ingradients is listed	

None of the ingredients is listed.

Canadian substance listings:

· Canadian Domestic Substances List (DSL)

All ingredients are listed.

· Canadian Non-Domestic Substances List (NDSL)

None of the ingredients is listed.

· Canadian Ingredient Disclosure list (limit 0.1%)

None of the ingredients is listed.

· Canadian Ingredient Disclosure list (limit 1%)

67-64-1 acetone

123-86-4 n-butyl acetate

· HMIS-ratings (scale 0 - 4)

Health = $^{*}2$ Fire = 1 Reactivity = 0

(Contd. on page 13)





according to WHMIS 2023 and HCS 2024

Date of issue 04/23/2025

Trade name: 422C

Version number 4.00

Revision: 04/23/2025

Page 13/13

(Contd. of page 12)

· Europe

- **RoHS (Restriction of Hazardous Substances Directive)** This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, OBP, or DIBP and complies with European RoHS regulations.
- WEEE (Waste Electrical and Electronic Equipment Directive) This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Regulatory department
- · Contact: sds@mgchemicals.com
- · Version number of previous version: 3.00
- · Date of preparation 04/23/2025
- Abbreviations and acronyms:
- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation
- IATA: International Air Transport Association
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- NIOSH: National Institute for Occupational Safety
- ** Data compared to the previous version altered.

CA —