

8349TFM-B

(PART B)

Safety Data Sheet

Section 1: Identification

Product Identifier and Other Means of Identification

Product Identifier: 8349TFM-B**Other Means of Identification:** Thermal Adhesive**Related Part #** 8349TFM-25ML, 8349TFM-45ML, 8349TFM-50ML, 8349TFM-200ML

Recommended Use and Restriction on Use

Use: Thermally conductive adhesive hardener**Uses Advised Against:** Not for use as a spray coating

Details of Manufacturer or Importer

Manufacturer

MG Chemicals
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADA



+1-800-340-0772

FAX +1-800-340-0773**E-MAIL** support@mgchemicals.com**WEB** www.mgchemicals.com**E-MAIL** (Competent Person): sds@mgchemicals.com

Emergency Phone Number

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents)USA or CANADA—Call Verisk 3E at **+1-866-519-4752** or **+1-760-476-3962**

(Service access code: 335388)



For emergencies involving the transport of dangerous goods; 24/7 serviceCANADA—Call CANUTEC collect at **+1-613-996-6666** or ***666** on cellular phones

8349TFM-B**(PART B)****Section 2: Hazard(s) Identification****Classification of Hazardous Chemical****GHS Categories**

Criteria	Category	Signal Word	Pictograms
Eye Corrosion	1	Danger	Corrosion
Sensitization	1	Warning	Exclamation
Skin Irritation	2	Warning	Exclamation

Note: The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

Label Elements

Signal Word	DANGER
Pictograms	Hazard Statements
	H318: Causes serious eye damage
	H317: May cause an allergic skin reaction H315: Causes skin irritation
Prevention	Precautionary Statements
P102	Keep out of reach of children.
P261	Avoid breathing fumes or vapors.
P264	Wash hands and exposed skin thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves and eye protection.

Section continued on the next page

8349TFM-B
(PART B)
Continued...

Response	Precautionary Statements
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor.
P302 + P352	IF ON SKIN: Wash with plenty of water.
P333 + P313	If skin irritation or rash occurs: Get medical advice or attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
Disposal	Precautionary Statements
P501	Dispose of contents in accordance with local, regional, national, and international regulations.

Hazards Not Otherwise Classified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
Metal fume fever	When the product is exposed to very high heat such as welding or when mechanically aerosolized, this may cause harmful aluminum oxide fumes and dust.	None	None

Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	%(weight)
21645-51-2	aluminum trihydrate	51%
1344-28-1	aluminum oxide	12%
109-55-7	3-aminopropyldimethylamine	3%
100-51-6	benzyl alcohol	2%
135108-88-2	methyleneoxide, polymer with benzenamine, hydrogenated	2%
70700-21-9	poly(oxy-1,2-ethanediyl), a-phosphono-w-methoxy-	1%
1333-86-4	carbon black	1%
1761-71-3	4,4'-methylenebis(cyclohexylamine)	0.2%
108-95-2	phenol	0.2%

8349TFM-B

(PART B)

Section 4: First-Aid Measures

<i>Exposure Condition</i>	<i>GHS Code: Precautionary Statement</i>
IF IN EYES	P305 + P351 + P338, P310
Immediate Symptoms	<i>redness, serious irritation, burns, pain</i>
Response	Rinse cautiously with water for at least 30 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
IF ON SKIN	P302 + P362, P352, P333 + P313, P363
Immediate Symptoms	<i>redness, allergic contact dermatitis, irritation</i>
Response	Take off immediately all contaminated clothing. Wash skin with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. Wash contaminated clothing before reuse.
IF INHALED	P304 + P340
Immediate Symptoms	<i>Low toxicity: cough, irritation of the respiratory track</i>
Response	Remove person to fresh air and keep comfortable for breathing.
IF SWALLOWED	P301 + P330 + P331
Immediate Symptoms	<i>Low toxicity: abdominal pain, diarrhea, drowsiness, nausea, vomiting</i>
Response	Rinse mouth. Do NOT induce vomiting.

8349TFM-B**(PART B)****Section 5: Fire-Fighting Measures**

Extinguishing Media	Use extinguishing media suitable for surrounding materials. Possible suitable fire extinguishing media are dry chemical, carbon dioxide, chemical foam, or water spray.
Specific Hazards	Not flammable or combustible, but burns if involved in a fire. Produces irritating smoke of unknown toxicity in fires. Inhalation of aluminum oxide fumes may cause metal fever and irritate the respiratory tract. The flu-like symptoms of metal fever may be delayed, occurring 4 to 12 hours after exposure. Prevent fire-fighting wash from entering waterway or sewer system.
Combustion Products	Produces carbon oxides (CO, CO ₂), nitrogen oxides (NO _x), phosphorous oxides, ammonia, and toxic metal fumes.
Fire-Fighter	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

Section 6: Accidental Release Measures

Personal Protection	Use personal protection recommended in Section 8.
Precautions for Response	Avoid breathing fumes or vapors. Remove all sources of extreme heat or open flames.
Environmental Precautions	Avoid releasing to the environment. Prevent spill from entering drains and waterways. Do not flush to sewer.
Containment Methods	Not applicable—not readily flowable
Cleaning Methods	Collect the liquid in a chemically resistant and sealable container. Wipe off residue with a paper towel and place dirty towels in the container. Wash the spill area with soap and water to remove the last traces of residue. RECOMMENDATION: Use a plastic, stainless steel or carbon steel container. Avoid containers containing copper, aluminum, zinc or galvanized surfaces, as waste can slowly oxidize them.
Disposal Methods	Dispose spill waste according to Section 13.

8349TFM-B
(PART B)
Section 7: Handling and Storage
Prevention

Keep out of reach of children.

Avoid breathing fumes or vapors.

Contaminated work clothing should not be allowed out of the workplace.

Handling

Wear protective gloves and eye protection.

Take off contaminated clothing and wash it before reuse.

Wash hands and exposed skin thoroughly after handling.

Storage

RECOMMENDATION: Keep in a dry and clean area, away from incompatible substances

Section 8: Exposure Controls/Personal Protection
Substances with Occupational Exposure Limit Values

Chemical Name	Country or Vendor	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
aluminum metal and insoluble compounds ^{a)}	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	1 mg/m ³ 15 mg/m ³ 10 mg/m ³ 1 mg/m ³ 1 mg/m ³ 10 mg/m ³	Not established Not established Not established Not established Not established Not established
benzyl alcohol	ACGIH U.S.A. OSHA PEL U.S.A (WEEL) Canada AB Canada BC Canada ON Canada QC	Not established Not established 10 ppm Not established Not established Not established Not established	Not established Not established Not established Not established Not established Not established Not established
carbon black ^{a)}	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	3.5 mg/m ³ 3.5 mg/m ³ 3.5 mg/m ³ 3 mg/m ³ 3.5 mg/m ³ 3.5 mg/m ³	Not established Not established Not established Not established Not established Not established

Section continued on the next page

8349TFM-B**(PART B)***Continued...*

Chemical Name	Country or Vendor	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
phenol	ACGIH	5 ppm (Skin)	Not established
	U.S.A. OSHA PEL	5 ppm (Skin)	Not established
	U.S.A (WEEL)	5 ppm (Skin)	Not established
	Canada AB	5 ppm (Skin)	Not established
	Canada BC	5 ppm (Skin)	Not established
	Canada ON	5 ppm (Skin)	Not established
	Canada QC	5 ppm (Skin)	Not established

Note: Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH¹, OSHA, and Canadian provinces exposure limits were consulted. Limits from the RTECS database² and from suppliers' SDSs were also consulted. Short term exposure limits (STEL) are usually for 15 min and long-term permissible exposure limits (PEL) for 8 h.

a) As respirable airborne particles.

Engineering Controls**Ventilation**

Keep airborne concentrations below the occupational exposure limits (OEL).

Note that the aluminum oxide and carbon black powders are inextricably bound to the adhesive mixture; therefore, they are not available as airborne hazard under normal or foreseeable condition of use.

Personal Protective Equipment**Eye protection**

Wear appropriate protective eyeglasses or chemical safety goggles.

RECOMMENDATION: Use safety glasses with lateral protection (side shields).

Skin Protection

For likely contacts, use of protective butyl rubber, neoprene, or other chemically resistant gloves.

For incidental contacts, use nitrile or other chemically resistant gloves.

Section continued on the next page

8349TFM-B**(PART B)****Respiratory Protection**

For over-exposures up to 10 x OEL of mist/vapors/spray, wear respirator such as a half-mask respirator with organic vapor cartridges. Dust particulate filters are not required.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

If the product is heated or worker has a known allergic reaction, consider using a full mask with organic vapor cartridge or with an independent air supply.

RECOMMENDATION: Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

8349TFM-B**(PART B)****Section 9: Physical and Chemical Properties**

Physical State	Liquid	Lower Flammability Limit	Not available
Appearance	Black, paste	Upper Flammability Limit	Not available
Odor	Slight ammoniacal	Vapor Pressure @20 °C	Not available
Odor Threshold	Not available	Vapor Density	Not available
pH	Not available	Relative Density @25 °C	1.74
Freezing/Melting Point	Not available	Solubility in Water	Insoluble
Initial Boiling Point ^{a)}	203 °C [397 °F]	Partition Coefficient n-octanol/water	Not available
Flash Point ^{a)}	96 °C [205 °F]	Auto-ignition Temperature	Not available
Evaporation Rate	Not available	Decomposition Temperature	Not available
Flammability	Non flammable	Viscosity @25 °C	>20.5 mm ² /s

a) Values based on benzyl alcohol

Section 10: Stability and Reactivity

Reactivity	Reacts exothermically with halogenated hydrocarbons, May attack metals such as aluminum, zinc, copper, and their alloys.
Chemical Stability	Chemically stable at normal temperatures and pressures
Conditions to Avoid	Avoid excessive heat and incompatible substances. Do not use in a way that forms a mist or aerosolize the product.
Incompatibilities	Strong oxidizing agents, strong acids
Polymerization	Will not occur
Decomposition	For thermal decomposition, see combustion products in Section 5.

8349TFM-B**(PART B)****Section 11: Toxicological Information****Summary of Effects and Symptoms by Routes of Exposure**

Eyes	Cause eye redness, pain, or eye damages.
Skin	Cause redness, skin irritation, and may cause allergic contact dermatitis.
Inhalation	Low toxicity: Inhalation of vapors may cause cough and irritation of the nose, throat, and lungs (upper respiratory tract).
Ingestion	Low toxicity: May cause abdominal pain, diarrhoea, drowsiness, nausea, and vomiting.
Chronic	Prolonged and repeated exposure to uncured epoxy hardener may lead to skin sensitization.

Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation
aluminum trihydrate	>2 000 mg/kg Rat ^{a)}	Not available	Not available
aluminum oxide	>2 000 mg/kg Rat	Not available	>2 mg/L 4 h Mouse (dust)
3-aminopropyldimethylamine	377.1 mg/kg Rat	300 mg/kg Rat	>4.31 mg/L 4 h Rat (vapor)
benzyl alcohol	1 620 mg/kg Rat	Not available	4.178 mg/L 4 h Rat
methyleneoxide, polymer with benzenamine, hydrogenated	368 mg/kg Rat	>1 000 mg/kg Rabbit	Not available
poly(oxy-1,2-ethanediyl), a- phosphono-w-methoxy-	Not available	Not available	Not available
carbon black	>15.4 g/kg Rat	>3 g/kg Rabbit	Not available
4,4'- methylenebis(cyclohexylamine)	>670 mg/kg Rat	2 110 mg/kg Rabbit	Not available
phenol	650 mg/kg Rat	660 mg/kg Rat	0.316 mg/L 4 h Rat (vapor)

Note: Toxicity data from the RTECS² and ECHA databases were consulted. The data from supplier SDSs were also consulted.

a) Supplier SDS

Section continued on the next page

8349TFM-B**(PART B)****Other Toxicological Effects****Skin corrosion/irritation**

Methyleneoxide, polymer with benzenamine, hydrogenated, 3-aminopropyldimethylamine, 4,4'-methylenebis(cyclohexylamine) causes severe skin burns.

Serious eye damage/irritation

Methyleneoxide, polymer with benzenamine, hydrogenated, 3-aminopropyldimethylamine, 4,4'-methylenebis(cyclohexylamine) and poly(oxy-1,2-ethanediyl), a-phosphono-w-methoxy-causes severe eye damage.

Respiratory and skin sensitization (allergic reactions)

Methyleneoxide, polymer with benzenamine, hydrogenated, 3-aminopropyldimethylamine, 4,4'-methylenebis(cyclohexylamine) may cause skin sensitization.

Carcinogenicity
(risk of cancer)

The carbon black [1333-86-4] is possibly carcinogenic by airborne routes of exposures under WHMIS 2015 and HCS 2012.

Because the carbon black is bound in the epoxy liquid mixture, it is not available as an airborne hazard (dust, mist, or spray) under normal use.

Carbon Black [1333-86-4]

IARC Group 2B: Possibly carcinogenic to humans

ACGIH A4: Not classified as a human carcinogen

CA Prop 65: Listed as a carcinogen (airborne, as unbound particles of respirable size)

NTP: Not listed

Mutagenicity
(risk of heritable genetic effects)

Based on available data, the classification criteria are not.

Reproductive Toxicity
(risk to sex functions)

Based on available data, the classification criteria are not.

Teratogenicity
(risk of fetus malformation)

Based on available data, the classification criteria are not.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not.

Aspiration hazard

There are no category 1 components, and the kinematic viscosity is $>20.5 \text{ mm}^2/\text{s}$ at 40°C .

8349TFM-B**(PART B)****Section 12: Ecological Information**

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

The 4,4'-methylenebis(cyclohexylamine) and phenol are classified as a chronic category 2 environmental toxicant.

Based on available data, aluminum trihydrate, aluminum oxide, benzyl alcohol, 3-aminopropyldimethylamine and carbon black are not classified as environmental hazard according to GHS criteria.

Acute Ecotoxicity

Available toxicity data does not meet classification thresholds.

Chronic Ecotoxicity

Available toxicity data does not meet classification thresholds.

Biodegradability

Not readily biodegradable

Bioaccumulation

Not available

Other Effects

Not available

Section 13: Disposal Considerations

Dispose of contents in accordance with all local, provincial, state, and federal regulations.

8349TFM-B**(PART B)****Section 14: Transport Information****Ground****Refer to TDG regulations** (Canadian Transportation of Dangerous Goods regulations);
USA DOT 49 CFR (Parts 100 to 185) **Regulations.**

Not Regulated

Air**Refer to ICAO-IATA Dangerous Goods Regulations.**

Not Regulated

Sea**Refer to IMDG regulations.**

Not Regulated

Note: **Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.**

Section 15: Regulatory Information**Canada****Domestic Substance List (DSL)/Non-Domestic Substance Lists (NDSL)**

All hazardous ingredients are listed on the DSL/NDSL.


Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.

Section continued on the next page

8349TFM-B
(PART B)
USA
Other Classifications
HMIS® RATING

HEALTH:	* 3
FLAMMABILITY:	1
PHYSICAL HAZARD:	0
PERSONAL PROTECTION:	

NFPA® 704 CODES


Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains aluminum oxide (CAS# 1344-28-1), which is subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

This product contains phenol (CAS# 108-95-2); reportable quantity = 1 000 lb), which is subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, USA).

This product contains carbon black, but it is bound and exposures during normal conditions of uses are below the Safe Harbor Threshold.

Section continued on the next page

8349TFM-B**(PART B)****Europe****RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

Section 16: Other Information

SDS Prepared by MG Chemical's Regulatory Department

Date of Revision 12 August 2024

Supersedes 07 March 2022

Reason for Changes: Added new part numbers in section 1.

Reference

1) ACGIH 2023 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2023).

2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Section continued on the next page

8349TFM-B**(PART B)****Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
IARC	International Agency for Research on Cancer
NOELR	No observable effect loading ratio
NTP	National Toxicology Program
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

Technical Queries Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Phone: +1-905-331-1396

Mailing Addresses *Manufacturing & Support*
1210 Corporate Drive
Burlington, Ontario, Canada
L7L 5R6

Disclaimer This safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.