

9200-B

STRUCTURAL EPOXY ADHESIVE

Safety Data Sheet

Section 1: Identification

Product Identifier and Other Means of Identification

Product Name: 9200-B**Other Means of Identification:** Structural Epoxy Adhesive**Related Part #** 9200-25ML, 9200-50ML, 9200-1.7L

Recommended Use and Restriction on Use


Use: Epoxy adhesive hardener for use with resins**Uses Advised Against:** Not for use as a spray coating


Details of Manufacturer or Importer

Manufacturer

MG Chemicals
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADA

MG Chemicals (Head Office)
9347-193 Street
Surrey, British Columbia V4N 4E7
CANADA

 +1-800-340-0772
FAX +1-800-340-0773
E-MAIL support@mgchemicals.com
WEB www.mgchemicals.com

 +1-905-331-1396
FAX +1-905-331-2682
E-MAIL info@mgchemicals.com

E-MAIL (Competent Person): sds@mgchemicals.com

Emergency Phone Number

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents)
USA or CANADA—Call Verisk 3E at **+1-866-519-4752** or **+1-760-476-3962**
(Service access code: 335388)

For emergencies involving the transport of dangerous goods; 24/7 service
CANADA—Call CANUTEC collect at **+1-613-996-6666** or ***666** on cellular phones




9200-B**STRUCTURAL EPOXY ADHESIVE****Section 2: Hazard(s) Identification****Classification of Hazardous Chemical****GHS Categories**

Criteria		Category	Signal Word	Pictograms
Serious Eye Damage		1	Danger	Corrosion
Skin Corrosion		1	Danger	Corrosion
Reproductive Toxicity		2	Warning	Health
Sensitization	Skin	1	Warning	Exclamation
Hazardous to the aquatic environment	Chronic	2	<i>none</i>	Environment

Note: The degree of severity is ranked within each hazard class from


1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

Label Elements

Signal Word	DANGER
Pictograms	Hazard Statements
	H314: Causes severe skin burns and eye damage
	H361: May damage fertility or the unborn child if swallowed
	H317: May cause an allergic skin reaction

Section continued on the next page

9200-B
STRUCTURAL EPOXY ADHESIVE
Continued...

Pictograms	Hazard Statements
	H411: Toxic to aquatic life with long lasting effects
Prevention	Precautionary Statements
P102	Keep out of reach of children.
P201, P202	Obtain special instructions before use. Do not handle all safety precautions have been read and understood.
P260	Do not breathe fumes, mist, or vapors.
P280	Wear protective gloves, protective clothing, and eye protection or face protection.
P264	Wash hands thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
Response	Precautionary Statements
P310	For all routes of exposure: Immediately call a POISON CENTER or doctor.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P301 + P330 + P352	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Wash with plenty of water [or shower].
P333 + P313	If skin irritation or rash occurs: Get medical advice or attention.
P363	Wash contaminated clothing before reuse.
P301 + P330 + P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308 + P313	IF exposed or concerned: Get medical advice or attention.
P391	Collect spillage.

Section continued on the next page

9200-B**STRUCTURAL EPOXY ADHESIVE***Continued...*

Storage	Precautionary Statements
P405	Store locked up.
Disposal	Precautionary Statements
P501	Dispose of contents in accordance to local, regional, national, and international regulations.

Hazards Not Otherwise Classified

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
None	None	None	None

Section 3: Composition/Information on Ingredients

CAS #	Chemical Name	%(weight)
68683-29-4	ATBN polymer	32%
7727-43-7	barium sulfate	30%
68410-23-1	fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines	24%
68082-29-1	fatty acids, C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine	7%
112-24-3	triethylenetetramine	3%
140-31-8	2-piperazin-1-ylethylamine (AEP)	2%

9200-B**STRUCTURAL EPOXY ADHESIVE****Section 4: First-Aid Measures**

<i>Exposure Condition</i>	<i>GHS Code: Precautionary Statement</i>
IF IN EYES	P305 + P351 + P338, P310
Immediate Symptoms	<i>redness, severe irritation, pain, burns</i>
Response	Rinse cautiously with water for 30 minutes or more. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
IF ON SKIN (or hair)	P301 + P330 + P352, P310, P333 + P313, P363
Immediate or Delayed Symptoms	<i>redness, irritation, rash (allergic contact dermatitis), pain, burns, blistering</i>
Response	Take off immediately all contaminated clothing. Wash with plenty of water [shower]. Immediately call a POISON CENTER or doctor. If skin irritation or rash occurs: Get medical advice or attention. Wash contaminated clothing before reuse.
IF SWALLOWED	P301 + P330 + P331, P310
Immediate Symptoms	<i>irritation, abdominal pain, nausea, vomiting, burns to the digestive tract</i>
Response	Rinse mouth. Do not induce vomiting. Immediately call a POISON CENTER or doctor.
IF INHALED	P304 + P340, P310
Immediate Symptoms	<i>cough, irritation of the respiratory track, burning sensation</i>
Delayed Symptoms	<i>asthma, difficulty breathing</i>
Response	Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor.

Advice to Physicians

In case of exposure to nitrogen oxides (NO_x) combustion products or triethylenetetramine vapors during a fire, the symptoms may be delayed. For significant exposures, the exposed person should be kept under medical surveillance for 48 hours.

9200-B**STRUCTURAL EPOXY ADHESIVE****Section 5: Fire-Fighting Measures**

Extinguishing Media	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.
Specific Hazards	<p>Not flammable or combustible, but burns if involved in a fire. Produces irritating and toxic fumes in fires or in contact with hot surfaces.</p> <p>Inhalation of toxic smoke during fire may have delayed effects. Exposed person may need to be put under surveillance for 48 h.</p> <p>Toxic for aquatic environment: Prevent fire-fighting wash from entering waterway or sewer system.</p>
Combustion Products	Produces carbon oxides (CO, CO ₂) and nitrogen oxides (NO _x).
Fire-Fighter	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

Section 6: Accidental Release Measures

Personal Protection	Use personal protection recommended in Section 8.
Precautions for Response	Do not breathe fumes, mist, or vapors.
Environmental Precautions	Avoid releasing to the environment. Prevent spill from entering drains and waterways. Do not flush to sewer.
Containment Methods	Contain with inert and non-flammable absorbent (such as soil, sand, vermiculite).
Cleaning Methods	Collect liquid in a sealable container. Sprinkle inert absorbent compound onto spill, then sweep into the container. Wipe residue with a paper towel wetted with a suitable organic solvent such as alcohol or ethyl lactate, and place dirty towels in container. Wash spill area with soap and water to remove the last traces of residue.
Disposal Methods	Dispose spill waste according to Section 13.

9200-B**STRUCTURAL EPOXY ADHESIVE****Section 7: Handling and Storage****Prevention**

Keep out of reach of children.

Do not breathe fumes, mist, or vapors.

Contaminated work clothing should not be allowed out of the workplace.

Avoid release to the environment.

Handling

Wear protective gloves, protective clothing, and eye protection or face protection.

Take off contaminated clothing and wash it before reuse.

Wash hands thoroughly after handling.

Collect spillage.

Storage

Store locked up.

Section 8: Exposure Controls/Personal Protection**Substances with Occupational Exposure Limit Values**

Chemical Name	Country or Vendor	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
Barium sulfate	ACGIH	10 mg/m ³	Not established
	U.S.A. OSHA PEL	15 mg/m ³ (Dust)	Not established
	Canada AB	10 mg/m ³	Not established
	Canada BC	10 mg/m ³ (Dust)	Not established
	Canada ON	10 mg/m ³	Not established
	Canada QC	10 mg/m ³	Not established
triethylenetetramine	ACGIH	Not established	Not established
	U.S.A. OSHA PEL	Not established	Not established
	U.S.A (WEEL)	1 ppm	Not established
	Canada AB	Not established	Not established
	Canada BC	Not established	Not established
	Canada ON	0.5 mg/m ³ (Skin) ^{a)}	Not established
	Canada QC	Not established	Not established

Note: Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH¹, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from by RTECS² database and data from suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

a) Skin—can be absorbed through the skin.

Section continued on the next page

Page **7** of **17**

Date: 18 December 2020 / Ver. 2.00

9200-B**STRUCTURAL EPOXY ADHESIVE****Engineering Controls****Ventilation**

Keep airborne concentrations below the occupational exposure limits (OEL).

Personal Protective Equipment**Eye protection**

Wear appropriate protective eyeglasses or chemical safety goggles.

RECOMMENDATION: Use safety glasses with lateral protection (side shields).

Skin Protection

For likely contacts, use of protective butyl rubber, neoprene, or other chemically resistant gloves.

For incidental contacts, use nitrile or other chemically resistant gloves.

Respiratory Protection

For over-exposures up to 10 x OEL of mist, vapors, or spray, wear respirator such as a half-mask respirator with organic vapor cartridges.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

If the product is heated or worker has a known allergic reaction, consider using a full mask with organic vapor cartridge or with an independent air supply.

RECOMMENDATION: Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

9200-B
STRUCTURAL EPOXY ADHESIVE
Section 9: Physical and Chemical Properties

Physical State	Liquid	Lower Flammability Limit	Not available
Appearance	Amber	Upper Flammability Limit	Not available
Odor	Ammonia-like	Vapor Pressure @20 °C^{a)}	<0.001 kPa [<0.01 mmHg]
Odor Threshold	Not available	Vapor Density	Not available
pH	Not available	Relative Density @25 °C	1.18
Freezing/Melting Point	Not available	Solubility in Water	Slightly soluble
Initial Boiling Point	Not available	Partition Coefficient	Not available
Flash Point^{a)}	>122 °C [>252 °F]	Auto-ignition Temperature	Not available
Evaporation Rate	Not available	Decomposition Temperature	Not available
Flammability	Not applicable	Viscosity @25 °C	>20.5 mm ² /s

a) Literature value for triethylenetetramine

Section 10: Stability and Reactivity

Reactivity	Reacts exothermically with ketones, halogenated hydrocarbons, cyanides, nitriles, and epoxides. May attack metals such as aluminum, zinc, copper, and their alloys.
Chemical Stability	Chemically stable at normal temperatures and pressures
Conditions to Avoid	Ignition sources, open flames, and incompatible substances
Incompatibilities	Strong oxidizing agents, strong acids
Polymerization	Will not occur
Decomposition	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.

9200-B**STRUCTURAL EPOXY ADHESIVE****Section 11: Toxicological Information****Summary of Effects and Symptoms by Routes of Exposure**

Eyes	May cause redness, severe irritation, pain, or burns.
Skin	May cause redness, serious skin irritation, allergic contact dermatitis, and chemical burns. Triethylenetetramine can be absorbed through skin leading to toxic effects. When heated, hot triethylenetetramine vapors may also result in itching of the face with skin redness (erythema) and swelling (edema).
Inhalation	May cause cough, irritation of the respiratory track, or burning sensation.
Ingestion	May cause irritation, abdominal pain, nausea, vomiting, burns to the digestive tract (see inhalation symptoms).
Chronic	Prolonged and repeated exposure to uncured epoxy hardener may lead to skin sensitization.

Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation
fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines	>5 000 mg/kg ^{a)}	>5 000 mg/kg ^{a)}	Not available
fatty acids, C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine	>5 000 mg/kg ^{a)}	>5 000 mg/kg ^{a)}	Not available
triethylenetetramine	2 500 mg/kg Rat	805 mg/kg Rabbit	Not available
2-piperazin-1-ylethylamine (AEP)	2 106 mg/kg Rat	866 mg/kg Rabbit	Not available

Note: Toxicity data from the RTECS² and ECHA were consulted. The data from supplier SDSs were also consulted.

a) Supplier SDS

Section continued on the next page

9200-B**STRUCTURAL EPOXY ADHESIVE****Other Toxicological Effects**

Skin corrosion/irritation	Triethylenetetramine and 2-piperazin-1-ylethylamine causes skin burns.
Serious eye damage/irritation	Triethylenetetramine and 2-piperazin-1-ylethylamine causes severe eye damage.
Respiratory and skin sensitization (allergic reactions)	The epoxy hardener components may cause skin sensitization according to animal studies.
Carcinogenicity (risk of cancer)	None of the ingredients are classified or listed as a carcinogen by IARC, ACGIH, CA Prop 65, or NTP.
Mutagenicity (risk of heritable genetic effects)	Based on available data, the classification criteria are not met.
Reproductive Toxicity (risk to sex functions)	Based on animal studies 2-piperazin-1-ylethylamine has been shown to be a developmental toxicant if swallowed.
Teratogenicity (risk of fetus malformation)	Based on available data, the classification criteria are not met.
STOT-single exposure	Based on available data, the classification criteria are not met.
STOT-repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Based on available data, the classification criteria are not met. There are no category 1 components, and the kinematic viscosity is >20.5 mm ² /s at 40 °C.

Section 12: Ecological Information

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

The fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines (CAS# 68410-23-1) and fatty acids, C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine (CAS# 68082-29-1) were classified as a chronic category 2 environmental toxicant (not readily biodegradable, LC50 range of 1–10 mg/L for fish; EC0 bacterial >10 and ≤100 mg/L).

Literature values for the triethylenetetramine (CAS # 112-24-3) suggest an acute category 3 aquatic toxicity (LC50, IC50, and EC50 values of >100 mg/L for fish and between 10 and 100 mg/L for algae).

Section continued on the next page

9200-B**STRUCTURAL EPOXY ADHESIVE****Acute Ecotoxicity**

Category 2

Toxic to aquatic life

Chronic Ecotoxicity

Category 2

Toxic to aquatic life with long lasting effect

Avoid release to the environment. Collect spillage.

Biodegradability

Not readily biodegradable

Bioaccumulation

Not available

Other Effects

Not available

Section 13: Disposal Information

Dispose of contents in accordance with all local, regional, national, and international regulations.

9200-B
STRUCTURAL EPOXY ADHESIVE
Section 14: Transport Information
Ground

Refer to TDG regulations (Canadian Transportation of Dangerous Goods regulations);
USA DOT 49 CFR (Parts 100 to 185) **Regulations.**

Sizes 1 L and under

*Part B of 9200-25ML, 9200-50ML,
9200-1.7L kits*

Limited Quantity



Sizes greater than 1 L

UN number: UN2735

Shipping Name: AMINES, LIQUID,
CORROSIVE, N.O.S. *

(containing triethylenetetramine,
dimer fatty acid (C18)poly amido
amine resin)

Class: 8

Packing Group: II

Marine Pollutant: Yes


Air

Refer to ICAO-IATA Dangerous Goods Regulations.

Sizes 0.1 L and under

*Part B of 9200-25ML, 9200-50ML
kits*

Limited Quantity



Sizes greater than 0.1 L up to 1 L

Part B of 9200-1.7L kit

UN number: UN2735

Shipping Name: AMINES, LIQUID,
CORROSIVE, N.O.S. *

(containing triethylenetetramine,
dimer fatty acid (C18)poly amido
amine resin)

Class: 8




Packing Group: II

Marine Pollutant: Yes



Section continued on the next page

9200-B
STRUCTURAL EPOXY ADHESIVE
Sea

Refer to IMDG regulations.	
Sizes 1 L and under <i>Part B of 9200-25ML, 9200-50ML, 9200-1.7L kits</i> Limited Quantity	Sizes greater than 1 L UN number: UN2735 Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. * (containing triethylenetetramine, dimer fatty acid (C18)poly amido amine resin) Class: 8 Packing Group: II Marine Pollutant: Yes
	 

Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.

Section 15: Regulatory Information
Canada
Domestic Substance List (DSL)/Non-Domestic Substance Lists (NDSL)

All hazardous ingredients are listed on the DSL/NDSL.


Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.

Section continued on the next page

9200-B**STRUCTURAL EPOXY ADHESIVE****USA****Other Classifications****HMIS[®] RATING**

HEALTH:	* 3
FLAMMABILITY:	1
PHYSICAL HAZARD:	0
PERSONAL PROTECTION:	

NFPA[®] 704 CODES

Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product does not contain substances that are subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, USA).

This product does not contain any listed substances in California.

Europe**RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

9200-B**STRUCTURAL EPOXY ADHESIVE****Section 16: Other Information**

SDS Prepared by	Regulatory Department
Date of Revision	18 December 2020
Supersedes	04 March 2020
Reason for Changes:	Update classification based on new data.

Reference

1) ACGIH 2017 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2017).

2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
IARC	International Agency for Research on Cancer
NOELR	No observable effect loading ratio
NTP	National Toxicology Program
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
SDS	Safety Data Sheet
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

Section continued on the next page

9200-B**STRUCTURAL EPOXY ADHESIVE**

Technical Queries Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Mailing Addresses *Manufacturing & Support*
1210 Corporate Drive
Burlington, Ontario, Canada
L7L 5R6

Head Office
9347-193rd Street
Surrey, British Columbia, Canada
V4N 4E7

Disclaimer This safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.