

1/2-14 NPT

Well-suited for corrosive environments, as well as food processing, medical, heating, and cooling applications. This series of stainless steel side-mounted float switches are among the most durable float switches in the industry.

## **Applicable Industries**

- Food-grade fluid level control
- Hot water boilers and steam generator tanks
- Chemical tanks, fuel tanks and other hazardous locations

## **Features**

- High-pressure and high-temperature industrial tank level control
- Available with extended stem lengths

# Material

• Stem and Float: 316 Stainless Steel

## **Specifications**

- Max. temperature: 392°F / 200°C
- Max. pressure: 300 psi
- Switch rating: 30 watt, SPST

## **Electrical Ratings**

 240V AC, 0.14A; 120V AC, 0.28A; 120V DC, 0.07A; 24V DC, 0.28A

Part Numbers	Mounting	Minimum Media SG	Lead Wires	Approvals	
M5900	1" x 1/2" NPT	0.75	24", 22 AWG, Teflon Insulated (standard)	CE, UL Haz. Loc., CSA Haz. Loc., NSF	
M5910	1/2" x 1/4" NPT	0.75	24", 22 AWG, Teflon Insulated (standard)	CE, UL Haz. Loc., CSA Haz. Loc., NSF	
M5920	1/2" x 1/2" NPT	0.75	24", 22 AWG, Teflon Insulated (standard)	CE, UL Haz. Loc., CSA Haz. Loc., NSF	

NOTE: Other fittings and voltages are available. Contact us to discuss your application.

## Level Switch Electrical Considerations and Reed Switch Protection

When using Madison level switches, it is important to consider the application's electrical parameters. Our level switches utilize reed switch technology, which are glass encapsulated, magnetically actuated switches. Madison generally provides electrical ratings for resistive loads; however, where the maximum current of the load permits, the switches are capable of controlling devices such as motors, solenoids or coils that produce capacitive or inductive electrical loads. Where possible, Madison recommends the use of general-purpose/isolation relays or controllers to protect the switch.

# Protect your level switch: Protection Techniques and Common Failure Modes

Reed Switch protection is the most successful method of increasing the performance and life of your level sensor. Since every application varies, it is important to understand your protection options. The life of the reed switch is typically 1 million cycles, within rated load conditions. The table below is a guide to suggested protection techniques and common failure modes associated with each load type.

Load	Load Example	Protection	Diagram	Common Failure Modes	Failure Mode Description	
Resistive (DC)	Indicator Lamp, Heaters	Current Limiting Resistor	A	In-rush Current (Switching)	In-rush current exceeds rating and welds switch closed	
				Over-Current (Carry)	Carry-current exceeds rating and switch welds or burns open like a fuse	
Inductive & Capacitative (DC)	Relay Coil	Reversing Diode	В		Voltage arcing during switching	
Inductive & Capacitive (AC or DC)	Solenoids, Motor	Resistor & Capacitor Network	С	Over-Voltage (Arcing)	welds contacts closed	
Resistive, Inductive & Capacitive (AC or DC)	Indicator Lamp, Heaters, Relay Coil, Solenoids, Motor	Varistor or MOV	D	Over-Voltage (Arcing)	Transients voltage spikes exceed breakdown voltage and weld switch closed	

#### **Capacitive Load**



Diagram A: Current Limiting Resistor



Diagram C: RC Network

For DC circuits: Insert a 1N4004 diode across the load (i.e.: relay coil) with the cathode end (marked with circular line) connected toward the positive side. This way the diode conducts only when the field collapses. General rule is to use a diode with a voltage rating at least three times the circuit voltage. A 1N4004 has a rating of 1 amp continuous, 30 amp surge, 400V max. Refer to diagram B.

#### **Inductive Load**



Diagram B: Reversing Diode



Diagram D: Varistor or MOV

For typical 120V AC circuits: Insert a 50 to 100 ohm, 1/2 watt Resistor in series with a .1 micro farad 400 to 600 volt capacitor across the switch. The capacitor is a high impedance to 60 hertz, but is essentially a short circuit to high frequencies of generated voltages. Alternately, a varistor V130LA10A by itself across the switch will also work for 120V AC. Refer to diagram D.



## Madison Company | Sensing Solutions since 1959

27 Business Park Drive Branford, CT 06405 USA Toll-Free: 800.466.5383 Outside the USA: +1.203.488.4477



www.madisonsensors.com

Not responsible for any typographic errors. Specifications are subject to change without notice. MAC\_042\_C 012023