





PART No. MATRIX


E	2	2	E	0	6	0	2	1	M	X	X	X	X
E=ETHERNET/ Ethernet		HEADS: 1 = M12 D-Coding		HEADS STYLE: 060 = MALE STR / MALE STR			CABLE TYPE : CABLE 21		UNITS: M= METER T=10x METER	LENGTH EXAMPLES: 005=0.5 m 010=1 m 150=15 m T100=100 m			H= 2 PCS. OF I/D Carrier
WIRING TYPE: E=8 Pole (STRAIGHT WIRED)													



BILL OF MATERIAL

ITEM	QTY	DESCRIPTION	MATERIAL	FINISH/COLOR
1	1	CABLE 4X(2X AWG26/7) CAT 7	TPE	GREEN
2	16	CONTACT M12 XC MALE	BRASS	Au PLATED
3	2	SHIELD SLEEVE	Zn	Ni PLATED
4	2	INSERT M12 XC MALE	PA	BLACK
5	-	MOULDING MATERIAL	TPU	BLACK
6	2	M12 HYBRID COUPLING NUT	BRASS	Ni PLATED
7	2	I/D CARRIER 6-10mmx30mm	PVC	TRANSPARENT
8	1	LABEL 2.0X1.75	VINYL	YELLOW

DOCUMENT STATUS	P1	RELEASE DATE	2022/01/25	10:26:15
-----------------	----	--------------	------------	----------

FUNCTIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION										
	DIMENSION UNITS		SCALE		CURRENT REV DESC: NOTE CHANGED			molex			
	mm		2:1								
	GENERAL TOLERANCES (UNLESS SPECIFIED)		EC NO: 692351 DRWN: ARPITT 2022/01/19 CHK'D: RSILLER 2022/01/25 APPR: RSILLER 2022/01/25 INITIAL REVISION: DRWN: RSCHIEBER 2019/05/13 APPR: RSILLER 2020/12/09			CSE M12 CAT6A 8P XC MA STR TPE XM					
	ANGULAR TOL ± 1.0°										
	4 PLACES ±										
	3 PLACES ±										
	2 PLACES ± 0.05										
	1 PLACE ± 0.3		PRODUCT CUSTOMER DRAWING								
	0 PLACES ± 0.5										
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS											
DIVISIONAL SYMBOLS	THIRD ANGLE PROJECTION		DRAWING		SERIES		DOCUMENT NUMBER		DOC TYPE	DOC PART	REVISION
			A3-SIZE		120341		1203410863		PSD	000	A5
							SEE TABLE 1		GENERAL MARKET		SHEET NUMBER
										1 OF 2	

10	9	8	7	6	5	4	3	2	1
TABLE 1									
MOLEX P/N	ENGINEERING NO.	DESCRIPTION	LENGTH						
1203410941	E22E06021M003	M12 CAT6A M/M ST/ST TPE GREEN 0.3M	300						
1203410863	E22E06021M005	M12 CAT6A M/M ST/ST TPE GREEN 0.5M	500						
1203410864	E22E06021M010	M12 CAT6A M/M ST/ST TPE GREEN 1M	1000						
1203410865	E22E06021M020	M12 CAT6A M/M ST/ST TPE GREEN 2M	2000						
1203410866	E22E06021M030	M12 CAT6A M/M ST/ST TPE GREEN 3M	3000						
1203410867	E22E06021M040	M12 CAT6A M/M ST/ST TPE GREEN 4M	4000						
1203410868	E22E06021M050	M12 CAT6A M/M ST/ST TPE GREEN 5M	5000						
1203410869	E22E06021M060	M12 CAT6A M/M ST/ST TPE GREEN 6M	6000						
1203410895	E22E06021M070	M12 CAT6A M/M ST/ST TPE GREEN 7M	7000						
1203410870	E22E06021M080	M12 CAT6A M/M ST/ST TPE GREEN 8M	8000						
1203410896	E22E06021M090	M12 CAT6A M/M ST/ST TPE GREEN 9M	9000						
1203410871	E22E06021M100	M12 CAT6A M/M ST/ST TPE GREEN 10M	10000						
1203410942	E22E06021M120	M12 CAT6A M/M ST/ST TPE GREEN 12M	12000						
1203410943	E22E06021M140	M12 CAT6A M/M ST/ST TPE GREEN 14M	14000						
1203410872	E22E06021M150	M12 CAT6A M/M ST/ST TPE GREEN 15M	15000						
1203410944	E22E06021M180	M12 CAT6A M/M ST/ST TPE GREEN 18M	18000						
1203410873	E22E06021M200	M12 CAT6A M/M ST/ST TPE GREEN 20M	20000						
1203410945	E22E06021M230	M12 CAT6A M/M ST/ST TPE GREEN 23M	23000						
1203410946	E22E06021M270	M12 CAT6A M/M ST/ST TPE GREEN 27M	27000						
1203410947	E22E06021M300	M12 CAT6A M/M ST/ST TPE GREEN 30M	30000						
1203410948	E22E06021M340	M12 CAT6A M/M ST/ST TPE GREEN 34M	34000						
1203410949	E22E06021M380	M12 CAT6A M/M ST/ST TPE GREEN 38M	38000						
1203410950	E22E06021M420	M12 CAT6A M/M ST/ST TPE GREEN 42M	42000						
1203410951	E22E06021M460	M12 CAT6A M/M ST/ST TPE GREEN 46M	46000						
1203410952	E22E06021M500	M12 CAT6A M/M ST/ST TPE GREEN 50M	50000						
1203410953	E22E06021M540	M12 CAT6A M/M ST/ST TPE GREEN 54M	54000						
1203410954	E22E06021M570	M12 CAT6A M/M ST/ST TPE GREEN 57M	57000						
1203410955	E22E06021M610	M12 CAT6A M/M ST/ST TPE GREEN 61M	61000						
1203410956	E22E06021M650	M12 CAT6A M/M ST/ST TPE GREEN 65M	65000						
1203410957	E22E06021M700	M12 CAT6A M/M ST/ST TPE GREEN 70M	70000						

TABLE 1			
WITH ID CARRIER			
MOLEX P/N	ENGINEERING NO.	DESCRIPTION	LENGTH
1203410999	E22E06021M005H	M12 CAT6A M/M ST/ST TPE GREEN 0.5M-ID	500
1203411031	E22E06021M010H	M12 CAT6A M/M ST/ST TPE GREEN 1M-ID	1000
1203411032	E22E06021M020H	M12 CAT6A M/M ST/ST TPE GREEN 2M-ID	2000
1203411033	E22E06021M030H	M12 CAT6A M/M ST/ST TPE GREEN 3M-ID	3000
1203411034	E22E06021M040H	M12 CAT6A M/M ST/ST TPE GREEN 4M-ID	4000
1203411003	E22E06021M050H	M12 CAT6A M/M ST/ST TPE GREEN 5M-ID	5000
1203411092	E22E06021M060H	M12 CAT6A M/M ST/ST TPE GREEN 6M-ID	6000
1203411093	E22E06021M070H	M12 CAT6A M/M ST/ST TPE GREEN 7M-ID	7000
1203411094	E22E06021M080H	M12 CAT6A M/M ST/ST TPE GREEN 8M-ID	8000
1203411000	E22E06021M100H	M12 CAT6A M/M ST/ST TPE GREEN 10M-ID	10000
1203411035	E22E06021M120H	M12 CAT6A M/M ST/ST TPE GREEN 12M-ID	12000
1203411036	E22E06021M150H	M12 CAT6A M/M ST/ST TPE GREEN 15M-ID	15000
1203411037	E22E06021M200H	M12 CAT6A M/M ST/ST TPE GREEN 20M-ID	20000
1203410918	E22E06021M250H	M12 CAT6A M/M ST/ST TPE GREEN 25M-ID	25000
1203410919	E22E06021M300H	M12 CAT6A M/M ST/ST TPE GREEN 30M-ID	30000
1203410920	E22E06021M350H	M12 CAT6A M/M ST/ST TPE GREEN 35M-ID	35000
1203410978	E22E06021M400H	M12 CAT6A M/M ST/ST TPE GREEN 40M-ID	40000
1203410979	E22E06021M450H	M12 CAT6A M/M ST/ST TPE GREEN 45M-ID	45000
1203410921	E22E06021M500H	M12 CAT6A M/M ST/ST TPE GREEN 50M-ID	50000
1203410980	E22E06021M550H	M12 CAT6A M/M ST/ST TPE GREEN 55M-ID	55000
1203411001	E22E06021M600H	M12 CAT6A M/M ST/ST TPE GREEN 60M-ID	60000
1203410981	E22E06021M650H	M12 CAT6A M/M ST/ST TPE GREEN 65M-ID	65000
1203410982	E22E06021M700H	M12 CAT6A M/M ST/ST TPE GREEN 70M-ID	70000
1203410983	E22E06021M750H	M12 CAT6A M/M ST/ST TPE GREEN 75M-ID	75000
1203411002	E22E06021M850H	M12 CAT6A M/M ST/ST TPE GREEN 85M-ID	85000
1203411038	E22E06021M800H	M12 CAT6A M/M ST/ST TPE GREEN 80M-ID	80000

NOTES:
VOLTAGE RATING: 48 V
CURRENT RATING: 0.5 A
TEMPERATURE RATING:
STATIC: -40 °C TO 80 °C
DYNAMIC: -25 °C TO 80 °C
IP RATING: IP 67 (IN MATED AND LOCKED CONDITION)
TRANSMISSION CHARACTERISTICS ACCORDING TO ISO/IEC 11801 CLASS E_A CHANNEL,
WITH INSERTION LOSS BEING IGNORED FOR CABLE LENGTHS ≤1 m OR ≥65 m
PACKAGING: CORDSETS ARE PACKED IN A POLYBAG

DOCUMENT STATUS	P1	RELEASE DATE	2022/01/25	10:26:15					
10	9	8	7	6	5	4	3	2	1

FUNCTIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION									
	0	DIMENSION UNITS	mm	SCALE	1:1	CURRENT REV DESC: NOTE CHANGED				
		GENERAL TOLERANCES (UNLESS SPECIFIED)								
		ANGULAR TOL	± 1.0 °							
		4 PLACES	±							
		3 PLACES	±							
	0	2 PLACES	± 0.05	EC NO: 692351 DRWN: ARPITT CHK'D: RSILLER APPR: RSILLER 2022/01/19 2022/01/25 2022/01/25						
		1 PLACE	± 0.3							
		0 PLACES	± 0.5							
		INITIAL REVISION:					2019/05/13 2020/12/09			
DRWN: RSCHEBER APPR: RSILLER										
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION		DRAWING	SERIES	DOCUMENT NUMBER		DOC TYPE	DOC PART	REVISION
				A3-SIZE	120341	1203410863		PSD	000	A5

MATERIAL NUMBER		CUSTOMER		SHEET NUMBER	
SEE TABLE 1		GENERAL MARKET		2 OF 2	