

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [1206132006](#)
Status: **Active**
Overview: Brad Ultra-Lock (M12) EX Connection System for Zone 2 Hazardous Locations
Description: Ultra-Lock (M12) EX Double-Ended Cordset, Zone 2, 5 Poles, Male (Straight) to Female (90°), 22 AWG, TPE Cable, 1.0m (3.28') Length

Documents:
[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)
[Product Specification PS-120614-001-001 \(PDF\)](#)

General	
Product Family	Industrial Cordsets
Series	120613
Connector End A	Ultra-Lock (M12) EX
Connector End B	Ultra-Lock (M12) EX
IP Rating	IP69K
Material - Contact	Copper Alloy
Overview	Brad Ultra-Lock (M12) EX Connection System for Zone 2 Hazardous Locations
Product Name	Ultra-Lock (M12) EX
Protocol	N/A
Region	America
Type	Double Ended
UPC	78172534853
Physical	
Cable Diameter	6.86mm (.270")
Cable Length	1.0m (3.28')
Color - Cable Jacket	Yellow
Coupling Style	Push to Lock
Gender	Female-Male
Keyway	Single
LED Indicator	No
Material - Cable Jacket	TPE
Material - Connector Body	TPE
Material - Coupling Nut	Nickel-plated Brass
Material - O-Ring	Fluoro-elastomer
Material - Plating Mating	Gold over Nickel
Orientation	90° to Straight
Poles	5
Temperature Range - Operating	-20°C to +40°C
Wire Size AWG	18
Wire/Cable Type	PLTC-ER
Electrical	
Current - Maximum per Contact	4.0A
Voltage - Maximum	250V AC/DC
Material Info	
Engineering Number	LWLW5031K03M010
Reference - Drawing Numbers	
Product Specification	PS-120614-001-001
Sales Drawing	SD-120613-003, SD-120613-007, SD-120614-999



EU ELV Not Reviewed	
EU RoHS Not Reviewed	China RoHS
REACH SVHC Not Reviewed	
Halogen-Free Status Not Reviewed	
For more information, please visit Contact US	
China ROHS	Not Reviewed
ELV	Not Reviewed
RoHS Phthalates	Not Reviewed

Search Parts in this Series
[120613](#) Series

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION