

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	1206134005
Status:	Active
Overview:	Brad Ultra-Lock (M12) EX Connection System for Zone 2 Hazardous Locations
Description:	Ultra-Lock (M12) EX Double-Ended Cordset, Zone 2, 3 Poles, Male (Straight) to Female (90°), 18 AWG, Rubber Cable, 1.0m (3.28') Length
Documents:	Drawing (PDF) RoHS Certificate of Compliance (PDF) Product Specification PS-120614-001-001 (PDF)
General	Industrial Cordsets Series 120613 Connector End A Ultra-Lock (M12) EX Connector End B Ultra-Lock (M12) EX IP Rating IP69K Material - Contact Copper Alloy Overview Brad Ultra-Lock (M12) EX Connection System for Zone 2 Hazardous Locations Product Name Ultra-Lock (M12) EX Protocol N/A Region America Type Double Ended UPC 78172534860
Physical	Cable Diameter 5.30mm (.209") Cable Length 1.0m (3.28') Color - Cable Jacket Yellow Coupling Style Push to Lock Gender Female-Male Keyway Single LED Indicator No Material - Cable Jacket CPE Material - Connector Body TPE Material - Coupling Nut Nickel-plated Brass Material - O-Ring Fluoro-elastomer Material - Plating Mating Gold over Nickel Orientation 90° to Straight Poles 3 Temperature Range - Operating -20°C to +40°C Wire Size AWG 18 Wire/Cable Type SJOOW
Electrical	Current - Maximum per Contact 4.0A Voltage - Maximum 250V AC/DC
Material Info	Engineering Number LWLW3031C02M010
Reference - Drawing Numbers	Product Specification PS-120614-001-001 Sales Drawing SD-120613-003, SD-120613-011, SD-120614-999



EU ELV	
Not Reviewed	
EU RoHS	China RoHS
Not Reviewed	
REACH SVHC	
Not Reviewed	
Halogen-Free	
Status	
Not Reviewed	
For more information, please visit Contact US	
China ROHS	Not Reviewed
ELV	Not Reviewed
RoHS Phthalates	Not Reviewed

Search Parts in this Series
[120613](#) Series

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION