Part Number: 1554211004
Status: Active
Overview: Flamar Standard and Custom Cables for Industrial Automation
Description: Flamar PROFIBUS* DP Network Cable, WSOR Jacket, Braided Shielding Overall, 2 Circuits, 0.34mm² / 22 AWG, 8.20mm (.323") Diameter, 200.0m (656.17') Length, Violet



Series image - Reference only

Documents:
Product Specification 1554211004-P1E (PDF)
RoHS Certificate of Compliance (PDF)
Brochure (PDF)

Agency Certification	
UL	E172949
General	
Product Family	Cable
Series	155421
Crimp Quality Equipment	Yes
Geographic Area	Global
Overview	Flamar Standard and Custom Cables for Industrial Automation
Product Name	Flamar, Network
Protocol	PROFIBUS
Taxonomy	Industrial Cable
UPC	889056464123
Physical	
Bending Radius - Minimum	> 15xOD
Cable Length	200.0m
Circuits (Loaded)	2
Color - Cable Jacket	Violet
Insulation	Foam PE
Material - Outer Jacket	WSOR
Net Weight	0.076/kg
Outer Jacket Diameter	8.20mm
Packaging Type	Reel
Temperature Range - Operating	-10° to +60°C
Wire Size AWG	22
Wire Size mm²	0.34
Wire/Cable Type	UL AWM 21215 / CSA
Electrical	
Current - Maximum per Contact	Contact Molex
Voltage - Maximum	600V
Material Info	
Engineering Number	1X200M
Reference - Drawing Numbers	
Product Specification	1554211004-P1E

EU ELV
Not Relevant

EU RoHS | **China RoHS**
Compliant

REACH SVHC
Not Contained Per - D(2022)4187-DC (10 June 2022)

Halogen-Free Status
Not Reviewed

For more information, please visit Contact US

China ROHS	Green Image
ELV	Not Relevant
RoHS Phthalates	Not Contained

Search Parts in this Series
155421 Series

Use With
Micro-Change (M12) 130047 , 120100 , 130034 , 120071