

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [2043160001](#)  
**Status:** **Active**  
**Overview:**  
**Description:** Sentrality 8.00mm Top-entry, Knurled Press-fit Socket Assembly in Tray

**General**

Product Family	PCB Receptacles
Series	<a href="#">204316</a>
Application	Busbar-to-Board, Busbar-to-Busbar, Power
Comments	Current and voltage performances are dependent upon application variables.
Overview	sentrality-pin-and-socket-interconnect-system
Product Name	Sentrality
Taxonomy	PCB Headers and Receptacles
UPC	191128468701

**Physical**

Circuits (Loaded)	1
Circuits (maximum)	1
Diameter	8.00mm
Durability (mating cycles max)	200
Glow-Wire Capable	No
Guide to Mating Part	No
Height Above Board	4.00mm
Material - Metal	Copper Alloy
Material - Plating Mating	Gold
Material - Plating Termination	Silver
Mating Orientation	Top-entry
Net Weight	8.240/g
Number of Rows	1
Orientation	Vertical
PCB Retention	None
Packaging Type	Tray
Pitch - Mating Interface	N/A
Polarized to PCB	No
Temperature Range - Operating	-40° to +125°C
Termination Interface: Style	Press-Fit

**Electrical**

Current - Maximum per Contact	200.0A
Voltage - Maximum	600V

**Material Info**

**Reference - Drawing Numbers**

Application Specification	2043130001-AS-000
Packaging Specification	2043180001-PK-000
Product Specification	2043130001-PS-000
Sales Drawing	2043160001-SD-000
Test Summary	2043130008-TS-000, 2043131234-TS-000

**EU ELV**

**Not Relevant**

**EU RoHS**

**Compliant**

**REACH SVHC**

Not Contained Per -  
D(2022)4187-DC (10  
June 2022)

**Halogen-Free**

**Status**

**Low-Halogen**

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

**China RoHS**

Green Image

Not Relevant

Not Contained

**Search Parts in this Series**

[204316](#) Series

**Mates With**

8.00mm Male Pin [203263](#)