

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

2043650018

Status:

Active

Overview:

Sentrality Pin and Socket Interconnect System

Description:

Sentrality 3.40mm Top-entry, Surface Mount Socket Assembly with +/-1.00mm Self-alignment Capability in Tray

- Documents:
- 3D Model

Packaging Specification 2043130018-PK-000 (PDF)
- Drawing (PDF)

Test Summary 2043130018-TS-000 (PDF)
- 3D Model (PDF)

Test Summary 2043131234-TS-000 (PDF)
- Product Specification 2043130018-PS-000 (PDF)

Datasheet (PDF)
- Application Specification 2043130018-AS-000 (PDF)

RoHS Certificate of Compliance (PDF)

General	
Product Family	PCB Receptacles
Series	204365
Application	Board-to-Board, Busbar-to-Board, Busbar-to-Busbar, Power
Comments	Current and voltage performances are dependent upon application variables.
Overview	Sentrality Pin and Socket Interconnect System
Product Name	Sentrality
Taxonomy	PCB Headers and Receptacles
UPC	191130519460
Physical	
Circuits (Loaded)	1
Circuits (maximum)	1
Diameter	3.40mm
Durability (mating cycles max)	200
Glow-Wire Capable	No
Guide to Mating Part	Yes
Height Above Board	5.17mm
Material - Metal	Copper Alloy
Material - Plating Mating	Gold
Material - Plating Termination	Silver
Mating Orientation	Top-entry
Net Weight	4.794/g
Number of Rows	1
Orientation	Vertical
PCB Retention	None
Packaging Type	Tray
Pitch - Mating Interface	N/A
Polarized to PCB	No
Temperature Range - Operating	-40° to +125°C
Termination Interface: Style	Surface Mount
Electrical	
Current - Maximum per Contact	75.0A
Voltage - Maximum	600V
Solder Process Data	
Duration at Max. Process Temperature (seconds)	600
Lead-freeProcess Capability	SMC&WAVE
Max. Cycles at Max. Process Temperature	002
Process Temperature max. C	205

Material Info



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

Compliant

REACH SVHC

Not Contained Per - D(2022)4187-DC (10 June 2022)

Halogen-Free

Status

Low-Halogen

For more information, please visit [Contact US](#)

China RoHS

Green Image

ELV

Not Relevant

RoHS Phthalates

Not Contained

Search Parts in this Series
204365 Series

Mates With
3.40mm Male Pin 203263

Reference - Drawing Numbers

Application Specification	2043130018-AS-000
Packaging Specification	2043130018-PK-000
Product Specification	2043130018-PS-000
Sales Drawing	2043650018-SD-000
Test Summary	2043130018-TS-000, 2043131234-TS-000

This document was generated on 08/31/2022

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION