



|                                |                |
|--------------------------------|----------------|
| Material - Plating Termination | Nickel         |
| Material - Resin               | Nylon          |
| Net Weight                     | 2.612/g        |
| Number of Rows                 | 1              |
| Orientation                    | Vertical       |
| PC Tail Length                 | 3.90mm         |
| PCB Locator                    | Yes            |
| PCB Retention                  | None           |
| PCB Thickness - Recommended    | 1.40mm         |
| Packaging Type                 | Bag            |
| Pitch - Mating Interface       | 5.00mm         |
| Pitch - Termination Interface  | 5.00mm         |
| Shrouded                       | Fully          |
| Stackable                      | No             |
| Surface Mount Compatible (SMC) | No             |
| Temperature Range - Operating  | -20° to +120°C |
| Termination Interface: Style   | Through Hole   |

**Electrical**

|                               |         |
|-------------------------------|---------|
| Current - Maximum per Contact | 16.0A   |
| Voltage - Maximum             | 250V AC |

**Material Info**

|                    |               |
|--------------------|---------------|
| Engineering Number | WITH ZYTEL RM |
|--------------------|---------------|

**Reference - Drawing Numbers**

|                         |                   |
|-------------------------|-------------------|
| Packaging Specification | PK-90858-001-001  |
| Product Specification   | PS-99020-0037-001 |
| Sales Drawing           | 919990001-000     |

This document was generated on 08/31/2022

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**