

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [2183221051](#)
Status: **Active**
Overview: [DuraClik Connector System](#)
Description: DuraClik ISL-to-DuraClik ISL Off-the-Shelf (OTS) Cable Assembly, 2.00mm Pitch, Single Row, 150.00mm Length, 5 Circuits, White

Documents:

[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)
[Datasheet \(PDF\)](#)

General

Product Family Cable Assemblies
Series [218322](#)
Application Automotive, Signal, Wire-to-Board
Assembly Configuration Dual Ended Connectors
Connector to Connector DuraClik ISL-to-DuraClik ISL
Overmolded No
Overview [DuraClik Connector System](#)
Product Name DuraClik
Type Discrete Wire Assembly
UPC 195842351622

Physical

Cable Length 150.00mm
Circuits (Loaded) 5
Color - Resin White
Gender Female-Female
Lock to Mating Part Yes
Material - Metal Copper Alloy
Material - Plating Mating Tin
Material - Plating Termination Tin
Material - Resin PBT
Net Weight 4.350/g
Number of Rows 1
Packaging Type Bag
Pitch - Mating Interface 2.00mm
Single Ended No
Termination Interface: Style Crimp or Compression
Wire Insulation Diameter 1.30mm
Wire Size AWG 22
Wire/Cable Type 1x0.35mm² FLRY-A

Electrical

Current - Maximum per Contact 3.0A
Voltage - Maximum 60V AC/DC

Material Info

Reference - Drawing Numbers

Sales Drawing 2183221051-000



EU ELV

Not Relevant

EU RoHS

Compliant

China RoHS

REACH SVHC

Not Contained Per -
D(2021)4569-DC (8
July 2021)

Halogen-Free

Status

Not Low-Halogen

For more information, please visit [Contact US](#)

China ROHS	Green Image
ELV	Not Relevant
RoHS Phthalates	Not Contained

Search Parts in this Series

[218322](#) Series

Mates With

DuraClik Right-Angle Header [502352](#) .
DuraClik Vertical Header [560020](#)