


Home: Crimp Housings >

Part Number: 03-09-2014
2.36mm Diameter Standard .093" Pin and Socket Plug Housing, 1 Circuit



Series image - Reference only

Table with 2 columns: Label (Status, Replacement, Series, Category, Overview, Engineering/Old PN) and Value (OBSELETE, NONE, 1951, Crimp Housings, Standard .093" Pin and Socket Connectors, 1951-P)

CHECK DISTRIBUTOR INVENTORY

- Add to My Parts
Email this page

Go to Part Detail

Use With:
1189 Crimp Terminals, 1190 Crimp Terminals, 1380 Male Crimp Terminals, 1381 Female Crimp Terminals, 1433 Crimp Terminals, 1434 Male Crimp Terminals, 2605, 2606, 1973, 2151, 2273, 2870, Li nk:2871, 4272

Specifications & Other Documents:

Note - Please disable browser pop-up blockers to view documents on www.molex.com

Product Environmental Compliance

Questions on Product Environmental Compliance? Email productcompliance@molex.com

EU ELV: Not Relevant
EU RoHS: Compliant
China RoHS:
REACH SVHC: Not Contained Per - ED/79/2015 (17 December 2015)
Low-Halogen Status: Low-Halogen

- RoHS Certificate of Compliance (PDF)
Multiple Part Product Compliance Form

Part Detail

COLLAPSE ALL

General

Table with 2 columns: Field (Status, Category, Series, Application, Comments, Obsolete Date, Overview, Product Name, UPC) and Value (Obsolete, Crimp Housings, 1951, Power, 17.0A max. can be achieved when housing is used with 42477 or 42478 terminals, 2001/01/01, Standard .093" Pin and Socket Connectors, Standard .093", 800753614796)

Physical

Table with 2 columns: Field (Circuits (maximum), Color - Resin, Gender, Glow-Wire Compliant) and Value (1, Natural, Dual, No)

Application Tooling

FAQ

Tooling specifications and manuals are found by selecting the products below.
Crimp Height Specifications are then contained in the Application Tooling Specification document.

Previously Available Application Tooling

Check our list of old tooling that used to be available for this part

Lock to Mating Part	Yes
Material - Resin	Nylon
Net Weight	2.236/g
Number of Rows	1
Packaging Type	Bag
Panel Mount	No
Pitch - Mating Interface	N/A
Pitch - Termination Interface	N/A
Stackable	No
Temperature Range - Operating	-40°C to +105°C

▼ Electrical

(Please review the Product Specification for specific details.)

Current - Maximum per Contact	14.0A
-------------------------------	-------

▼ Material Info

Old Part Number	1951-P
-----------------	--------

PRODUCTS

Antennas
Application Tooling
Cable Assemblies
Connectors
Copper Flex
Electrical Products
Industrial Automation
Membrane Switches
Optical Solutions
PCB Assemblies
Solid State Lighting

QUICK LINKS

Contact Molex
Cross-Reference
Industries
Literature
Press Room / Press Releases
Product Index
Sitemap

RESOURCES

California Supply Chains Act
Careers
Compliance
ecocare
Feedback | Help
Legal | Trademarks
Mobile Site
Supplier Portal
Privacy Policy

STAY CONNECTED

