

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [0351800209](#)  
**Status:** **Active**  
**Overview:** [VersaBlade Wire-to-Wire Connector System](#)  
**Description:** [VersaBlade Multi-Module Hybrid Receptacle Housing, with Mounting Ears, 2 Circuits, Type A, Natural, Glow-Wire Capable](#)

**Documents:**

<a href="#">Drawing (PDF)</a>	<a href="#">Packaging Specification 351800200SPK-001 (PDF)</a>
<a href="#">Product Specification 351800200PS-000 (PDF)</a>	<a href="#">Datasheet (PDF)</a>
<a href="#">Application Specification 351500000ASENG-000 (PDF)</a>	<a href="#">Brochure (PDF)</a>
<a href="#">Application Specification 351500000ASKOR-000 (PDF)</a>	<a href="#">RoHS Certificate of Compliance (PDF)</a>

**General**

Product Family	Crimp Housings
Series	<a href="#">35180</a>
Application	Power, Wire-to-Wire
Overview	<a href="#">VersaBlade Wire-to-Wire Connector System</a>
Product Name	VersaBlade
UPC	195842650565

**Physical**

Circuits (maximum)	2
Color - Resin	Natural
Gender	Receptacle
Glow-Wire Capable	Yes
Keying to Mating Part	None
Lock to Mating Part	Yes
Material - Resin	PET/PC
Net Weight	3.083/g
Number of Rows	2
Packaging Type	Bag
Panel Mount	Yes
Pitch - Mating Interface	8.00mm
Pitch - Termination Interface	8.00mm
Polarized to Mating Part	Yes
Stackable	No
Temperature Range - Operating	-40° to +110°C

**Material Info**

**Reference - Drawing Numbers**

Application Specification	351500000AS_ENG-000, 351500000AS_KOR-000
Packaging Specification	351800200SPK-001
Product Specification	351800200PS-000
Sales Drawing	351800200-000



*Series image - Reference only*

**EU ELV**

**Not Relevant**

**EU RoHS**

**Compliant**

**REACH SVHC**

Not Contained Per -  
D(2021)4569-DC (8  
July 2021)

**Halogen-Free**

**Status**

**Not Low-Halogen**

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

**China RoHS**

Green Image

Not Relevant

Not Contained

**Search Parts in this Series**

[35180 Series](#)

**Mates With**

VersaBlade Multi-Module Hybrid Plug Housing [359659200](#)

**Use With**

VersaBlade Crimp Terminals [35745](#) .  
VersaBlade TPA [359650290](#) , [359650292](#) ,  
[359650293](#)