

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0039000215](#)
Status: **Active**
Overview: Mini-Fit Family Power Connectors
Description: Mini-Fit Female Crimp Terminal, Tin (Sn) over Phosphor Bronze, 22-28 AWG, Reel

Documents:

| | |
|--|---|
| Drawing (PDF) | Product Specification PS-5556-002-001 (PDF) |
| Product Specification 55560002-PS-CH-000 (PDF) | Application Specification 55560001-AS-000 (PDF) |
| Product Specification 55560002-PS-ES-000 (PDF) | Packaging Specification 55560001-PK-000 (PDF) |
| Product Specification 55560002-PS-SK-000 (PDF) | Test Summary 55560010-TS-000 (PDF) |
| Product Specification 55560008-TS-000 (PDF) | Test Summary TS-5556-002-001 (PDF) |
| Product Specification PS-5556-001-001 (PDF) | RoHS Certificate of Compliance (PDF) |



General

| | |
|-------------------------|--|
| Product Family | Crimp Terminals |
| Series | 5556 |
| Application | Power, Wire-to-Board, Wire-to-Wire |
| Crimp Quality Equipment | Yes |
| Overview | Mini-Fit Family Power Connectors |
| Packaging Alternative | 39000216 (Loose) |
| Product Name | Mini-Fit |
| Taxonomy | Crimp Terminals |
| UPC | 800754396233 |

Physical

| | |
|--------------------------------|----------------------|
| Durability (mating cycles max) | 30 |
| Gender | Female |
| Material - Metal | Phosphor Bronze |
| Material - Plating Mating | Tin |
| Material - Plating Termination | Tin |
| Net Weight | 186.000/mg |
| Packaging Type | Reel |
| Plating min - Mating | 2.540µm |
| Plating min - Termination | 1.270µm |
| Termination Interface: Style | Crimp or Compression |
| Wire Insulation Diameter | 0.90-1.80mm |
| Wire Size AWG | 22, 24, 26, 28 |
| Wire Size mm ² | N/A |

Electrical

| | |
|-------------------------------|------|
| Current - Maximum per Contact | 9.0A |
| Voltage - Maximum | 600V |

Solder Process Data

| | |
|-----------------------------|-----|
| Lead-freeProcess Capability | N/A |
|-----------------------------|-----|

Material Info

| | |
|--------------------|------------|
| Engineering Number | 5556-PBS2P |
|--------------------|------------|

Reference - Drawing Numbers

| | |
|---------------------------|---|
| Application Specification | 55560001-AS-000 |
| Packaging Specification | 55560001-PK-000 |
| Product Specification | 55560002-PS-CH-000, 55560002-PS-ES-000, 55560002-PS-SK-000, 55560008-TS-000, PS-5556-001-001, PS-5556-002-001 |
| Sales Drawing | SD-5556-SPX-001 |
| Test Summary | 55560010-TS-000, TS-5556-002-001 |

EU ELV

Not Relevant

EU RoHS

Compliant

REACH SVHC

Not Contained Per -
D(2022)4187-DC (10
June 2022)

Halogen-Free

Status

Low-Halogen

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

China RoHS

Green Image

Not Relevant

Not Contained

Search Parts in this Series

[5556 Series](#)

Use With

Mini-Fit Jr. Receptacle Housing [5557](#)

Mini-Fit BMI Slide and Lock Panel
 Mount [44516](#)
Mini-Fit BMI Panel Mount
 Receptacle Housing
 [42474](#) , [43760](#)

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description

Product #

| | |
|--|---------------------------|
| PremiumGrade Hand | 638191000 |
| Crimp Tool for Mini-Fit Jr. Male and Female Terminals, 22-28 AWG | |
| FineAdjust Applicator | 639002700 |
| for Insulation OD | |

1.30-1.50mm, 22-28
AWG Wire
FineAdjust Applicator 639020200
for Insulation OD
1.10-1.30mm - 22-28
AWG
FineAdjust Applicator 639023800
for Insulation OD
0.95-1.08mm - 22-28
AWG
T2 Terminator 639102700
for Insulation OD
1.30-1.50mm, 22-28
AWG
T2 Terminator 639120200
for insulation OD
1.10-1.30mm - 22-28
AWG
T2 Terminator 639123800
for insulation OD
0.95-1.08mm - 22-28
AWG

This document was generated on 09/27/2022

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION