

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0457501111](#)
Status: **Active**
Overview: [Mini-Fit Family Power Connectors](#)
Description: [Mini-Fit Plus Crimp Terminal, 18-20 AWG, Reel, Copper \(Cu\) Alloy, Tin \(Sn\)](#)

Documents:

[Drawing \(PDF\)](#) [Product Specification PS-45750-001-001 \(PDF\)](#)
[Product Specification 55560008-TS-000 \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

General

Product Family	Crimp Terminals
Series	45750
Application	Power, Wire-to-Board, Wire-to-Wire
Comments	Current = 13A max. per circuit when header is mated to a receptacle loaded with 45750 series terminals crimped to 16 AWG wire. . See Molex product specification PS-45750-001 for additional current de-rating information. Series 45750 is Hot-Swappable
Crimp Quality Equipment Overview	Yes
Packaging Alternative	Mini-Fit Family Power Connectors
Product Name	457501112 (Loose)
Taxonomy	Mini-Fit Plus
UPC	Crimp Terminals 822350286015

Physical

Durability (mating cycles max)	100
Gender	Female
Material - Metal	Copper Alloy
Material - Plating Mating	Tin
Material - Plating Termination	Tin
Net Weight	0.150/g
Packaging Type	Reel
Plating min - Mating	2.540µm
Plating min - Termination	2.540µm
Termination Interface: Style	Crimp or Compression
Wire Insulation Diameter	1.80-3.10mm
Wire Size AWG	18, 20
Wire Size mm²	N/A

Electrical

Current - Maximum per Contact	13.0A
Voltage - Maximum	600V

Solder Process Data

Lead-freeProcess Capability	N/A
-----------------------------	-----

Material Info

Reference - Drawing Numbers

Product Specification	55560008-TS-000, PS-45750-001-001
Sales Drawing	SD-45750-001-001, SDIN-45750-001-001



Series image - Reference only

EU ELV

Compliant

EU RoHS

Compliant

REACH SVHC

Not Contained Per -
D(2022)4187-DC (10
June 2022)

Halogen-Free

Status

Low-Halogen

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

China RoHS

Green Image

Compliant

Not Contained

Search Parts in this Series

[45750 Series](#)

Use With

[5557](#) Mini-Fit Jr., [30067](#) Mini-Fit TPA, [42474](#) Mini-Fit BMI Panel Mount, [43760](#) Mini-Fit BMI, [44516](#) Mini-Fit BMI Panel Mount Slide-N-Lock

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description

Product #

Extraction Tool for Mini-Fit Jr. Terminals PremiumGrade Hand	11030044
Crimp Tool for Mini-Fit Jr. Male and Female Terminals, 18-24 AWG	638190901

FineAdjust	<u>639015600</u>
Applicator for 18-20 AWG and 18-24 AWG Wires with Insulation Diameter 1.90-2.30mm	
FineAdjust Applicator	<u>639023900</u>
for Insulation OD 1.40-1.70mm - 18-24 AWG	
FineAdjust Applicator	<u>639024800</u>
for Insulation OD 2.50-2.95mm Optimized for 18 AWG Only	
FineAdjust Applicator	<u>639024900</u>
for Insulation OD 2.30-2.60mm - 18-24 AWG	
FineAdjust Applicator	<u>639047800</u>
for Insulation OD 2.50-2.95mm, 18-24 AWG	
FineAdjust Applicator	<u>639048000</u>
for Insulation OD 1.65-2.05mm, 18-24 AWG	
T2 Terminator	<u>639115600</u>
for insulation OD 1.90-2.30mm - 18-24 AWG	
T2 Terminator	<u>639123900</u>
for insulation OD 1.40-1.70mm - 18-24 AWG	
T2 Terminator	<u>639124800</u>
for insulation OD 2.50-2.95mm optimized for 18 AWG only	
T2 Terminator	<u>639124900</u>
for insulation OD 2.30-2.60mm - 18-24 AWG	
T2 Terminator	<u>639147800</u>
for Mini-Fit Crimp Terminals, 18-24 AWG with Large Insulation ODs	
T2 Terminator	<u>639148000</u>
for Mini-Fit Crimp Terminals, 18-24 AWG with Smaller Insulation ODs	

This document was generated on 09/26/2022

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION