

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0462355002

Status:

Active

Overview:

Micro-Fit Connector System

Description:

Micro-Fit RMF High Mating Cycle, Reduced Mating Force, Crimp Terminal, Female, with 0.76µm Selective Gold (Au) over Nickel (Ni), 20-24 AWG, with Lubricant



Series image - Reference only

Documents:

- [Drawing \(PDF\)](#)[Product Specification PS-46235-001-001 \(PDF\)](#)[Packaging Specification PK-46235-001-001 \(PDF\)](#)[Test Summary TS-46235-001-001 \(PDF\)](#)
- [Test Summary TS-46235-501-001 \(PDF\)](#)[Datasheet \(PDF\)](#)[RoHS Certificate of Compliance \(PDF\)](#)

General

Product Family	Crimp Terminals
Series	46235
Application	Power, Wire-to-Board, Wire-to-Wire
Comments	90% increase in mating cycles (250 cycles) and up to 50% reduction in mating force
Crimp Quality Equipment	Yes
Overview	Micro-Fit Connector System
Product Name	Micro-Fit RMF
Taxonomy	Crimp Terminals
UPC	883906382384

Physical

Durability (mating cycles max)	250
Gender	Female
Material - Metal	Copper-Zinc-Tin
Material - Plating Mating	Gold
Material - Plating Termination	Nickel
Net Weight	0.076/g
Packaging Type	Reel
Plating min - Mating	0.762µm
Plating min - Termination	1.270µm
Termination Interface: Style	Crimp or Compression
Wire Insulation Diameter	1.85mm max.
Wire Size AWG	20, 22, 24
Wire Size mm²	N/A

Electrical

Current - Maximum per Contact	5.0A
-------------------------------	------

Material Info

Reference - Drawing Numbers

Packaging Specification	PK-46235-001-001
Product Specification	PS-46235-001-001
Sales Drawing	SD-46235-001-001
Test Summary	TS-46235-001-001, TS-46235-501-001

EU ELV

Not Relevant

EU RoHS

Compliant

REACH SVHC

Not Contained Per -
D(2022)4187-DC (10
June 2022)

Halogen-Free

Status

Low-Halogen

For more information, please visit [Contact US](#)

China ROHS	Green Image
ELV	Not Relevant
RoHS Phthalates	Not Contained

Search Parts in this Series

46235 Series

Use With

Micro-Fit 3.0 Receptacle Housings [43025](#)
, [43645](#) . Micro-Fit BMI Panel Mount
Receptacle Housings [44133](#) . Micro-Fit TPA
Receptacle Housing [172952](#)

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description	Product #
Extraction Tool for Micro-Fit Terminals PremiumGrade Hand	11030043 638192900
Crimp Tool for Low Force Micro-Fit 3.0 Terminals, 20-30 AWG	

FineAdjust Applicator639046500
for Low-Force
Micro-Fit 3.0
Terminals, for 20-24
AWG Wire with
Insulation Diameter
1.30-1.85mm
T2 Terminator 639101400
Tooling to be used
with Low Force
Crimp Terminals,
20-24 AWG Wire

This document was generated on 10/10/2022
PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION