

This document was generated on 09/22/2011

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0050362301

Status: **Active** minifit ir **Overview:**

4.20mm (.165") Pitch Mini-Fit Jr.™ Receptacle Housing, Dual Row, PA Polyamide **Description:**

Nylon 6/6, UL 94V-0, 4 Circuits, Glow Wire Compatible

Documents:

3D Model Test Summary TS-5556-002 (PDF) Drawing (PDF) RoHS Certificate of Compliance (PDF)

Product Specification PS-5556-001 (PDF)

Agency Certification

CSA LR19980 UL E29179

General

Product Family Crimp Housings 5557

Series

Power, Wire-to-Wire Application Comments

"Current = 13A max. per circuit when header is mated to a receptacle loaded with 45750 series terminals crimped to 16 AWG wire. . See Molex product specification PS-45750-001 for additional current derating information.<P><P>This Molex product is manufactured from material that has the following ratings, tested by independent agencies:. a) A Glow Wire Ignition Temperature (GWIT) of at least 775 deg C per IEC 60695-2-13.. b) A Glow Wire Flammability Index (GWFI) above 850 deg C per IEC 60695-2-12.and hence complies with the requirements set out in the International Standard IEC 60335-1 5th edition - household and similar electrical appliances - safety, section 30 Resistance to heat and fire. <P><P> The customers using this product must determine its suitability for use in their particular application through testing or other acceptable means as described in end-product glow-wire flammability test standard IEC 60695-2-11 and any applicable product end-use standard(s). <P> If it is determined during the customer's evaluation of suitability, that higher performance is required, please contact Molex for

possible product options."

minifit jr Overview Mini-Fit Jr.™ **Product Name**

Physical

Circuits (maximum) Color - Resin White Flammability 94V-0 Gender Receptacle **Glow-Wire Compliant** Yes Keying to Mating Part None Lock to Mating Part Yes Material - Resin Nylon Number of Rows 2 Packaging Type Bag



EU RoHS ELV and RoHS Compliant **REACH SVHC** Not Reviewed **Low-Halogen Status** Low-Halogen

China RoHS

Need more information on product environmental compliance?

Email productcompliance@molex.com For a multiple part number RoHS Certificate of Compliance, click here

Please visit the Contact Us section for any non-product compliance questions.

Search Parts in this Series 5557Series

Mates With

5559 Crimp Housings Plug, 5566 PCB Header, 5569 PCB Header

Use With

5556 Female Terminal Mini-Fit® Crimp **Terminal**

Panel Mount No

Pitch - Mating Interface 4.20mm (.165")
Pitch - Termination Interface 4.20mm (.165")

Polarized to Mating Part Yes
Ports 1
Stackable No

Temperature Range - Operating -40°C to +105°C

Electrical

Current - Maximum per Contact 13A

Material Info

Old Part Number 5557-04R-225N

Reference - Drawing Numbers

Product Specification PS-5556-001
Sales Drawing SD-5557-003
Test Summary TS-5556-002

This document was generated on 09/22/2011

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION