

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [5007620483](#)
Status: **Active**
Overview: CMC and CMX Sealed, Hybrid, Modular Connectors
Description: 2.50mm, 3.50mm, 3.70mm CMC Header, Right-Angle, 48 Circuits, Brown

Documents:

[3D Model](#) [Product Specification PS-64319-001-001 \(PDF\)](#)
[3D Model \(PDF\)](#) [Datasheet \(PDF\)](#)
[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

General

Product Family PCB Headers
Series [500762](#)
Application Automotive, Power, Wire-to-Board
Comments Coding: Brown
Overview [CMC and CMX Sealed, Hybrid, Modular Connectors](#)
Product Name CMC
Taxonomy PCB Headers and Receptacles
UPC 887191516967

Physical

Breakaway No
Circuits (Loaded) 48
Circuits (maximum) 48
Circuits Detail 8 x 1.5mm & 40 x 0.635mm terminals
Color - Resin Brown
Durability (mating cycles max) 20
First Mate / Last Break Yes
Glow-Wire Capable No
Guide to Mating Part No
Keying to Mating Part Yes
Lock to Mating Part Yes
Material - Metal Copper Alloy
Material - Plating Mating Tin
Material - Plating Termination Tin
Net Weight 35.300/g
Number of Rows 4
Orientation Right Angle
PC Tail Length 3.60mm
PCB Locator Yes
PCB Retention None
PCB Thickness - Recommended 1.60mm
Packaging Type Tray
Pitch - Mating Interface 2.50mm, 3.50mm, 3.70mm
Pitch - Termination Interface 2.50mm, 3.50mm, 3.70mm
Polarized to Mating Part Yes
Polarized to PCB Yes
Shrouded Closed Ends
Stackable No
Surface Mount Compatible (SMC) No
Temperature Range - Operating -40° to +125°C
Termination Interface: Style Solder or Weld

Electrical

Current - Maximum per Contact 12.0A, 2.5A
Voltage - Maximum 14V DC



EU ELV

Compliant

EU RoHS

Compliant

REACH SVHC

Not Contained Per -
D(2022)4187-DC (10
June 2022)

Halogen-Free

Status

Not Low-Halogen

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

China RoHS

Green Image

Compliant

Not Contained

Search Parts in this Series

[500762](#) Series

Mates With

CMC Receptacles [643201319](#) , [643203319](#)

Solder Process Data

Duration at Max. Process Temperature (seconds)	003
Lead-free Process Capability	WAVE
Max. Cycles at Max. Process Temperature	001
Process Temperature max. C	260

Material Info**Reference - Drawing Numbers**

Product Specification	PS-64319-001-001
Sales Drawing	SD-500762-001-001

This document was generated on 09/04/2022

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION