

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [5019512250](#)
Status: **Active**
Overview:
Description: Easy-On FFC/FPC Connector, 0.50mm Pitch, V-Flip Series, Vertical, 4.05mm Height, 22 Circuits, Copper Alloy, 125°C Operating Temperature, Gold Plating

Agency Certification

UL E29179

General

Product Family FFC/FPC Connectors
 Series [501951](#)
 Overview [easyon_ffc_fpc_connectors](#)
 Product Name Easy-On
 Series Name V-Flip
 Taxonomy FFC / FPC Connectors
 UPC 191128825566

Physical

Actuator Type Front Flip
 Circuits (Loaded) 22
 Color - Resin White
 Contact Position N/A
 Durability (mating cycles max) 20
 Flammability 94V-0
 Mated Height 4.05mm
 Material - Metal Copper Alloy
 Material - Plating Mating Gold
 Material - Plating Termination Gold
 Material - Resin Liquid Crystal Polymer
 Net Weight 260.700/mg
 Number of Rows 1
 Orientation Vertical
 PCB Locator No
 PCB Mounting Surface Mount
 PCB Retention Yes
 Packaging Type Embossed Tape on Reel
 Pitch - Mating Interface 0.50mm
 Plating min - Mating 0.102µm
 Plating min - Termination 0.102µm
 Polarized to PCB No
 Stackable No
 Temperature Range - Operating -40° to +125°C
 Wire/Cable Type FFC/FPC

Electrical

Current - Maximum per Contact 0.5A
 Voltage - Maximum 50V

Material Info

Reference - Drawing Numbers

Packaging Specification 5019519200-201
 Product Specification 5019510008-PS-000
 Sales Drawing 5019510008-SD-000, 5019511008-SD-000

EU ELV

Not Relevant

EU RoHS

Compliant

REACH SVHC

Not Contained Per -

Halogen-Free

Status

Low-Halogen

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

China RoHS

Green Image

Not Relevant

Not Contained

Search Parts in this Series

[501951](#) Series

Mates With

Premo-Flex FFC Cable [15020](#)

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION