

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0534261110

Status:

Active

Overview:

Mini-Lock Wire-to-Board Connector System

Description:

2.50mm Pitch, Mini-Lock PCB Header, Single Row, Right-Angle, Through Hole with Kinked Pins, Tin Plating, Positive Lock, 11 Circuits, Tray, 3.40mm PC Tail Length

Documents:

3D Model (PDF)

Drawing (PDF)

3D Model

Product Specification 511630000-PS-000 (PDF)

Product Specification 511631000-PS-000 (PDF)

Product Specification PS-51103-005-001 (PDF)

Packaging Specification SPK-53426-002-001 (PDF)

Datasheet (PDF)

RoHS Certificate of Compliance (PDF)

Agency Certification

CSA

UL

LR19980

E29179

General

Product Family

Series

Application

Overview

Product Name

Taxonomy

UPC

PCB Headers

53426

Signal, Wire-to-Board

Mini-Lock Wire-to-Board Connector System

Mini-Lock

PCB Headers and Receptacles

800753446793

Physical

Breakaway

Circuits (Loaded)

Circuits (maximum)

Color - Resin

Durability (mating cycles max)

Flammability

Glow-Wire Capable

Keying to Mating Part

Lock to Mating Part

Material - Metal

Material - Plating Mating

Material - Plating Termination

Material - Resin

Net Weight

Number of Rows

Orientation

PC Tail Length

PCB Locator

PCB Retention

PCB Thickness - Recommended

Packaging Type

Pitch - Mating Interface

Polarized to Mating Part

Polarized to PCB

Shrouded

Stackable

Temperature Range - Operating

Termination Interface: Style

No

11

11

Natural

30

94V-0

No

None

Yes

Phosphor Bronze

Tin

Tin

Polyester

1407.200/mg

1

Right Angle

3.40mm

No

Yes

1.60mm

Tray

2.50mm

Yes

No

Fully

No

-40° to +105°C

Through Hole - Kinked Pin

Electrical



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

China RoHS

Compliant

REACH SVHC

Not Contained Per -

D(2022)4187-DC (10

June 2022)

Halogen-Free

Status

Not Low-Halogen

For more information, please visit

Contact US

China ROHS

Green Image

ELV

Not Relevant

RoHS Phthalates

Not Contained

Search Parts in this Series
53426 Series

Mates With
Mini-Lock Receptacle 51163 . Mini-Lock Cable Assembly 15137

Current - Maximum per Contact3.0A
Voltage - Maximum250V AC (RMS)/DC

Material Info

Reference - Drawing Numbers

Packaging SpecificationSPK-53426-002-001
Product Specification511630000-PS-000, 511631000-PS-000,
PS-51103-005-001
Sales Drawing534260000-SD-000

This document was generated on 10/01/2022

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION