



基板穴推奨寸法 (部品実装側)
RECOMMENDED P.C.B. LAYOUT
(COMPONENT SIDE)

(SCALE:4-1)

注記 NOTE

1. 嵌合相手 : 51089-**05
MATE WITH : 51089-**05
- △2 イジェクターが開いた状態の寸法を示す。
EJECTORS IN OPEN POSITION.
- △3 公差非累積
TOLERANCES : NON CUMULATIVE

20極 (参考)
20 CIRCUITS

46.1	80.4	71.4	63.6	58	55458 6005	60
36.1	70.4	61.4	53.6	48	55458 5005	50
26.1	60.4	51.4	43.6	38	55458 4005	40
20.1	54.4	45.4	37.6	32	55458 3405	34
16.1	50.4	41.4	33.6	28	55458 3005	30
6.1	40.4	31.4	23.6	18	55458 2005	20
E	(D)	C	B	(A)	オーダー番号 ORDER NUMBER	極数 CKT

部品 PART	材料 MATERIAL			
ハウジング HOUSING	ポリエステル(PBT)、ガラス充填、UL 94V-0、色 : グレー POLYESTER(PBT), GLASS FILLED, UL 94V-0, COLOR:GRAY			
イジェクター EJECTOR	ポリエステル(PBT)、ガラス充填、UL 94V-0、色 : グレー POLYESTER(PBT), GLASS FILLED, UL 94V-0, COLOR:GRAY			
ピン PIN	黄銅 BRASS			
	金めっき : 0.5µmMIN. GOLD PLATING : 0.5µmMIN.			
	ニッケルめっき(下地) : 1.0~1.5µm NICKEL(UNDER PLATING) : 1.0~1.5µm			
DOCUMENT STATUS	P1	RELEASE DATE	2018/10/16	09:02:14

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		CURRENT REV DESC:		molex	
DIMENSION UNITS	SCALE	EC NO: 605860			
mm	NTS	DRWN: RWATANABE01 2018/10/09		MI II 2.0 W/B DUAL ROW HEADER ASSY WITH EJECTOR	
GENERAL TOLERANCES (UNLESS SPECIFIED)		CHK'D: KOMURAKAMI 2018/10/16			
ANGULAR TOL	± 3.0°	APPR: TKANEKO 2018/10/16		PRODUCT CUSTOMER DRAWING	
4 PLACES	± 0.2	INITIAL REVISION:		DOCUMENT NUMBER	
3 PLACES	± 0.2	DRWN: RWATANABE01 2018/10/09		554580000-SD	
2 PLACES	± 0.2	APPR: TKANEKO 2018/10/16		DOC TYPE	DOC PART
1 PLACE	± 0.2	THIRD ANGLE PROJECTION		PSD	000
0 PLACES	± 0.2	DRAWING	SERIES	REVISION	A
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		A3-SIZE	55458	MATERIAL NUMBER	CUSTOMER
		SEE CHART	GENERAL	SHEET NUMBER	
				1 OF 1	