

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [0737802257](#)  
**Status:** **Active**  
**Overview:** [HDM Backplane Connector System](#)  
**Description:** HDM Board-to-Board Daughtercard Receptacle, Vertical, Signal Module, 72 Circuits, Mounted Height 17.00mm, Pin Length 3.50mm, Press-Fit

**Documents:**

[Drawing \(PDF\)](#) [Application Specification AS-73670-9998-001 \(PDF\)](#)  
[Product Specification PS-73780-999-001 \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

**Agency Certification**


UL E29179

**General**

Product Family Backplane Connectors  
 Series [73780](#)  
 Application Daughtercard, Mezzanine  
 Comments Press-Fit Tail  
 Component Type PCB Receptacle  
 Data Rate 1.0 Gbps  
 Overview [HDM Backplane Connector System](#)  
 Product Name HDM  
 Taxonomy Backplane Connectors  
 UPC 800756550268

**Physical**

Circuits (Loaded) 72  
 Circuits (maximum) 72  
 Color - Resin Black  
 Durability (mating cycles max) 250  
 First Mate / Last Break No  
 Flammability 94V-0  
 Guide to Mating Part No  
 Keying to Mating Part None  
 Material - Metal Copper-Nickel-Tin  
 Material - Plating Mating Gold  
 Material - Plating Termination Tin  
 Material - Resin High Temperature Thermoplastic  
 Net Weight 9.498/g  
 Number of Columns 12  
 Number of Pairs Open Pin Field  
 Number of Rows 6  
 Orientation Vertical  
 PC Tail Length 3.50mm  
 PCB Locator No  
 PCB Retention None  
 PCB Thickness - Recommended 1.60mm  
 Packaging Type Tube  
 Pitch - Mating Interface 2.00mm  
 Pitch - Termination Interface 2.00mm  
 Plating min - Mating 0.762µm  
 Plating min - Termination 0.889µm  
 Polarized to PCB No  
 Stackable Yes  
 Surface Mount Compatible (SMC) Yes  
 Temperature Range - Operating -55° to +105°C  
 Termination Interface: Style Through Hole - Compliant Pin



**EU ELV**

**Not Relevant**

**EU RoHS**

**Compliant**

**REACH SVHC**

Not Contained Per -  
 D(2022)4187-DC (10  
 June 2022)

**Halogen-Free**

**Status**

**Low-Halogen**

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

Green Image

Not Relevant

Not Contained

**Search Parts in this Series**

[73780](#) Series

**Mates With**

HDM Board-to-Board Backplane Header  
[73642](#) , [73643](#) , [73644](#) , [73942](#) , [73943](#) ,  
[73944](#) , [74349](#) , [74428](#). HDM Board-to-  
 Board Stacking Header [73769](#) , [73770](#) ,  
[73782](#) , [73783](#) , [73771](#)

**Electrical**

Current - Maximum per Contact	15.0A, 1.0A
Real Signals (per 25mm)	75
Shielded	No
Voltage - Maximum	250V AC

**Solder Process Data**

Lead-freeProcess Capability	N/A
-----------------------------	-----

**Material Info****Reference - Drawing Numbers**

Application Specification	AS-73670-9998-001
Product Specification	PS-73780-999-001
Sales Drawing	SD-73780-001-001

This document was generated on 09/26/2022

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**