

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [0762857207](#)  
**Status:** **Active**  
**Overview:** [Impact Backplane Connector and Cable Assembly System](#)  
**Description:** Impact 100 Ohm 6 Pair Vertical Orthogonal Header Left Guided, Right Endwall, 12 Columns, 216 Circuits, Pin Length 4.90mm, Plated Through Hole Dimension 0.39mm, Lead-Free

**Documents:**

|   |  |
|---|--|
| <a href="#">3D Model</a>  | <a href="#">Application Specification AS-76850-990-001 (PDF)</a> |
| <a href="#">Drawing (PDF)</a>                                     | <a href="#">Packaging Specification PK-70873-766-001 (PDF)</a>   |
| <a href="#">3D Model (PDF)</a>                                    | <a href="#">Symbol Footprint Data SYM-76285-7207-001 (PDF)</a>   |
| <a href="#">Product Specification PS-76060-999-001 (PDF)</a>      | <a href="#">RoHS Certificate of Compliance (PDF)</a>             |
| <a href="#">Application Specification AS-76060-9999-001 (PDF)</a> |  |

**Agency Certification**


UL E29179

**General**

|                               |  |
|-------------------------------|--|
| Product Family                | Backplane Connectors   |
| Series                        | <a href="#">76285</a>  |
| Application                   | Orthogonal Midplane  |
| Application Tooling Documents | TM-622018799-001   |
| Component Type                | PCB Header   |
| Data Rate                     | 25.0 Gbps  |
| Overview                      | <a href="#">Impact Backplane Connector and Cable Assembly System</a> |
| Product Name                  | Impact   |
| Taxonomy                      | Backplane Connectors   |
| UPC                           | 884982039704   |

**Physical**

|                                |                                |
|--------------------------------|--------------------------------|
| Circuits (Loaded)              | 216                            |
| Circuits (maximum)             | 216                            |
| Color - Resin                  | Black                          |
| Durability (mating cycles max) | 200                            |
| First Mate / Last Break        | No                             |
| Flammability                   | 94V-0                          |
| Guide to Mating Part           | Yes                            |
| Keying to Mating Part          | None                           |
| Material - Metal               | High Performance Alloy (HPA)   |
| Material - Plating Mating      | Gold                           |
| Material - Plating Termination | Tin                            |
| Material - Resin               | High Temperature Thermoplastic |
| Net Weight                     | 8.384/g                        |
| Number of Columns              | 12                             |
| Number of Pairs                | 6                              |
| Number of Rows                 | 18                             |
| Orientation                    | Vertical                       |
| PC Tail Length                 | 1.40mm                         |
| PCB Locator                    | No                             |
| PCB Retention                  | Yes                            |
| PCB Thickness - Recommended    | 3.00mm                         |
| Packaging Type                 | Tray                           |
| Pitch - Mating Interface       | 1.90mm, 2.15mm                 |
| Pitch - Termination Interface  | 1.90mm, 2.15mm                 |
| Plating min - Mating           | 0.762µm                        |
| Polarized to PCB               | No                             |



*Series image - Reference only*

**EU ELV**

**Not Relevant**

**EU RoHS**

**Compliant**

**REACH SVHC**

Not Contained Per -  
D(2022)4187-DC (10  
June 2022)

**Halogen-Free**

**Status**

**Low-Halogen**

For more information, please visit [Contact US](#)

China ROHS

ELV

RoHS Phthalates

**China RoHS**

Green Image

Not Relevant

Not Contained

**Search Parts in this Series**

[76285 Series](#)

**Mates With**

[76290](#) Impact 100 Ohm Right Angle Orthogonal Daughtercard

|                               |                              |
|-------------------------------|------------------------------|
| Stackable                     | No                           |
| Temperature Range - Operating | -55° to +85°C                |
| Termination Interface: Style  | Through Hole - Compliant Pin |

**Electrical**

|                               |                 |
|-------------------------------|-----------------|
| Current - Maximum per Contact | 0.75A           |
| Impedance                     | 100Ω            |
| Shield Type                   | N/A             |
| Shielded                      | No              |
| Voltage - Maximum             | 30V AC (RMS)/DC |

**Solder Process Data**

|                              |     |
|------------------------------|-----|
| Lead-free Process Capability | N/A |
|------------------------------|-----|

**Material Info****Reference - Drawing Numbers**

|                           |                                     |
|---------------------------|-------------------------------------|
| Application Specification | AS-76060-9999-001, AS-76850-990-001 |
| Packaging Specification   | PK-70873-766-001                    |
| Product Specification     | PS-76060-999-001                    |
| Sales Drawing             | SD-76285-002-001                    |
| Symbol/Footprint Data     | SYM-76285-7207-001                  |

This document was generated on 09/27/2022

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**