

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0876781001

Status:

Active

Overview:

Serial ATA Connectors

Description:

1.27mm Pitch Serial ATA Backplane Receptacle, Through Hole, Vertical, Extended Height, 0.76µm Gold (Au) Selective, 22 Circuits, Lead-Free

Documents:

3D Model

Packaging Specification PK-87678-100-001 (PDF)

Drawing (PDF)

RoHS Certificate of Compliance (PDF)


Product Specification PS-87678-029-001 (PDF)

Agency Certification		
CSA		LR19980
UL		E29179
General		
Product Family		PCB Receptacles
Series		87678
Application		Board-to-Board, Signal
Overview		Serial ATA Connectors
Product Name		Serial ATA
Taxonomy		PCB Headers and Receptacles
UPC		822348693399

Physical		
(p)ower-(s)ignal Configuration		15p - 7s
Circuits (Loaded)		22
Circuits (maximum)		22
Durability (mating cycles max)		500
Flammability		94V-0
Glow-Wire Capable		No
Guide to Mating Part		Yes
Lock to Mating Part		Yes
Material - Metal		Copper
Material - Plating Mating		Gold
Material - Plating Termination		Tin
Net Weight		1.897/g
Number of Rows		1
Orientation		Vertical
PC Tail Length		3.45mm
PCB Locator		Yes
PCB Retention		None
PCB Thickness - Recommended		0.80mm, 2.50mm
Packaging Type		Tray
Pitch - Mating Interface		1.27mm
Plating min - Mating		0.762µm
Plating min - Termination		2.540µm
Polarized to Mating Part		Yes
Polarized to PCB		Yes
Surface Mount Compatible (SMC)		Yes
Temperature Range - Operating		-40° to +105°C
Termination Interface: Style		Through Hole - Compliant Pin

Electrical		
Current - Maximum per Contact		1.5A
Voltage - Maximum		30V

Solder Process Data



Series image - Reference only

EU ELV	
Not Relevant	
EU RoHS	China RoHS
Compliant	
REACH SVHC	
Not Contained Per - D(2022)4187-DC (10 June 2022)	
Halogen-Free	
Status	
Low-Halogen	
For more information, please visit Contact US	
China ROHS	Green Image
ELV	Not Relevant
RoHS Phthalates	Not Contained

Search Parts in this Series

87678 Series

Mates With

87679 , 87799 , 87703

Duration at Max. Process Temperature (seconds)	010
Lead-freeProcess Capability	SMC&WAVE
Max. Cycles at Max. Process Temperature	001
Process Temperature max. C	260

Material Info

Reference - Drawing Numbers

Electrical Model Document	EE-87678-001-001
Packaging Specification	PK-87678-100-001
Product Specification	PS-87678-029-001
Sales Drawing	SD-87678-023-001

This document was generated on 08/31/2022

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION