

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0903273306

Status:

Active

Overview:

Picoflex Ribbon-Cable Connectors

Description:

Picoflex PF-50, Low Profile, IDT Receptacle, 6 Circuits, White, Gold (Au) Plated, Bag

Documents:

3D Model (PDF)

Product Specification PS-99020-0011-001 (PDF)

Drawing (PDF)

Packaging Specification PK-90327-001-001 (PDF)

3D Model

RoHS Certificate of Compliance (PDF)

Agency Certification		
CSA		LR19980
UL		E29179
General		
Product Family		Ribbon Cable / Wire Trap Connectors
Series		90327
Comments		Low Profile
Component Type		Housing
Glow-Wire Capable		No
Overview		Picoflex Ribbon-Cable Connectors
Product Name		Picoflex
Taxonomy		Connector Housings
UPC		800753669970

Physical		
Circuits (Loaded)		6
Circuits (maximum)		6
Color - Resin		White
Durability (mating cycles max)		100
Entry Angle		Vertical
Flammability		94V-0
Lock to Mating Part		Yes
Material - Metal		Phosphor Bronze
Material - Plating Mating		Gold
Material - Plating Termination		Gold
Material - Resin		Polyester
Net Weight		1.096/g
Number of Rows		2
PCB Locator		No
PCB Retention		None
Packaging Type		Bag
Pitch - Mating Interface		1.27mm
Pitch - Termination Interface		1.27mm
Polarized to Mating Part		Yes
Polarized to PCB		No
Shrouded		Fully
Stackable		No
Surface Mount Compatible (SMC)		N/A
Temperature Range - Operating		-40° to +105°C
Termination Interface: Style		IDT or Pierce
Wire Insulation Diameter		1.00mm max.
Wire Size AWG		26, 28
Wire/Cable Type		Ribbon Cable

Electrical		
Current - Maximum per Contact		1.2A



Series image - Reference only

EU ELV	
Not Relevant	
EU RoHS	China RoHS
Compliant	
REACH SVHC	
Not Contained Per - D(2022)4187-DC (10 June 2022)	
Halogen-Free	
Status	
Not Low-Halogen	
For more information, please visit Contact US	
China ROHS	Green Image
ELV	Not Relevant
RoHS Phthalates	Not Contained

Search Parts in this Series

90327 Series

Mates With

Low Profile Vertical 90325 , Low Profile Right Angle 90800 , 90715 , 90814 , 90779 Vertical, 91714 1.27mm Pitch Picoflex PF-50 Header

Application Tooling | [FAQ](#)

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global	
Description	Product #
Extractor Tool for Connectors	621006000
Extraction Tool for Picoflex PF-50 Connectors, 4-26 Circuits	690081070
PremiumGrade Hand Crimp Tool	690081090

Voltage - Maximum	250V	for Picoflex PF-50
Solder Process Data		IDT Receptacle,
Lead-freeProcess Capability	N/A	4-26 Circuits, 26
Material Info		or 28 AWG Flat
Reference - Drawing Numbers		Cable, 1.00mm max.
Packaging Specification	PK-90327-001-001	thickness
Product Specification	PS-99020-0011-001	Arbor Press Fixture 690201902
Sales Drawing	SDA-90327-001	Arbor Press Fixture 690201908
		Semi-Automatic 691271001
		Bench Press PB14
		for 4-26 Circuit
		Semi-Automatic 691271004
		PB14 Bench Press
		with Auto De-reeling
		Assembly of De- 691275045
		Tape Unit for
		PB14 Part Number
		691271001

This document was generated on 09/09/2022

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION