



SPECIFICATION SHEET

33-VRX180



G-TEK® VR-X™ NYLON GLOVE WITH POLYURETHANE COATING – TOUCHSCREEN COMPATIBLE

- Nylon blended shell, featuring an ultra-thin 18 gauge liner for exceptional dexterity
- VR-X™ Polyurethane coating on full hand provides advanced barrier protection against micro-organism risks, the treated coating provides a tactile grip in wet, dry and slightly oily conditions
- ESD Safe, Surface Resistance per ESD S11.11 Static dissipative range at 10⁸ ohms, 12%RH, 48hrs @100Volts
- 4.0 AQL, similar to the AQL levels for industrial grade disposable gloves
- Touchscreen compatible to allow the user to operate a touch screen phone or device without removing gloves
- Silicone Free
- Washable, resistant to water and ultraviolet light
- Recommended wash cycle: Maximum 6 cycles

APPLICATIONS

- Inspection
- Construction
- Maintenance and Repair
- Manufacturing
- Precision Assembly
- Shipping and Packaging
- Small Parts Handling

CARE INSTRUCTIONS

Recommend washing gloves in slightly warm water not exceeding 40°C. A mild non-ionic detergent should be used. A 5-10 minute cycle time should be employed. Tumble dry on low - maximum temperature 140°F (60°C).

TECHNICAL DATA

| | | | | | | |
|-----------------|---|-----------------|-------------------|--------------------|----------------|--------------------|
| MATERIAL | Nylon / Treated Polyurethane coating on full hand | | | | | |
| CONSTRUCTION | 18 Gauge seamless knit | | | | | |
| COLOR | Shell: ■ Blue / Coating: ■ Black | | | | | |
| SIZES | XS - XXL | | | | | |
| PACKAGING | 1 pair per bag, 12 pairs per dozen, 12 dozen per case | | | | | |
| CASE DIMENSIONS | 15" x 12.2" x 10.6" / 38cm x 31cm x 27cm | | | | | |
| CASE WEIGHT | XS | S | M | L | XL | XXL |
| | 8.4 lbs 3.8 kg | 8.8 lbs 4 kg | 9.5 lbs 4.3 kg | 10.1 lbs 4.6 kg | 11 lbs 5 kg | 11.9 lbs 5.4 kg |
| COO | China | | | | | |

PERFORMANCE PROPERTIES

| | | | | | | |
|----------------|--|---|---|---|---|---|
| EN388: 3111X | | | | | | |
| ABRASION | 0 | 1 | 2 | 3 | 4 | - |
| CUT | X | 1 | 2 | 3 | 4 | 5 |
| TEAR | 0 | 1 | 2 | 3 | 4 | - |
| PUNCTURE | 0 | 1 | 2 | 3 | 4 | - |
| ISO EN374-2 | Test method for determining the penetration resistance of gloves that protect against dangerous chemicals and/or micro-organisms | | | | | |
| ISO EN374-5 | Performance testing and terminology to determine protection against micro-organisms risks | | | | | |
| ISO 21702:2019 | Test method for antiviral activity on non-porous products | | | | | |
| ISO 20743:2013 | Specifies quantitative test methods to determine the antibacterial activity of all antibacterial textile products including nonwovens. | | | | | |
| CE CAT III | Suitable for potentially fatal risks | | | | | |




BARCODES

| ITEM | PAIR | PACK | CASE |
|-----------------|--------------|----------------|----------------|
| ■ 33-VRX180/XS | 616314373398 | 10616314373395 | 20616314373392 |
| ■ 33-VRX180/S | 616314373411 | 10616314373418 | 20616314373415 |
| ■ 33-VRX180/M | 616314373435 | 10616314373432 | 20616314373439 |
| ■ 33-VRX180/L | 616314373459 | 10616314373456 | 20616314373453 |
| ■ 33-VRX180/XL | 616314373480 | 10616314373487 | 20616314373484 |
| ■ 33-VRX180/XXL | 616314373534 | 10616314373531 | 20616314373538 |

DIMENSIONS (in/cm)

| | XS | S | M | L | XL | XXL |
|----------|----------|-----------|----------|------------|-------------|------------|
| A | 9 / 23 | 9.4 / 24 | 9.8 / 25 | 10.2 / 26 | 10.4 / 26.5 | 10.6 / 27 |
| B | 3.5 / 9 | 3.7 / 9.5 | 3.9 / 10 | 4.1 / 10.5 | 4.3 / 11 | 4.5 / 11.5 |
| H | ■ Purple | ■ Red | ■ Yellow | ■ Brown | ■ Black | ■ Blue |



PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

AMERICAS: (800) 262-5755 • (518) 861-0133 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | www.pipglobal.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED.