

SPECIFICATION SHEET

STYLE: 155-0-11



NOVAX®

Class 0 Rubber Insulating Glove with Straight Cuff - 11"

- · Contoured shape reduces hand fatigue
- Natural rubber construction offers the required dielectric properties combined with flexibility, strength and durability
- · Silicone free
- Individually numbered for traceability and stamped with factory manufacturing date
- Meet ANSI/ASTM D120 standard and NFPA 70E for use around electrical hazards and arc flash protection
- A WARNING: Cancer www.P65Warnings.ca.gov

Applications

- Power Generation
- Electrical Contractors
- Plant Maintenance
- Utility Work
- Hybrid Automotive Repair, Service and Manufacturing



Technical Data

Color	Black
Sizes Available	7-12
Packaging	Boxed
Packed	12 Pair/Case
Case Dimensions (in)	16.93 x 16.93 x 12.80
Case Weight (lbs)	10.32
Country of Origin	Malaysia
Material	Rubber
Length	11"
Cuff	Straight
Cuff Color	Orange
Construction	
Certifications	ASTM D120, Silicone Free
Product Circularity	

Performance Data

Electrical Class Class 0

Care Instructions

Wash in warm water (29°C/85°F) with mild detergent and disinfect with a small amount of chlorine bleach. Air or tumble dry at low heat (74°C/165°F). Gloves may be dusted lightly with talc to reduce tackiness. Gloves should be stored in a glove bag, finger tips up, hung and not laid flat. Leather protecting glove should be removed before storage. Never fold gloves. Store in as dry and cool (35°C/95°F maximum) location as possible, away from sources of ozone and direct sunlight.



SPECIFICATION SHEET

STYLE: 155-0-11

SKU Information

SKU	COLOR	SIZE	UPC	UPC (INNER)	UPC (CASE)	
155-0-11/7	Black	7	616314059322	01616314059321	02616314059320	
155-0-11/8	Black	8	616314059339	01616314059338	02616314059337	
155-0-11/9	Black	9	616314059346	01616314059345	02616314059344	
155-0-11/10	Black	10	616314059353	01616314059352	02616314059351	
155-0-11/11	Black	11	616314059360	01616314059369	02616314059368	
155-0-11/12	Black	12	616314059377	01616314059376	02616314059375	