



Technical Data

Color	Clear
Sizes Available	S-XL
Packaging	Bagged Pair
Packed	10 Bags/Case
Case Dimensions (in)	16.00 x 7.00 x 4.00
Case Weight (lbs)	3.00
Country of Origin	Japan
Polymer	Polyethylene
Grip	Smooth
Cuff	Straight
Length	12"
Powder	Powder Free
Thickness	4 Mil
Construction	Unsupported, ESD Safe
Certifications	TAA Compliant
Product Circularity	Recycled via Terracycle

QRP® PolyTuff®

Polyurethane ISO 5 (Class 100) Static Dissipative Gloves - 4 mil

- Packaged for ISO 5 (Class 100) applications
- Unique, form-flexible PolyTuff polyurethane (4 mil) film wicks perspiration away for greater comfort
- Ergonomic Comfort Curve hand specific design
- Resists common solvents such as MeCl, TCE, and IPA
- Anti-static 10(9) ohms per square surface unit
- For use with Class II static sensitive devices (thresholds above 1000V)
- Compliant with ASTM and IEST-RP-CC005.3 standards
- RoHS Compliant
- Sulfur free

Performance Data

ISO Cleanroom	ISO 5 (Class 100)
Temperature Resistant	--
Static Control Property	Static Dissipative

Care Instructions

KEY: Made from recycled or bio-based Launderable Recyclable via TerraCycle®

PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

AMERICAS: +1 (800) 262-5755 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | www.pipglobalsafety.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED. 2024-02-22



SKU Information

SKU	COLOR	SIZE	UPC	UPC (INNER)	UPC (CASE)
25GS	Clear	S	616314277962	10616314277969	20616314277966
25GM	Clear	M	616314277955	10616314277952	20616314277959
25GL	Clear	L	616314277948	10616314277945	20616314277942
25GXL	Clear	XL	616314277979	10616314277976	20616314277973