

**B-Series** Jaws are hardened and ground for semi-flush cutting of mild wire. Cutting edges are parallel with axis of housing actuator.

**D-Series** Semi-flush cutter set at an angle to allow access to vertical screws, wires, etc.

**S-Series** Designed expressly for copper cable.

# Wire Cutter

## Wire Cutting Jaws



**B-31CH**



**B-32CH**



**B-33CH**



**B-35**



**B-38**



**D-31**



**D-33**



**D-4-D2**

Model	B-31CH	B-32CH	B-33CH	B-35	B-38	D-31	D-33	D-4-D2	SA-2000
Maximum Mild Wire	0.25" (6.35mm)	0.25" (6.35mm)	0.25" (6.35mm)	0.25" (6.35mm)	0.25" (6.35mm)	0.25" (6.35mm)	0.25" (6.35mm)	0.25" (6.35mm)	5/8" Copper Cable
Housing Length	4.18" (149.9mm)	4.18" (149.9mm)	4.18" (149.9mm)	4.18" (149.9mm)	4.18" (149.9mm)	4.18" (149.9mm)	4.18" (149.9mm)	4.18" (149.9mm)	4.18" (149.9mm)
Weight	1.5 lb (680.4g)	1.375 lb (623.7g)	1.5 lb (680.4g)	1.375 lb (623.7g)	1.375 lb (623.7g)	1.3125 lb (595.3g)	1.3125 lb (595.3g)	1.3125 lb (595.3g)	1.125 lb (510.3g)
Diameter	1.72" (43.69mm)	1.72" (43.69mm)	1.72" (43.69mm)	1.72" (43.69mm)	1.72" (43.69mm)	1.72" (43.69mm)	1.72" (43.69mm)	1.72" (43.69mm)	1.72" (43.69mm)
Length of Cut	1.6" (40.64mm)	1.04" (26.42mm)	1.6" (40.64mm)	0.75" (19.10mm)	0.93" (23.62mm)	0.43" (10.92mm)	0.86" (21.84mm)	0.74" (18.75mm)	N/A
Maximum tip opening	0.68" (17.27mm)	0.49" (12.45mm)	0.68" (17.27mm)	0.31" (7.91mm)	0.38" (9.53mm)	0.31" (7.81mm)	0.62" (15.63mm)	0.43" (10.94mm)	0.44" (11.18mm)
Cutting Edge/Angle	Side Cut	Side Cut	Center Cut	Center Cut	Side Cut	45°	25°	25°	45°



**SA-2000**



### Custom

Simonds pride goes into every jaw set we make. Made from tool steel blanks, we hand-grind our jaws in-house which allows Simonds the ability to make the perfect tool that solves your problem. Simonds Customs are one of our most popular options.

248 Elm Street,  
Southbridge, MA 01550 USA

**SIMONDS**

Revolutionary American Tools



(508) 764-3235 | [info@simonds.tools](mailto:info@simonds.tools)  
<https://www.simonds.tools>