


# Active Probes

## TAP2500 • TAP3500 Datasheet



### Features & Benefits

- Outstanding Electrical Performance
  - High Probe Bandwidth
  - Fast Probe Rise Time
  - Excellent Signal Fidelity
  - $\leq 0.8$  pF Input Capacitance
  - 40 k $\Omega$  Input Resistance
  - -4 V to +4 V Input Dynamic Range
  - -10 V to +10 VDC Input Offset Range
  - $\pm 30$  V (DC + peak AC) Max Input Voltage (Nondestruct)
- Versatile Mechanical Performance
  - Small Compact Probe Head for Probing Small Geometry Circuit Elements
  - DUT Attachment Accessories Enable Connection to SMDs as Small as 0.5 mm Pitch
  - Robust Design for Reliability

- Easy-to-Use
  - Connects Directly to Oscilloscopes with the TekVPI™ Probe Interface
  - Provides Automatic Units Scaling and Readout on the Oscilloscope Display
  - Easy Access to Oscilloscope Probe Menu Display for Probe Status/Diagnostic Information and to Control Probe DC Offset
  - Remote GPIB/USB Probe Control through the Oscilloscope

### Applications

- Verification, Debug, and Characterization of High-speed Designs
- Signal Integrity, Jitter, and Timing Analysis
- Manufacturing Engineering and Test
- Signals with Voltage Swings up to 8 V<sub>pk-pk</sub>

Selecting the right probe for your application is key to attaining the best signal fidelity in your measurements. Active probes provide truer signal reproduction and fidelity for high-frequency measurements. With our ultra-low input capacitance and unique interface, the TAP2500 and TAP3500 Single-ended Active FET probes provide excellent high-speed electrical and mechanical performance required for today's digital system designs.

Specifically designed for use and direct connection to oscilloscopes with the TekVPI™ probe interface, the TAP2500 and TAP3500 Active FET probes achieve high-speed signal acquisition and measurement fidelity by solving three traditional problems:

- Lower DUT loading effects with  $\leq 0.8$  pF input capacitance and 40 k $\Omega$  input resistance
- Versatile DUT connectivity for attaching to small SMDs
- Preserves instrument bandwidth at the probe tip for up to 3.5 GHz oscilloscopes

## Characteristics

**Bandwidth (Probe only)** –

≥2.5 GHz (TAP2500).

≥3.5 GHz (TAP3500).

**Attenuation (Probe only)** – 10:1.

**Rise Time (Probe only)** –

<140 ps (TAP2500).

<130 ps (TAP3500).

**Input Capacitance** – ≤0.8 pF.

**Input Resistance** – 40 kΩ.

**Input Dynamic Range** – –4 V to +4 V.

**Input Offset Range** – –10 V to +10 V.

**Max Input Voltage (Nondestruct)** – ±30 V (DC + peak AC).

**Propagation Delay** – 5.3 ns.

## Physical Characteristics

Dimensions	mm	in.
Width	7.6	0.30
Height	7.6	0.30
Depth	57.2	2.25
Cable Length	1300	51
Weight	kg	lb.
Net	0.091	0.2 (probe only, using ME lab scale)

## Power Requirements

TAP2500 and TAP3500 are powered directly by oscilloscopes with the TekVPI™ probe interface.

## Recommended Oscilloscopes

Oscilloscopes with the TekVPI™ probe interface.

**Note:** For best probe support, download and install the latest version of the oscilloscope software from [www.tektronix.com](http://www.tektronix.com)

## Environmental

**Temperature** –

Operating: 0 °C to +50 °C.

Nonoperating: –40 °C to +71 °C.

**Humidity** –

Operating: 5% to 95% Relative Humidity (RH) at up to +30 °C; 5% to 85% RH above +30 °C up to +50 °C; noncondensing.

Nonoperating: 5% to 95% Relative Humidity (RH) at up to +30 °C; 5% to 85% RH above +30 °C up to +75 °C; noncondensing.

**Altitude** –

Operating: Up to 4,400 m (15,000 ft.).

Nonoperating: Up to 12,192 m (40,000 ft.).

## Regulatory

**Emissions Compliance** – EN 55011, Class A.

**Compliance Labeling** –

C-Tick (Australia / New Zealand)

CE (European Union)

WEEE (European Union)

## Ordering Information

### TAP2500

2.5 GHz Active Probe.

### TAP3500

3.5 GHz Active Probe.

Description	Qty with TAP2500 and TAP3500	Reorder Part Number (Qty)
Y-lead Adapter (2 each) and 3 in. ground lead (3 each)	1 set	196-3456-xx (1 set)
Micro CKT Test Tip	2 each	206-0569-xx (1 ea)
Customizable Ground Lead (set of 5)	1 set	196-3482-xx (1 set)
Color Band Kit (5 colored pairs)	1 set	016-1315-xx (1 set)
Pogo Pin Ground (set of 10)	1 set	016-1772-10 (1 set)
Square Pin Socket (set of 10)	1 set	016-1773-10 (1 set)
Push-in Probe Tip (set of 10)	1 set	131-5638-11 (1 set)
Right-angle Adapter (set of 10)	1 set	016-1774-xx (1 set)
SureToe™ Adapter (set of 4)	1 set	131-6254-xx (1 set)
Antistatic Wrist Strap	1 each	006-3415-xx (1 ea)
Nylon Carrying Case	1 each	016-1952-xx (1 ea)
Plastic Accessory Case	1 each	006-7164-xx (1 ea)
Instruction Manual	1 each	071-xxxx-xx (1 ea)

## Optional Accessories

Description	Package Quantity	Ordering Part Number
IC Micro Grabber	2	013-0309-xx
SMA-to-Probe Tip Adapter	1	015-0678-xx
TekVPI Calibration Fixture (for PV)	1	067-1701-xx

## Manual Language Options

Opt. L5 – Japanese instruction manual.

Opt. L7 – Simplified Chinese instruction manual.

## Service Options

Opt. C3 – Calibration Service 3 years.

Opt. C5 – Calibration Service 5 years.

Opt. D1 – Calibration Data Report.

Opt. D3 – Calibration Data Report 3 Years (with Opt. C3).

Opt. D5 – Calibration Data Report 5 Years (with Opt. C5).

Opt. R3 – Repair Service 3 Years.

Opt. R5 – Repair Service 5 Years.

Opt. SILV900 – Standard Warranty Extended to 5 Years.



Tektronix is registered to ISO 9001 and ISO 14001 by SRI Quality System Registrar.

**Contact Tektronix:**

- ASEAN / Australasia** (65) 6356 3900
- Austria** 00800 2255 4835\*
- Balkans, Israel, South Africa and other ISE Countries** +41 52 675 3777
- Belgium** 00800 2255 4835\*
- Brazil** +55 (11) 3759 7627
- Canada** 1 800 833 9200
- Central East Europe and the Baltics** +41 52 675 3777
- Central Europe & Greece** +41 52 675 3777
- Denmark** +45 80 88 1401
- Finland** +41 52 675 3777
- France** 00800 2255 4835\*
- Germany** 00800 2255 4835\*
- Hong Kong** 400 820 5835
- India** 000 800 650 1835
- Italy** 00800 2255 4835\*
- Japan** 81 (3) 6714 3010
- Luxembourg** +41 52 675 3777
- Mexico, Central/South America & Caribbean** 52 (55) 56 04 50 90
- Middle East, Asia, and North Africa** +41 52 675 3777
- The Netherlands** 00800 2255 4835\*
- Norway** 800 16098
- People's Republic of China** 400 820 5835
- Poland** +41 52 675 3777
- Portugal** 80 08 12370
- Republic of Korea** 001 800 8255 2835
- Russia & CIS** +7 (495) 7484900
- South Africa** +41 52 675 3777
- Spain** 00800 2255 4835\*
- Sweden** 00800 2255 4835\*
- Switzerland** 00800 2255 4835\*
- Taiwan** 886 (2) 2722 9622
- United Kingdom & Ireland** 00800 2255 4835\*
- USA** 1 800 833 9200

\* European toll-free number. If not accessible, call: +41 52 675 3777

Updated 10 February 2011

**For Further Information.** Tektronix maintains a comprehensive, constantly expanding collection of application notes, technical briefs and other resources to help engineers working on the cutting edge of technology. Please visit [www.tektronix.com](http://www.tektronix.com)



Copyright © Tektronix, Inc. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies.

26 Jul 2012

51W-19044-7

