

RB Series

Anti-Static Rubber Bands

Anti-Static rubber bands are use to bundle and protect ESD sensitive IC tubes, trays, boxes and carriers quickly and safely.

- Vulcanized Natural Rubber
- Surface Resistivity: 10^9 ohms/sq
- Static Decay Rate: Less then 2 sec
- ESD Shelf Life: Approximately one year

Meets or exceeds requirements of ANSI ESD-S20.20.


Specifications:

Surface Resistivity:	10^9 ohms/sq
Surface Decay:	Less than 2 seconds
Lead:	<6.45 PPM
Cadmium:	<1.25 PPM
Mercury:	<0.95 PPM
Chromium Hexavalent:	<1.84 PPM

Part Numbers:

Item No.	Description	Approx # Per Bag*
TTRB1	Anti-Static Rubber Band - 6.25"x1/4"	200
TTRB2	Anti-Static Rubber Band - 4.75"x1/8"	475
TTRB3	Anti-Static Rubber Band - 6.25"x1/8"	30
TTRB4	Anti-Static Rubber Band - 4.00"x1/8"	600
TTRB5	Anti-Static Rubber Band - 4.75"x1/4"	300
TTRB6	Anti-Static Rubber Band - 3.00"x1/16"	1200
TTRB7	Anti-Static Rubber Band - 4.75"x1/4"	350
TTRB8	Anti-Static Rubber Band - 7.50"x1/4"	150
TTRB10	Anti-Static Rubber Band - 4.50"x1/2"	175

*Minimum order of 4 bags

This document is prepared for our customers as a service, and is to the best of our knowledge true and accurate. However, it is understood and agreed by the users of this document that we will accept no liability for the conclusions reached. Users of this document may therefore wish to perform additional testing before determining that products mentioned are suitable.