



<https://wearwell.com/>

## Electrically Conductive, Smooth

### Group 786-SM

Electrically Conductive Anti-Fatigue effectively protects sensitive and dramatically reduces fatigue.

- "Best" sponge base

NSFI Certified

- Nitricell sponge base delivers 2X the resilience and 3X the life of typical sponges

- Available in Smooth and Diamond Plate surface pattern
- Lay-flat design and up to 20% more standing area than look-alikes
- Overall thickness, Standard 9/16" or UltraSoft 15/16"

◦ Grounding snap is attached to the corner of each mat (NOTE: Mat must be grounded with a ground cord; workers must wear Heel Grounder or shoes with conductive soles)

**Wearwell Categories** Anti-Fatigue Matting

**Suitable Environment** Dry Floors

**Customization Options** C3 - Full Custom (Length, Width, Shape)

**Solid or Drainage** Solid

**Material** PVC Surface With Nitrile Infused Sponge

**Recycled** <10%

**Warranty** 1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	ASTM D 3884 / 1% loss
Temperature Range	10 to 140 F
Coefficient of Friction	ASTM F1677 / Dry: COF = .68 / Wet COF = .17
Compression Deflection	ASTM D575 - 9/16 = 7.1psi @ 25% = .15" distance compressed and 15/16 = 6.2psi @ 25% = .24" distance compressed
Tear Strength	Not Available
ESD Rating	EOS/ESD S7.1: $1 \times 10^3$ - $1 \times 10^6$ (meets ANSI/ESD 20.20 requirements)
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
786.1516x2x3SMBK	715411220762	Black	15/16 In. (24 mm)	2' x 3'	Y	EA
786.1516x3x5SMBK	715411220465	Black	15/16 In. (24 mm)	3' x 5'	Y	EA
786.1516x3x75SMBK		Black	15/16 In. (24 mm)		N	RL
786.1516x4x75SMBK		Black	15/16 In. (24 mm)		Y	EA
786.916x2x3SMBK	715411607099	Black	9/16 In. (14 mm)	2' x 3'	Y	EA
786.916x3x5SMBK	715411603558	Black	9/16 In. (14 mm)	3' x 5'	Y	EA
786.916x3x75SMBK	715411609680	Black	9/16 In. (14 mm)	3' x 75'	N	RL

786.916x4x75SMBK		Black	9/16 In. (14 mm)		Y		EA
------------------	--	-------	------------------	--	---	--	----