

CURRENT MEASUREMENT PROBES

MR SERIES AC/DC CURRENT PROBES

MODELS MR415 / 416 / 525 / 526

General Purpose Hall Effect Current Probes for use with DMMs, Data Loggers and Power Analyzers



MR415

MR416

MR525

MR526

SPECIFICATIONS

MODELS	MR415	MR416	MR525	MR526
ELECTRICAL				
Current Range	0.5 to 400A _{AC} , 600A _{DC}	0.5 to 40A _{AC} , 60A _{DC} 0.5 to 400A _{AC} , 600A _{DC}	0.5 to 1000A _{AC} , 1400A _{DC}	0.5 to 100A _{AC} , 150A _{DC} 0.5 to 1000A _{AC} , 1400A _{DC}
Output Signal	1mV/A	10mV/A, 1 mV/A	1mV/A	10mV/A, 1mV/A
Frequency Range	DC to 30kHz (-3dB) (depending of current value)			
Phase Shift At 50/60Hz	≤1.5°@ 400A	≤2.2°@ 40A ≤1.5° @ 400A	≤1.5°@ 800A	≤2°@ 100A ≤1.5° @ 800A
Load Impedance	>1MΩ and ≤100pF			
Overload	3000A _{DC} or 1000A _{AC} continuous for < 1kHz			
Zero Adjust	Automatic on both ranges			
Power Source	9V Alkaline battery (NEDA 1060A, 6LR61) or 5V DC Micro-USB type B			
Battery Life	50H typical			
Low Battery Indication	Green LED blinking			
Overload Indication	Red LED on when measurement > than selected range			
Output Termination	Double-insulated 5 ft (1.5m) lead with two 4mm safety banana plugs			
MECHANICAL				
Maximum Conductor Size	Cables: (1) 1.18" (30mm) or (2) .94" (24mm) Bus Bar: (1) 1.97 x 0.39" (50 x 10mm) or (2) 1.23 x 0.39" (31.5 x 10mm) or (3) 0.98 x 0.31" (25 x 8mm)		Cables: (1) 1.5" (39mm) or (2) 1" (25.4mm) Bus Bar: (1) 1.97 x 0.49" (50 x 12.5mm) or (2) 0.98 x 0.2" (25 x 5mm); (1) 1.24 x 0.30" (31.5 x 10mm) or (3) 0.98" x 0.31" (25 x 8mm)	
Dimensions (H x W x D)	8.82 x 3.82 x 1.73" (224 x 97 x 44mm)		9.31 x 3.82 x 1.73" (236.5 x 97 x 44mm)	
Weight (with Battery)	0.98lbs (440g)		1.15lbs (520g)	
ENVIRONMENTAL				
Operating Temperature	14° to +131°F (-10 to +55°C)			
Storage Temperature	-40° to +176°F (-40 to +80°C)			
Relative Humidity	Up to 85% @ 35°C			
SAFETY				
Ingress Protection	IP 40			
EMC	EN 61326-1			
Safety Rating	IEC 61010-1, EN 61010-2-32, Pollution Degree 2, 600V CAT III			



FEATURES

- The jaw shape enables users to clamp on to cables or small bus bars
- Powered by battery or standard external 5V power source via micro-USB connector
- Measures up to 1000A_{AC} and 1400A_{DC} (model dependent)
- Automatic Zero DC reset function
- Auto Power Off enable/disable function
- Millivolt output compatible with most equipment and instruments
- Battery life up to 50 hours
- Safety rating 600V CATIII







4mm Banana Plug Terminals

Consult factory for NIST Calibration prices

CATALOG NO.	DESCRIPTION
1200.80	AC/DC Current Probe Model MR415 (400A _{AC} , 1mV/A & 600A _{DC} , 1mV/A, 4mm Banana Plug Lead) - Replaces MR410
1200.82	AC/DC Current Probe Model MR416 (40A _{AC} , 60A _{DC} , 10mV/A & 400A _{AC} , 600A _{DC} , 1mV/A, 4mm Banana Plug Lead) - Replaces MR411
1200.81	AC/DC Current Probe Model MR525 (1000A _{AC} , 1mV/A & 1400A _{DC} , 1mV/A, 4mm Banana Plug Lead) - Replaces MR520
1200.83	AC/DC Current Probe Model MR526 (100A _{AC} , 150A _{DC} , 10mV/A & 1000A _{AC} , 1400A _{DC} , 1mV/A, 4mm Banana Plug Lead) - Replaces MR521

CURRENT MEASUREMENT PROBES

GENERAL PURPOSE PROBES SELECTION CHART





Series	Model	Ratio	Measurement Range		Output Signal		Phase Shift**	Maximum Conductor Size		Output Connection	Catalog No.			
			AC	DC	Current	Voltage		Ø Cable	Bus Bar					
	MN01	1000:1	2 to 150A	-	1mA/A*	-	N/A	0.39" (10mm)	-	Leads	2129.17			
	MN02		50mA to 100A 50mA to 90A			-					2129.20			
	MN03	2 to 100A	-		1mV/A	2129.18								
	MN05	-	5mA to 10A 1 to 100A		-	1mV/A 1mV/A					2129.19			
	MN103	-	1mA to 10A 1 to 100A		-	1mV/A 1mV/A					1031.02			
	MN106	1000:1	2 to 150A		1mA/A	-	<10°	0.47" (12mm)	-	-	1031.17			
	MN114	-	1mA to 10A		-	100mV/A	<8°				2110.71			
	MN185	-	50mA to 120A		1mA/A	-	<3.5°				Jacks	100.185		
	MN213	1000:1			1mA/A*	-	<2.5°	N/A	-	Leads	2115.75			
	MN251	-	0.5 to 240A		-	1mV/A					2115.77			
MN253				-	10mV/A	2115.79								
MN255	-	0.1 to 24A 0.1 to 240A		-	100mV/A 10mV/A	2115.81								
MN291	-	0.5 to 240A		-	100mVdc/Aac	N/A	2115.84							
MN307	-	10mA to 12A		-	100mV/A		2116.23							
MN312	1000:1	0.1 to 200A		1mA/A*	-	<2.5°	0.78" (19.8mm)				-	-	Jacks	2116.24
MN313				-									Leads	2116.25
MN352	-	0.1 to 150A		-	10mV/A								Jacks	2116.26
MN353				-		2116.27								
MN373	-	0.01 to 2.4A 0.1 to 200A		-	1000mV/A 10mV/A	<3°			2116.28					
MN375			0.1 to 10A		-	100mV/A			2115.41					
MN379			5mA to 6A 0.1 to 120A		-	200mV/A 10mV/A		<1.5°	2153.01					
	SL206		10mA to 1.5A 50mA to 60A	10mA to 2A 50mA to 80A	-	1mV/mAac/dc 10mV/Aac/dc		<1°	0.46" (11.8mm)				Leads	1201.45
	MD301	1000:1	2 to 500A		-	1mVdc/Aac		N/A	1.18" (30mm) 2 x 500kcmil	2.48 x 0.20" (63 x 5mm)			-	1201.07
	MD305		1 to 600A		1mA/A*	-		<1°						1201.36

*Output Protection for open secondary
 **Phase shift indicated at maximum rating

Note: Models MN103, MN106, MN114 & MN185 are not CE compliant. MN200 & MN300 series are UL approved except MN379.
 Consult factory for NIST Calibration price.

CURRENT MEASUREMENT PROBES

GENERAL PURPOSE PROBES SELECTION CHART

SERIES	MODEL	RATIO	MEASUREMENT RANGE		OUTPUT SIGNAL		PHASE SHIFT**	MAXIMUM CONDUCTOR SIZE		OUTPUT CONNECTION	CATALOG NO.
			AC	DC	CURRENT	VOLTAGE		Ø CABLE	BUS BAR		
	MR415	-	0.5 to 400A	0.5 to 600A	-	1mV/A	≤1.5°	1.18" (30mm)	2 bus bar 1.24 x 0.39" (31.5 x 10mm)	5 ft (1.5m) Lead	1200.80
	MR416		0.5 to 40A 0.5 to 400A	0.5 to 60A 0.5 to 600A		10mV/A 1mV/A	≤2.2° ≤1.5°				1200.82
	MR525		0.5 to 1000A	0.5 to 1400A		1mV/A	≤1.5°	1200.81			
	MR526		0.5 to 100A 0.5 to 1000A	0.5 to 150A 0.5 to 1400A		10mV/A 1mV/A	≤2° ≤1.5°	1.53" (39mm)	2 bus bar 1.96 x 0.19" (50 x 5mm)		1200.83
	SR600	1000:1	0.1 to 1000A	-	1mA/A	-	<0.5°	2.05" (52mm)	1.96 x 0.19" (50 x 5mm)	Jacks	2113.42
	SR601				1mA/A*					2113.43	
	SR604				1mA/A*					Leads	2113.44
	SR634	250:5 500:5 1000:5	1 to 250A 1 to 500A 1 to 1000A	20mA/A 10mA/A 5mA/A*	<1°	Jacks	2113.48				
	SR651	-	0.1 to 1000A	-	1mV/A	<0.5°	Jacks			2113.45	
	SR701	1000:1	1mA to 1000A	-	1mA/A*	-	<0.7°			2116.29	
	SR704									2116.30	
	SR752	0.1 to 1000A	1mV/A	Leads	2116.32						
	SR759	1mA to 1A 10mA to 10A 0.1 to 100A 1 to 1000A	1000mV/A 100mV/A 10mV/A 1mV/A	<1°	2116.33						
	K100	-	0.1mA to 3A	0.05mA to ±4A	1mV/mA	N/A	0.18" (4.5 mm)	N/A	Plugs	1200.67	
	K110		0.1mA to 300mA	0.05mA to ±450mA	10mV/mA					2111.73	
	LM102	1000:1	50mA to 200A	-	1mA/A*	-	<3°	0.63" (16 mm)	Leads	2153.04	
	LM103	-	0.1 to 200A	-	-	1mV/A				2153.05	

*Output Protection for open secondary

**Phase shift indicated at maximum rating

Note: All SR probes listed on this chart are UL approved, however not all SR series probes are UL approved; please consult factory. Consult factory for NIST Calibration price.



OUTPUT TERMINATIONS

Lead with BNC

Insulated 6.5 ft (2m) coaxial cable with insulated BNC connector rated 600Vrms



Jacks

Two standard safety banana jacks (4mm)



Leads

Double/reinforced 5 ft (1.5m) leads with 4mm safety banana plug







Shrouded Banana Plugs

Two 4mm safety banana plugs; standard 3/4" (19mm) spacing










AMPFLEX® AND MINIFLEX® PROBES - SELECTION CHARTS

SERIES	MODEL	RATIO	MEASUREMENT RANGE	OUTPUT SIGNAL	MAXIMUM CONDUCTOR SIZE	CATALOG NO.
	MF 300-6-2-10-HF	—	30A / 300A	100mV/A, 10mV/A	1.77" (45mm)	2126.83
	MF 300-10-2-10-HF	—			2.95" (70mm)	2126.84
	MA114	—	3A / 30A / 300A / 3000A	1mV/mA, 100mV/A 10mV/A, 1mV/A	4" (101mm)	2153.41
	300-24-2-10	—	30A / 300A	100mV/A, 10mV/A	7.48" (190mm)	2112.88
	1000-24-1-1	—	1000A	1mV/A		2112.39
	1000-24-2-1	—	100A / 1000A	10mV/A, 1mV/A	11" (290mm)	2112.98
	1000-36-2-1	—			11" (290mm)	2113.00
	3000-24-1-1	—	3000A	1mV/A	7.48" (190mm)	2112.46
	3000-36-1-1	—			11" (290mm)	2112.48
	3000-24-2-1	—	300A / 3000A	10mV/A, 1mV/A	7.48" (190mm)	2113.05
	3000-36-2-1	—			11" (290mm)	2112.00
	3000-48-2-1	—			15" (390mm)	2112.01
	6000-36-2-0.1	—	600A / 6000A	1mV/A, 0.1mV/A	11" (290mm)	2113.21
30000-24-2-0.1	—	3000A / 30,000A	2113.33			
	24-3001	—	300A / 3000AAC	10mV/A, 1mV/A	7.48" (190mm)	2120.81

Consult factory for NIST Calibration price

OSCILLOSCOPE & BNC TERMINATED PROBES

MODEL	MEASUREMENT RANGE		OUTPUT SIGNAL VOLTAGE	PHASE SHIFT*	MAXIMUM CONDUCTOR SIZE		OUTPUT CONNECTION
	AC	DC			Ø CABLE	BUS BAR	
 SL261	100mA to 10A 1 to 100A		100mV/A 10mV/A	<1.5°	0.46" (11.8mm)	N/A	6.6 ft (2m) Lead w/BNC
 MN261	0.1 to 24A 0.5 to 240A	—		<2.5°	0.78" (19.8mm)		
 SR661	0.1 to 12A 0.1 to 120A 1 to 1200A		<1°	2.05" (52mm)	1.96 x 0.19" (50 x 5mm)		
 MN251T MN379T	0.5 to 240A		1mV/A	<2.5°	0.78" (20mm)	0.78" (20mm)	10 ft (3m) Lead w/BNC
	0.005 to 6A	200mV/A	<4°				
	0.1 to 120A	10mV/A	<2.2°				
 MH60	0.5 to 100A	0.5 to 100A	10mV/A	<1°	1.02" (26mm)	N/A	6.6 ft (2m) Lead w/BNC
 MR417	0.5 to 40A 0.5 to 400A	0.5 to 60A 0.5 to 600A	10mV/A 1mV/A	≤2.2° ≤1.5°	1.18" (30mm)	2 bus bar 1.24 x 0.39" (31.5 x 10mm)	
 MR527	0.5 to 100A 0.5 to 1000A	0.5 to 150A 0.5 to 1400A		≤2.2° ≤1.5°	1.53" (39mm)	2 bus bar 1.96 x 0.19" (50 x 5mm)	

*Phase shift indicated at maximum rating. Note: All probes are rated 600V CAT III and CE compliant. Not all models are UL approved; please consult factory. Consult factory for NIST Calibration price.