

CURRENT MEASUREMENT PROBES

SR SERIES CURRENT PROBES

SR600 SERIES

Current probes well-suited for power applications where high accuracy and low phase shift is important



SR601

SPECIFICATIONS

MODELS	SR600	SR601	SR604	SR634	SR651	SR661	
ELECTRICAL							
Nominal Range	1000AAC			250, 500, 1000AAC	1000AAC	10, 100, 1000AAC	
Measurement Range	0.1 to 1200AAC						
Transformation Ratio	1000: 1			250:5, 500:5, 1000:5	Voltage Output	Voltage output	
Output Signal	1mA/A (1AAC @ 1000A)			20mA; 10mA; 5mA/A (5AAC @ 250; 500; 1000A)	1mV/A (1VAc @ 1000A)	100mV; 10mV; 1mV/A (1VAc @10, 100 1000A)	
Phase Shift	10A: 3° 50A: 1.5° 200A: 0.75° 1000A: 0.5° 1200A: 0.5°			(250A Range) 12.5A: 10°; 50A: 10°; 250A: 10°; 300A: 10° (500A Range) 10A: 6°; 25A: 4°; 100A: 3°; 500A: 2.5°; 600A: 2.5° (1000A Range) 20A: 5°; 50A: 3°; 200A: 1.5°; 1000A: 1°; 1200A: 1°	10A: 3° 50A: 1,5° 200A: 0,75° 1000A: 0,5° 1200A: 0,5°	(10A Range) 10A: ≤15° (100A Range) 20A: ≤15° 100A: ≤10° 120A: ≤5° (1000A Range) 200A: ≤3° 1000A: ≤2° 1200A: ≤1	
Overload	1200A for 40 min ON, 20 min OFF			1200A for 30 min ON, 15 min OFF	1200A for 40 min ON, 20 min OFF		
Frequency Range				30Hz to 5kHz*		10Hz to 100kHz*	
Load Impedance	5Ω max			0.4Ω max	100kΩ min	1MΩ min	
Working/Common Mode Voltage	600V CAT III						
Output Surge Protection	No	30V peak				N/A	
Output Termination	Two 4mm safety banana jacks	Lead with plugs	Two 4mm safety banana jacks				6.5 ft (2m) coaxial cable with BNC terminal
MECHANICAL							
Jaw Opening	2.25" (57mm) max						
Maximum Conductor Size	2.05" (52mm)						
Maximum Bus Bar Size	One 1.95 x 0.19" (50 x 5mm)						
Dimensions	4.37 x 8.50 x 1.77" (111 x 216 x 45mm)						
Weight	1.21 lbs (550g)						
Material	Polycarbonate UL 94						
ENVIRONMENTAL							
Operating Temperature	14° to 122°F (-10° to 50°C)						
Storage Temperature	-4° to 158°F (-20° to 70°C)						
Operating Relative Humidity	0 to 85% decreasing linearly above 95°F (35°C)						
SAFETY							
Electrical	EN 61010-2-32, 600 V CAT III						
UL Approval	Yes - Canada and United States						
Double Insulation	Yes						
CE Mark	Yes						

FEATURES

- Measurement range of 100mA to 1200Aac
- Large jaw opening accommodates up to two 500kcmil conductors
- Ergonomic design and easy operation
- Low phase shift for power measurements
- Available with mA or mV output signals
- Designed for DMMs, recorders, loggers, oscilloscopes, power and harmonic meters
- UL approved

ACCESSORIES

Catalog #1017.45

4mm Banana plug adaptor (Safety Leads to non-recessed plug)

Catalog #2118.46

Banana (Female)
BNC (Male) Adaptor

*Current derating above 1kHz using the formula: 1000A x 1/F (in kHz)
Consult factory for NIST Calibration prices

CATALOG NO.	DESCRIPTION
2113.42	AC Current Probe Model SR600 (1000A, 1mA/A, Jack)
2113.43	AC Current Probe Model SR601 (1000A, 1mA/A, Lead) L**
2113.44	AC Current Probe Model SR604 (1000A, 1mA/A, Lead) L**
2113.48	AC Current Probe Model SR634 (250A, 20mA/A; 500A, 10mA/A & 1000A, 5mA/A, Jack) L**
2113.45	AC Current Probe Model SR651 (1000A, 1mV/A, Jack)
2113.49	AC Current Probe Model SR661 (10A, 100mV/A; 100A, 10mV/A & 1000A, 1mV/A, BNC)



CURRENT MEASUREMENT PROBES

GENERAL PURPOSE PROBES SELECTION CHART

Series	Model	Ratio	Measurement Range		Output Signal		Phase Shift**	Maximum Conductor Size		Output Connection	Catalog No.	
			AC	DC	Current	Voltage		Ø Cable	Bus Bar			
	MN01	1000:1	2 to 150A	-	1mA/A*	-	N/A	0.39" (10mm)		Leads	2129.17	
	MN02		50mA to 100A 50mA to 90A			-					2129.20	
	MN03	2 to 100A	-		1mV/A	2129.18						
	MN05	5mA to 10A 1 to 100A	-		1mV/A 1mV/A	2129.19						
	MN103	-	1mA to 10A 1 to 100A		-	1mV/A 1mV/A	<10° <8° <3.5°	0.47" (12mm)			Jacks	1031.02
	MN106		1000:1		2 to 150A	1mA/A						-
	MN114	-	1mA to 10A		-	100mV/A						2110.71
	MN185	1000:1	50mA to 120A		1mA/A	-						100.185
	MN213	1000:1	0.5 to 240A	-	1mA/A*	-	<2.5°	0.78" (19.8mm)	N/A	Leads		2115.75
	MN251	-			-	1mV/A						2115.77
	MN253				-	10mV/A						2115.79
	MN255	-			0.1 to 24A 0.1 to 240A	-						100mV/A 10mV/A
	MN291				0.5 to 240A	-					100mVdc/Aac	N/A
	MN307	10mA to 12A			-	100mV/A					2116.23	
	MN312	1000:1	0.1 to 200A		1mA/A*	-	<2.5°			Jacks	2116.24	
	MN313					-				Leads	2116.25	
	MN352	-	0.1 to 150A		-	10mV/A	Jacks			2116.26		
	MN353				-		Leads			2116.27		
	MN373	-	0.01 to 2.4A 0.1 to 200A		-	1000mV/A 10mV/A				<3°	2116.28	
	MN375		0.1 to 10A		-	100mV/A				<1.5°	2115.41	
	MN379		5mA to 6A 0.1 to 120A		-	200mV/A 10mV/A					2153.01	
		SL206			10mA to 1.5A 50mA to 60A	10mA to 2A 50mA to 80A	-			1mV/mAac/dc 10mV/Aac/dc	<1°	0.46" (11.8mm)
	MD301	1000:1	2 to 500A	-	-	1mVdc/Aac	N/A	1.18" (30mm) 2 x 500kcmil	2.48 x 0.20" (63 x 5mm)		1201.07	
	MD305		1 to 600A		1mA/A*	-	<1°			1201.36		

*Output Protection for open secondary

**Phase shift indicated at maximum rating

Note: Models MN103, MN106, MN114 & MN185 are not CE compliant. MN200 & MN300 series are UL approved except MN379.

Consult factory for NIST Calibration price.

CURRENT MEASUREMENT PROBES

GENERAL PURPOSE PROBES SELECTION CHART

Series	Model	Ratio	Measurement Range		Output Signal		Phase Shift**	Maximum Conductor Size		Output Connection	Catalog No.		
			AC	DC	Current	Voltage		Ø Cable	Bus Bar				
	MR415	—	0.5 to 400A	0.5 to 600A	—	1mV/A	≤1.5°	1.18" (30mm)	2 bus bar 1.24 x 0.39" (31.5 x 10mm)	5 ft (1.5m) Lead	1200.80		
	MR416		0.5 to 40A 0.5 to 400A	0.5 to 60A 0.5 to 600A		10mV/A 1mV/A	≤2.2° ≤1.5°				1200.82		
	MR525		0.5 to 1000A	0.5 to 1400A		1mV/A	≤1.5°	1.53" (39mm)	2 bus bar 1.96 x 0.19" (50 x 5mm)		1200.81		
	MR526		0.5 to 100A 0.5 to 1000A	0.5 to 150A 0.5 to 1400A		10mV/A 1mV/A	≤2° ≤1.5°				1200.83		
	SR600	1000:1	0.1 to 1000A	—	1mA/A	—	<0.5°	2.05" (52mm)	1.96 x 0.19" (50 x 5mm)	Jacks	2113.42		
	SR601				1mA/A*					Jacks	2113.43		
	SR604				1mA/A*					Leads	2113.44		
	SR634	250:5 500:5 1000:5	1 to 250A 1 to 500A 1 to 1000A		20mA/A 10mA/A 5mA/A*	<1°	Jacks			2113.48			
	SR651	—	0.1 to 1000A		—	1mV/A				<0.5°	2113.45		
	SR701	1000:1	1mA to 1000A		1mA/A*	—	<0.7°			Jacks	2116.29		
	SR704									2116.30			
	SR752	—	0.1 to 1000A		—	1mV/A	<1°			Leads	2116.32		
	SR759		1mA to 1A 10mA to 10A 0.1 to 100A 1 to 1000A			1000mV/A 100mV/A 10mV/A 1mV/A					2116.33		
	K100	—	0.1mA to 3A	0.05mA to ±4A	—	1mV/mA	N/A	0.18" (4.5 mm)	N/A	Plugs	1200.67		
	K110		0.1mA to 300mA	0.05mA to ±450mA		10mV/mA				2111.73			
	LM102	1000:1	50mA to 200A	—	1mA/A*	—	<3°	0.63" (16 mm)		Leads	2153.04		
	LM103	—	0.1 to 200A		—	1mV/A					2153.05		

*Output Protection for open secondary

**Phase shift indicated at maximum rating

Note: All SR probes listed on this chart are UL approved, however not all SR series probes are UL approved; please consult factory.
Consult factory for NIST Calibration price.



OUTPUT TERMINATIONS

Lead with BNC

Insulated 6.5 ft (2m) coaxial cable with insulated BNC connector rated 600Vrms



Jacks

Two standard safety banana jacks (4mm)



Leads

Double/reinforced 5 ft (1.5m) leads with 4mm safety banana plug



Shrouded Banana Plugs

Two 4mm safety banana plugs; standard ¾" (19mm) spacing



AMPFLEX® AND MINIFLEX® PROBES - SELECTION CHARTS

SERIES	MODEL	RATIO	MEASUREMENT RANGE	OUTPUT SIGNAL	MAXIMUM CONDUCTOR SIZE	CATALOG NO.
	MF 300-6-2-10-HF	—	30A / 300A	100mV/A, 10mV/A	1.77" (45mm)	2126.83
	MF 300-10-2-10-HF	—			2.95" (70mm)	2126.84
	MA114	—	3A / 30A / 300A / 3000A	1mV/mA, 100mV/A 10mV/A, 1mV/A	4" (101mm)	2153.41
	300-24-2-10	—	30A / 300A	100mV/A, 10mV/A	7.48" (190mm)	2112.88
	1000-24-1-1	—	1000A	1mV/A		2112.39
	1000-24-2-1	—	100A / 1000A	10mV/A, 1mV/A		2112.98
	1000-36-2-1	—			11" (290mm)	2113.00
	3000-24-1-1	—	3000A	1mV/A	7.48" (190mm)	2112.46
	3000-36-1-1	—			11" (290mm)	2112.48
	3000-24-2-1	—	300A / 3000A	10mV/A, 1mV/A	7.48" (190mm)	2113.05
	3000-36-2-1	—			11" (290mm)	2112.00
	3000-48-2-1	—			15" (390mm)	2112.01
	6000-36-2-0.1	—	600A / 6000A	1mV/A, 0.1mV/A	11" (290mm)	2113.21
	30000-24-2-0.1	—	3000A / 30,000A			2113.33
	24-3001	—	300A / 3000AAC	10mV/A, 1mV/A	7.48" (190mm)	2120.81

Consult factory for NIST Calibration price

OSCILLOSCOPE & BNC TERMINATED PROBES

MODEL	MEASUREMENT RANGE		OUTPUT SIGNAL	PHASE SHIFT*	MAXIMUM CONDUCTOR SIZE		OUTPUT CONNECTION
	AC	DC			Ø CABLE	BUS BAR	
 SL261	100mA to 10A 1 to 100A		100mV/A 10mV/A	<1.5°	0.46" (11.8mm)	N/A	6.6 ft (2m) Lead w/BNC
 MN261				<2.5°	0.78" (19.8mm)		
 SR661			100mV/A 10mV/A 1mV/A	<1°	2.05" (52mm)	1.96 x 0.19" (50 x 5mm)	
 MN251T MN379T	0.5 to 240A	—	1mV/A	<2.5°	0.78" (20mm)	0.78" (20mm)	10 ft (3m) Lead w/BNC
	0.005 to 6A		200mV/A	<4°			
	0.1 to 120A		10mV/A	<2.2°			
 MH60	0.5 to 100A	0.5 to 100A	10mV/A	<1°	1.02" (26mm)	N/A	6.6 ft (2m) Lead w/BNC
 MR417	0.5 to 40A 0.5 to 400A	0.5 to 60A 0.5 to 600A	10mV/A 1mV/A	≤2.2° ≤1.5°	1.18" (30mm)	2 bus bar 1.24 x 0.39" (31.5 x 10mm)	
 MR527	0.5 to 100A 0.5 to 1000A	0.5 to 150A 0.5 to 1400A		≤2.2° ≤1.5°	1.53" (39mm)	2 bus bar 1.96 x 0.19" (50 x 5mm)	

*Phase shift indicated at maximum rating. Note: All probes are rated 600V CAT III and CE compliant. Not all models are UL approved; please consult factory. Consult factory for NIST Calibration price.