


Standard Features

- **Protection Level:** IP54* / IP65**
- **Technical:**
 - Knockout Sidewalls
 - Tinted Transparent Door
 - Multiple Enclosure Combination Option
- **Enclosure Material:** Polystyrene
- **Door Material:** Polycarbonate
- **Gasket Material:** Polyurethane
- **Temperature Range:** -40°C to 70°C (-40°F to 158°F)
- **Color:** Light Gray
- **Included Accessories:** 35mm DIN Rail, 12 Pole Ground/Neutral Terminal Strip
12 ea. 9mm (0.35 in.) Filler Strips
1 ea. Pg21 & Pg29 Entry Spouts
7 ea. Pg16 Entry Spouts
Label Strip
- **Accessories:** See section below



* With Supplied Entry Spouts
** As Equipped or with Optional IP65 Cable Gland

EK

Ordering Information	Cat. No.	Type	Length	Dimensions mm (in) Width	Height	Std. Pk.
Enclosure	542-412	EK012	180 mm (7.09 in)	254 mm (10.00 in)	110 mm (4.33 in)	1

Accessories

Ordering Information	Cat. No.	Type	Std. Pk.
Key Lock	548-102	KL	1
Terminal	X-583	PE/N Terminal - 12 pole	1

Please refer to pages 106-113 for additional accessories and detailed information.

