


CX SERIES


SPRING TERMINAL BLOCKS

MULTIPLE CONNECTION GROUND / EARTH TERMINAL BLOCKS


CXG4/4



CXG6/3



CXG10/3



Dimensions

Width	6 mm	8 mm	10 mm
Length	86.2 mm	82.2 mm	82.2 mm
Height w DIN Rail 35 x 7.5 mm 35 x 15 mm	38.0 mm 45.5 mm	43.0 mm 50.5 mm	43.0 mm 50.5 mm

Technical Data/Ratings

Approvals						
Wire Size (solid stranded)	24-10 AWG		24-8 AWG		24-6 AWG	
	0.2-4 mm ²		0.2-6 mm ²		0.2-10 mm ²	
Voltage Rating	600 V		600 V		600 V	
	1000 V		1000 V		1000 V	
Current Rating	—		—		—	
Insulation Material	Polyamide 66		Polyamide 66		Polyamide 66	

Installation Instructions

Wire Stripping Length	10 mm	10 mm	18 mm
Screwdriver	0.6x3.5 mm	0.8x4 mm	0.8x4 mm

Terminal Blocks

	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
Yellow / Green	CXG4/4	50	CXG6/3	50	CXG10/3	50

Accessories

End Plate		EPCX4/4	20	EPCX6/3	20	EPCX10/3	20
Partition Plate		PPCX4/4	20	—	—	—	—
DIN Rail		2511120 CA701-15/S	20 20	2511120 CA701-15/S	20 20	2511120 CA701-15/S	20 20
End Stop		CA702 CA802 CA103	50 50 50	CA702 CA802 CA103	50 50 50	CA702 CA802 CA103	50 50 50
Shorting Link/ Jumpers	2 pole 3 pole 4 pole 10 pole 	JX4/2 JX4/3 JX4/4 JX4/10	100 50 50 10	JX6/2 JX6/3 JX6/4 JX6/10	100 50 50 10	JX10/2 — — —	100 — — —
Warning Label		WLX4	100	WLX6	100	WLX10	100
Test Plug		TX4	50	TX6	50	TX10	50
Marking Tag		MT6	100	MT8	100	MT10	100