



MULTIPLE CONNECTION TERMINAL BLOCKS

CX SERIES

SPRING TERMINAL BLOCKS

CX2.5/4P

CX2.5/4(E)D1



CX2.5/4P is a double potential Terminal Block. It allows 2 different voltage potential to be used within the same Terminal Block. One side of the CX2.5/4P can be shorted with the standard JX2.5 series jumpers.

CX2.5/4(E)D1 is a specially designed 4 connection spring Terminal Block. It has a built in Diode (1N4007) for reverse polarity protection and only allows current to flow in one direction.

Dimensions

Width	5 mm	5 mm
Length	74.7 mm	74.7 mm
Height w DIN Rail	35 x 7.5 mm 35 x 15 mm	38.0 mm 45.5 mm

Technical Data/Ratings

Approvals		
Wire Size (solid stranded)	24-12 AWG	0.2-2.5 mm ²
Voltage Rating	600 V	1000 V
Current Rating	20 A	24 A
Insulation Material	Polyamide 66	Polyamide 66

Installation Instructions

Wire Stripping Length	10 mm	10 mm
Screwdriver	0.5x3 mm	0.6x3.5 mm

Terminal Blocks

	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
Grey (standard)	CX2.5/4P	50	CX2.5/4(E)D1	50

Accessories

	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
End Plate	EPCX2.5/4	20	EPCX2.5/4	20
Partition Plate	PPCX4/4	20	PPCX4/4	20
DIN Rail	2511120 CA701-15/S	20 20	2511120 CA701-15/S	20 20
End Stop	CA702 CA802 CA103	50 50 50	CA702 CA802 CA103	50 50 50
Shorting Link/ Jumpers	JX2.5/2 JX2.5/3 JX2.5/4 JX2.5/10	100 50 50 10	JX2.5/2 JX2.5/3 JX2.5/4 JX2.5/10	100 50 50 10
Warning Label	WLX2.5	100	WLX2.5	100
Test Plug	TX2.5	50	TX2.5	50
Marking Tag	MT5	100	MT5	100