

# Enlarger *Polyamide*

**Material:**

- Polyamide glass fiber reinforced

**Characteristics:**

- PG/Metric external thread
- PG/Metric internal thread

External thread	Internal thread	SW mm	Thread length mm	Complete length mm	Cat. No. Light Gray	Std. Pk.
<b>PG 1</b>	<b>PG 2</b>					
PG 7	PG 9	19	7	20	<b>7004200</b>	100
PG 9	PG 11	22	8	23	<b>7004201</b>	100
PG 11	PG 13.5	24	8	23	<b>7004202</b>	100
PG 13.5	PG 16	27	9	26	<b>7004203</b>	100
PG 16	PG 21	32	9	29	<b>7004204</b>	100
PG 21	PG 29	42	10	32	<b>7004205</b>	50
PG 29	PG 36	53	11	35.5	<b>7004206</b>	25
PG 36	PG 42	60	13	40.5	<b>7004207</b>	10
PG 42	PG 48	65	13	41	<b>7004208</b>	10
<b>Metric 1</b>	<b>Metric 2</b>					
M12 x 1.5	M16 x 1.5	20	8	18.5	<b>7004300</b>	50
M16 x 1.5	M20 x 1.5	24	8	20	<b>7004301</b>	50
M20 x 1.5	M25 x 1.5	30	9	22	<b>7004302</b>	50
M25 x 1.5	M32 x 1.5	36	10	24	<b>7004303</b>	20
M32 x 1.5	M40 x 1.5	44	11	26	<b>7004304</b>	20
M40 x 1.5	M50 x 1.5	55	12	28	<b>7004305</b>	20
M50 x 1.5	M63 x 1.5	70	13	31.5	<b>7004306</b>	10



**Temperature Range**  
 -30 to 100°C  
 (-22 to 212°F)